



Cat[®] D3K2, D5K2

SHIPHOLD

The Cat[®] D3K2 and D5K2 Shiphold, equipped with a Two Way Dozer and rear guard, is ideal for shiphold bulk material handling. Lifting eyes located on the blade c-frame and rear guard provide easy lifting of the machine in and out of the shiphold.

OPERATOR STATION

- Spacious cab with generous leg room
- Standard air conditioning with cab option
- Fully adjustable air suspension seat
- Seat mounted joystick controls

HYDROSTATIC TRANSMISSION CONTROL

- Joystick control for intuitive steering, direction and speed control
- Power turn provides optimum maneuverability

UNDERCARRIAGE

- XL configuration – ideal for most material
- LGP configuration – available for material requiring additional machine floatation
- Sealed and Lubricated Track (SALT)
- Slotted track shoes (optional) – reduces material packing

PRODUCTIVITY

- Exceptional maneuverability
- Fast cycle times – quicker ship loading and unloading

BLADE

- Two Way Dozer designed for use in shiphold to move various bulk material
- Inside mounted c-frame provides lift height suitable for pulling material off ship walls
- Blade pitches hydraulically forward or rearward for versatile operation

SERVICEABILITY

- Ground level accessibility
- Grouped service points

LIFTING

- Four lift points provide secure control while lifting machine

GUARDING AND PROTECTION

- Rear guard prevents damage from ship wall contact
- Corrosive protection on key electrical terminals (optional)

OWNING AND OPERATING COSTS

- Low undercarriage cost per hour
- Engine air precleaner (centrifugal) located under hood for longer air filter life
- Extended service intervals
- Low fuel consumption

D3K2, D5K2 Shiphold

Specifications

	D3K2 XL		D5K2 XL	
Operating weight*	8516 kg	18,775 lb	10 226 kg	22,544 lb
Power – Net	59.7 kW	80 hp	77.6 kW	104 hp
Max travel speed – forward	9.0 km/h	5.6 mph	9.0 km/h	5.6 mph
Max travel speed – reverse	10 km/h	6.2 mph	10 km/h	6.2 mph
Overall length with blade	4830 mm	190.2"	4925 mm	193.9"
Width of tractor – no blade	1900 mm	74.8"	2110 mm	83.1"
Blade width	2400 mm	94.5"	2575 mm	101.4"
Tractor height	2763 mm	108.8"	2769 mm	109.0"
Track gauge	1495 mm	58.9"	1600 mm	63.0"
Shoe width – standard	405 mm	15.9"	510 mm	20.1"
Blade height	875 mm	34.4"	950 mm	37.4"
Blade lift height	1580 mm	62.2"	1650 mm	65.0"
Digging depth	588 mm	23.0"	605 mm	23.8"
Blade capacity	1.58 m ³	2.07 yd ³	2.0 m ³	2.62 yd ³
Blade tilt – front	38°		38°	
Blade tilt – rear	30°		30°	

*Includes dozer blade, cab EROPS, operator and fuel.

Meets U.S. EPA Tier 4 Final/EU Stage IV/Japan 2014 emission standards.



For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

AEHQ8109 (01-2018)

© 2018 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

