



FG Wilson  
**Gama de Grupos  
Electrógenos**

“Potenciando una nueva  
generación”

[www.fgwilson.com](http://www.fgwilson.com)

# DATOS TÉCNICOS

Modelo del grupo electrógeno	50 Hz (kVA/kW)		60 Hz (kVA/kW)		Alternador de motor	Depósito de combustible (L)	50 Hz (L/h)		60 Hz (L/h)		L (mm)	An (mm)	Al (mm)	P (kg)
	PR	SB	PR	SB			PR	SB	PR	SB				
P7.5-1S	6.8/ 6.8	7.5/ 7.5	-	-	403A-11G1 FGL10030	-	2.5	2.8	-	-	1550	620	1020	238
P7.5-4S	6.8/ 6.8	7.5/ 7.5	8/ 8	8.8/ 8.8	403D-11G FGL10030	-	2.5	2.8	2.9	3.3	1550	620	1020	238
P9.5-1	8.5/ 6.8	9.5/ 7.6	-	-	403A-11G1 FGL10020	-	2.5	2.8	-	-	1550	620	1020	231
P9.5-4	8.5/ 6.8	9.5/ 7.6	10/ 8	11/ 8.8	403D-11G FGL10020	-	2.7	3.0	2.9	3.3	1550	620	1020	231
P11-6S	10/ 10	11/ 11	12/ 12	13/ 13	403D-15G FGL10030	-	3.6	4.0	4.3	4.8	1550	620	1020	315
P12-1S	11/ 11	12/ 12	-	-	403A-15G2 FGL10030	-	4.0	4.5	-	-	1550	620	1020	315
P13.5-6	12.5/ 10	13.5/ 10.8	15/ 12	16.5/ 13.2	403D-15G FGL10020	-	3.6	4.0	4.3	4.8	1550	620	1020	308
P14-6S	13/ 13	14/ 14	15.5/ 15.5	17/ 17	404D-22G1 FGL10040	-	4.3	4.6	4.8	5.3	1550	620	1020	377
P16-1	14.5/ 11.6	16/ 12.8	-	-	403A-15G2 FGL10040	-	4.3	4.9	-	-	1550	620	1020	335
P16.5-1S	15/ 15	16.5/ 16.5	-	-	404A-22G1 FGL10060	-	5	5.6	-	-	1550	620	1020	385
P16.5-6S	15/ 15	16.5/ 16.5	17.6/ 17.6	19.4/ 19.4	404D-22G FGL10060	-	4.9	5.4	5.8	6.3	1550	620	1020	385
P18-6	16.5/ 13.2	18/ 14.4	20/ 16	22/ 17.6	404D-22G1 FGL10040	-	4.4	4.8	5.3	5.8	1550	620	1020	372
P22-1	20/ 16	22/ 17.6	-	-	404A-22G1 FGL10060	-	5.4	6.1	-	-	1550	620	1020	385
P22-6	20/ 16	22/ 17.6	22.5/ 18	25/ 20	404D-22G FGL10060	-	5.2	5.9	5.8	6.4	1550	620	1020	385
P26-3S	24/ 24	26/ 26	27/ 27	30/ 30	1103A-33G1 FGL20050-M <sup>1</sup> LLB1514J <sup>2</sup>	71	6,9	7,5	8,1	9	1570	760	1229	699
P26-6S	24/ 24	26/ 26	-	-	1103D-33G3 FGL20050-M <sup>1</sup> LLB1514J <sup>2</sup>	71	7,4	7,9	-	-	1570	760	1229	699
P33-3 (skid)	30/ 24	33/ 26.4	33.8/ 27	37.5/ 30	1103A-33G1 LL1514F <sup>2</sup>	-	7.0	7.7	8.1	9.0	1565	860	1081	656
P33-3	30/ 24	33/ 26,4	33,8/ 27	37,5/ 30	1103A-33G1 FGL20030 <sup>1</sup> MJB 160 MB4 <sup>2</sup>	71	6,9	7,7	8,1	9,1	1570	760	1229	712
P33-6	30/ 24	33/ 26,4	-	-	1103D-33G3 FGL20030 <sup>1</sup> MJB 160 MB4 <sup>2</sup>	71	7,4	8,2	-	-	1570	760	1229	712
P40-3S	36/ 36	40/ 40	40/ 40	45/ 45	1103A-33TG1 FGL20080-M <sup>1</sup> LLB1514P <sup>2</sup>	145	10,2	11,4	11,8	13,7	1680	760	1336	779
P40-4S	36/ 36	40/ 40	-	-	1103C-33TG2/3 FGL20080-M <sup>1</sup> LLB1514P <sup>2</sup>	145	10,2	11,3	-	-	1680	760	1336	771
P50-3	45/ 36	50/ 40	50/ 40	56,3/ 45	1103A-33TG1 FGL20060 <sup>1</sup> MJB 200 SB4 <sup>2</sup>	145	10,5	11,7	11,9	13,4	1680	760	1336	810
P50-4	45/ 36	50/ 40	-	-	1103C-33TG2/3 FGL20060 <sup>1</sup> MJB 200 SB4 <sup>2</sup>	145	10,6	11,8	-	-	1680	760	1336	802
P50-5S	45/ 45	50/ 50	55/ 55	60/ 60	1103A-33TG2 FGL30030-M <sup>1</sup> LLB3114D <sup>2</sup>	145	12,6	14,2	15,8	17,3	1680	760	1336	912

# DATOS TÉCNICOS

Modelo del grupo electrógeno	50 Hz (kVA/kW)		60 Hz (kVA/kW)		Alternador de motor	Depósito de combustible (L)	50 Hz (L/h)		60 Hz (L/h)		L (mm)	An (mm)	Al (mm)	P (kg)
	PR	SB	PR	SB			PR	SB	PR	SB				
P55-3	50/40	55/44	56,3/45	62,5/50	1103A-33TG2 FGL20070 <sup>1</sup> MJB 200 SB4 <sup>2</sup>	145	11,6	12,8	13,7	15,2	1680	760	1336	810
P55-4	50/40	55/44	-	-	1104C-44TG2/3 FGL20070 <sup>1</sup> MJB 200 SB4	180	15,9	17,4	-	-	1870	840	1336	864
P55-6S	50/50	55/55	-	-	1104D-44TG2/3 FGL30030-M <sup>1</sup> LLB3114D <sup>2</sup>	180	16,5	18,2	-	-	1870	840	1336	941
P65-5	60/48	65/52	68,8/55	75/60	1103A-33TG2 FGL20080 <sup>1</sup> MJB 200 MA4 <sup>2</sup>	145	13,7	15	16,3	18	1680	760	1336	852
P65-6	60/48	65/52	-	-	1104D-44TG2/3 FGL20080 <sup>1</sup> MJB 200 MA4 <sup>2</sup>	180	16,6	18,3	-	-	1870	840	1336	906
P88-3	80/64	88/70,4	90/72	100/80	1104A-44TG2 FGL30020 <sup>1</sup> MJB 200 LA4 <sup>2</sup>	180	18,2	20,1	21	23,2	1870	840	1333	1002
P88-6	80/64	88/70,4	-	-	1104D-E44TAG1 FGL30020 <sup>1</sup> MJB 200 LA4 <sup>2</sup>	218	20,2	21,7	-	-	1980	890	1398	1135
P90-3S	82/82	90/90	90/90	99,5/99,5	1104C-44TAG2 FGL30100-M <sup>1</sup> LLB3114H <sup>2</sup>	218	22,1	24,3	26	28,8	1980	890	1374	1131
P90-6S	82/82	90/90	-	-	1104D-E44TAG2 FGL30100-M <sup>1</sup> LLB3114H <sup>2</sup>	218	24,2	25,7	-	-	1980	890	1449	1208
P110-3	100/80	110/88	113/90,4	125/100	1104C-44TAG2 FGL30040 <sup>1</sup> MJB 225 MA4 <sup>2</sup>	218	21,7	23,9	26,1	29	1980	890	1317	1132
P110-6	100/80	110/88	-	-	1104D-E44TAG2 FGL30040 <sup>1</sup> MJB 225 MA4 <sup>2</sup>	218	23,8	25,5	-	-	1980	890	1435	1252
P150-5	135/108	150/120	150/120	165/132	1106A-70TG1 FGL30080 <sup>1</sup> MJB 225 LA4 <sup>2</sup>	327	29,9	33,4	33,1	36,7	2450	1010	1554	1428
P165-5	150/120	165/132	169/135	188/150	1106A-70TAG2 FGL30100 <sup>1</sup> MJB 250 MA4 <sup>2</sup>	327	32,4	35,1	37,9	41,6	2450	1010	1554	1566
P165-6	150/120	165/132	-	-	1106D-E70TAG2 FGL30110 <sup>1</sup> MJB 250 MA4 <sup>2</sup>	327	35,2	37,8	-	-	2450	1010	1554	1611
P175-2	160/128	175/140	-	-	1106D-E70TAG3 FGL30110 <sup>1</sup> MJB 250 MA4 <sup>2</sup>	327	36,9	39,7	-	-	2450	1010	1554	1611
P200-3	180/144	200/160	200/160	219/175	1106A-70TAG3 FGL30120 <sup>1</sup> MJB 250 MB4 <sup>2</sup>	394	39,8	43,2	46,5	50,6	2510	1010	1640	1650
P200-6	180/144	200/160	-	-	1106D-E70TAG4 FGL30120 <sup>1</sup> MJB 250 MB4 <sup>2</sup>	394	41,3	45,2	-	-	2510	1010	1640	1624
P220-3	200/160	220/176	-	-	1106A-70TAG4 FGL30120 <sup>1</sup> MJB 250 LA4 <sup>2</sup>	394	45,1	49	-	-	2510	1010	1640	1735

# DATOS TÉCNICOS

Modelo del grupo electrógeno	50 Hz (kVA/kW)		60 Hz (kVA/kW)		Alternador de motor	Depósito de combustible (L)	50 Hz (L/h)		60 Hz (L/h)		L (mm)	An (mm)	Al (mm)	P (kg)
	PR	SB	PR	SB			PR	SB	PR	SB				
P249-5	-	-	225 / 180	250 / 200	1506A-E88TAG2 MJB 250 LA4	528	-	-	49,4	54,3	2662	1071	1818	2056
P250-5	230 / 184	250 / 200	-	-	1506A-E88TAG2 MJB 250 LB4	528	46,9	50,3	-	-	2662	1071	1818	2096
P275-2	250 / 200	275 / 220	-	-	1506A-E88TAG3 MJB 250 LB4	528	56,2	60,3	-	-	2662	1071	1818	2096
P275-5	250 / 200	275 / 220	-	-	1506A-E88TAG3 MJB 250 LB4	528	53,2	58,5	-	-	2662	1071	1818	2096
P300-4	275 / 220	300 / 240	-	-	1506D-E88TAG4 FG26A230	528	60,2	64,3	-	-	2675	1071	1818	2110
P300-5	275 / 220	300 / 240	-	-	1506A-E88TAG4 FG26A230	528	59	64,5	-	-	2675	1071	1818	2110
P313-5	-	-	281 / 225	313 / 250	1506A-E88TAG3 MJB 250 LB4	464	-	-	60,2	66,8	2662	1071	1818	2096
P330-5	300 / 240	330 / 264	-	-	1506A-E88TAG5 FG26A250	528	62,8	70,1	-	-	2785	1071	1818	2261
P344-5	-	-	313 / 250	344 / 275	1506A-E88TAG4 FG26A250	528	-	-	66,7	73,7	2785	1071	1818	2261
P375-4	-	-	338 / 270	375 / 300	1506D-E88TAG4 FG26A250	528	-	-	73,3	80,5	2785	1071	1818	2261
P375-5	-	-	338 / 270	375 / 300	1506A-E88TAG5 FG26A250	528	-	-	71,9	80,5	2785	1071	1818	2261
P400-3	350 / 280	400 / 320	-	-	2206A-E13TAG2 EG315M-280N	888	69,6	79	-	-	3800	1131	2156	3161
P438-3	-	-	400 / 320	438 / 350	2206A-E13TAG5 EG315M-280N	888	-	-	80,9	88	3800	1131	2156	3161
P450-2	400 / 320	450 / 360	-	-	2206D-E13TAG3A LL6114C	888	89,1	98,1	-	-	3800	1131	2156	3233
P450-3	400 / 320	450 / 360	-	-	2206A-E13TAG3 FG29A320	888	78,2	87,2	-	-	3800	1131	2156	3253
P500-3	455 / 364	500 / 400	-	-	2506A-E15TAG1 FG29A360	888	91,3	101,5	-	-	3800	1131	2215	3661
P501-3	-	-	438 / 350	500 / 400	2206A-E13TAG6 FG29A320	888	-	-	87,8	99,4	3800	1131	2156	3253

# DATOS TÉCNICOS

Modelo del grupo electrógeno	50 Hz (kVA/kW)		60 Hz (kVA/kW)		Alternador de motor	Depósito de combustible (L)	50 Hz (L/h)		60 Hz (L/h)		L (mm)	An (mm)	Al (mm)	P (kg)
	PR	SB	PR	SB			PR	SB	PR	SB				
P550-2	500/400	550/440	-	-	2506D-E15TAG2 FG29A400	1083	104	113,9	-	-	3787	1481	2193	3832
P550-3	500/400	550/440	-	-	2506A-E15TAG2 FG29A400	888	97,2	107,4	-	-	3800	1131	2215	3699
P563-3	-	-	513 / 410	563 / 450	2506A-E15TAG3 FG29A360	888	-	-	101,6	111,3	3800	1131	2215	3661
P605-3	550/440	605/484	-	-	2806A-E18TAG1 FG33A450	1132	107,4	119	-	-	3900	1461	2156	4202
P625-3	-	-	569 / 455	625 / 500	2506A-E15TAG4 FG29A400	888	-	-	112,8	123,2	3800	1131	2215	3699
P660-3	600/480	660/528	-	-	2806A-E18TAG1A FG33A500	1132	118,5	131,1	-	-	3900	1461	2156	4342
P688-3	-	-	625 / 500	688 / 550	2806A-E18TAG1A FG33A500	1132	-	-	124,6	138,2	3900	1461	2156	4342
P715-3	650/520	715/572	-	-	2806A-E18TAG2 FG33A560	1132	127,6	142	-	-	3900	1461	2156	4522
P750-3	-	-	681 / 545	750 / 600	2806A-E18TAG3 FG33A500	1132	-	-	138,9	155	3900	1461	2156	4342
P780-1	706/565	780/624	-	-	2806A-E18TTAG4 LL7224J	1702	144.2	160.6	-	-	4130	1690	2570	4979
P813-1	-	-	750 / 600	813 / 650	2806A-E18TTAG6A LL7224H	1702	-	-	160.7	176	4130	1690	2570	4834
P850-1	770/616	850/680	-	-	2806A-E18TTAG5 LL7224L	1702	160.3	179.9	-	-	4130	1690	2570	5040
P895-1	-	-	813 / 650	895 / 716	2806A-E18TTAG6 LL7224J	1702	-	-	172.8	192	4130	1690	2570	4979
P938-1	-	-	850 / 680	938 / 750	2806A-E18TTAG7 LL7224L	1702	-	-	183.3	204.7	4130	1690	2570	5040

# DATOS TÉCNICOS

Modelo del grupo electrógeno	50 Hz (kVA/kW)		60 Hz (kVA/kW)		Alternador de motor	Depósito de combustible (L)	50 Hz (L/h)		60 Hz (L/h)		L (mm)	An (mm)	Al (mm)	P (kg)
	PR	SB	PR	SB			PR	SB	PR	SB				
P730P1 / P800E1	730/584	800/640	735/588	844/675	4006-23TAG2A FGL70020 <sup>1</sup> LL7224J <sup>2</sup>	1494	157,4	171,8	174,3	201,1	4280	1690	2379	5934
P800P1 / P900E1	800/640	900/720	835/668	938/750	4006-23TAG3A FGL70030 <sup>1</sup> LL7224L <sup>2</sup>	1494	171,2	193,4	198,9	224,4	4280	1690	2379	5995
P900P1 / P1001E1	-	-	900/720	1000/800	4008TAG1 LL7224N	-	-	-	198,3	223,2	4821	2046	2375	7201
P910P1 / P1000E1	910/728	1000/800	-	-	4008TAG1A FGL70040	-	192,7	214,9	-	-	4967	2162	2227	6820
P1000P1 / P1100E1	1000/800	1100/880	-	-	4008TAG2A FGL70050	-	214,1	240	-	-	4967	2162	2227	6820
P1001P1 / P1101E1	-	-	1000/800	1100/880	4008TAG2 LL7224P	-	-	-	221,2	244,4	4821	2046	2375	7250
P1125P1 / P1250E1	1125/900	1250/1000	-	-	4008-30TAG3 LL8224H	-	240,1	266,3	-	-	4789	2257	2069	7753
P1250P3 / P1375E3	1250/1000	1375/1100	1250/1000	1375/1100	4012-46TWG2A LL8224H/L	-	258	284,9	266	298	4788	1895	2450	9079
P1350P1 / P1500E1	1350/1080	1500/1200	1350/1080	1500/1200	4012-46TWG3A LL8224L/P	-	279,2	313,4	289	324	4888	1895	2450	9697
P1500P3 / P1650E3	1500/1200	1650/1320	-	-	4012-46TAG2A LL8224N	-	296,6	326,3	-	-	5095	1900	2435	10385
P1700P1 / P1875E1	1700/1360	1875/1500	-	-	4012-46TAG3A LL9324F	-	349,7	390,2	-	-	5259	2192	2453	11207
P1750 / P1925E	1750/1400	1925/1540	-	-	4016TAG LL9224F	-	361,5	399,9	-	-	5752	2300	3020	15455
P1825 / P2000E	1825/1460	2000/1600	-	-	4016TAG1A LL9224F	-	378,2	419,9	-	-	5752	2300	3020	15455
P2000 / P2250E	2000/1600	2249/1799	-	-	4016TAG2A LL9224H	-	425,7	486,8	-	-	5752	2300	3020	15680
P2000-1 / P2000-1E	1850/1480	2000/1600	-	-	4016-61TRG1 LL9324F	-	385,4	410,8	-	-	5839	2176	2605	12528
P2250-1 / P2250-1E	2000/1600	2250/1800	-	-	4016-61TRG2 LL9324H	-	418,1	470,8	-	-	5839	2176	2605	12528
P2500-1 / P2500-1E	2250/1800	2500/2000	-	-	4016-61TRG3 LL9324P	-	470,6	528,4	-	-	6038	2180	2900	13380

1 - 50Hz 2 - 60Hz

# DATOS TÉCNICOS

Modelo del grupo electrógeno	50 Hz (kVA/kW)		60 Hz (kVA/kW)		Alternador de motor	Depósito de combustible (L)	50 Hz (L/h)		60 Hz (L/h)		L (mm)	An (mm)	Al (mm)	P (kg)
	PR	SB	PR	SB			PR	SB	PR	SB				
P56-1	45/ 36	50/ 40	50/ 40	56,3/ 45	1103A-33TG1 GTA 201 AE20	145	10,8	12	11,9	13,6	1680	760	1333	826
P75-1	60/ 48	65/ 52	68,8/ 55	75/ 60	1103A-33TG2 GTA 202 AE32	145	13,7	14,9	16,2	17,7	1741	760	1333	828
P100-1	80/ 64	88/ 70,4	90/ 72	100/ 80	1104A-44TG2 GTA 202 AE36	180	18,2	20,1	21,2	23,6	1870	840	1333	1032
P125-1	100/ 80	110/ 88	113/ 90,4	125/ 100	1104C-44TAG2 GTA 202 AS36	218	22,2	24,5	26,1	29,3	1980	890	1376	1083
P169-1	135/ 108	150/ 120	149,5/ 119,6	168,8/ 135	1106A-70TG1 GTA 251 AE27	327	30,3	34	33,1	37,8	2450	1010	1544	1443
P218-3	180/ 144	200/ 160	196,3/ 157	217,5/ 174	1106A-70TAG3 GTA 252 AE37	394	40,1	43,3	45,2	48,7	2510	1010	1640	1563
M260-1	-	-	240/ 192	260/ 208	MWM 7.3P GTA 252 AI44	457	-	-	50	57,4	2512	1030	1700	1775
S450-1	-	-	410/ 328	450/ 360	DC13072A GTA 311 AI41	250	-	-	80,4	88,8	3480	1120	2075	2953
S550-1	-	-	500/ 400	550/ 440	DC13072A GTA 311 AI41	250	-	-	100,7	113,1	3480	1120	2075	2953
P500-5	455/ 364	500/ 400	-	-	2506A-E15TAG1 GTA 312 AE49	888	94,9	104,1	-	-	3800	1131	2215	3775
P550-5	500/ 400	550/ 440	-	-	2506A-E15TAG2 GTA 312 AE52	888	100,2	110,9	-	-	3800	1131	2215	3825
P563-5	-	-	512,5/ 410	562,5/ 450	2506A-E15TAG3 GTA 311 AE41	888	-	-	101,7	111,2	3800	1131	2215	3598
P605-5	550/ 440	605/ 484	-	-	2806A-E18TAG1 GTA 312 AEDI	1132	107,9	120,1	-	-	3900	1461	2156	4162
P625-5	-	-	568,8/ 455	625/ 500	2506A-E15TAG4 GTA 311 AE41	888	-	-	113,3	124,4	3800	1131	2215	3598
P660-5	600/ 480	660/ 528	-	-	2806A-E18TA- G1A GTA 312 AEDJ	1132	119,9	132,9	-	-	3900	1461	2156	4182
P688-5	-	-	625/ 500	687,5/ 550	2806A-E18TA- G1A GTA 312 AE47	1132	-	-	122,7	136,3	3900	1461	2156	4051
P700-5	635/ 508	700/ 560	-	-	2806A-E18TAG2 GTA 312 AEDJ	1132	126,2	141	-	-	3900	1461	2156	4182
P750-5	-	-	681,3/ 545	750/ 600	2806A-E18TAG3 GTA 312 AEDK	1132	138,8	153,7	-	-	3900	1461	2156	4102





[www.fgwilson.com](http://www.fgwilson.com)