



# Buckets

for Hydraulic Excavators

## Technical Specifications

Not all attachments available in all regions. Consult your Cat® dealer for specific configurations available in your region.

### Table of Contents

<b>Model-Linkage Cross Reference Chart</b> .....	<b>2</b>
<b>Pin-on Cat® Pin Grabber Buckets</b> .....	<b>6</b>
312-Family .....	.6
M312/M315-Family .....	.6
315/316-Family .....	.6
M318/M320-Family .....	.6
A-Family .....	.6
B-Family .....	.7
CB-Family .....	.7
DB-Family .....	.7
TB-Family .....	.8
UB-Family .....	.8
VB-Family .....	.8
WB2-Family .....	.8
JC-Family .....	.8
<b>Ground Engaging Tools (GET)</b> .....	<b>9</b>

# Buckets for Hydraulic Excavators Technical Specifications

## Model-Linkage Cross Reference Chart

Caterpillar classifies excavator buckets according to the “linkage family” at the end of the stick. Refer to the following charts to identify which linkage family each Cat excavator uses when determining bucket compatibility.

Not all machines are available in all regions. Consult your Cat dealer for specific machines and configurations available in your region.

Linkage Family	312, A	M312/ M315	315/316	M318/ M320	B	CB	DB	TB	UB	VB2	WB2	HB2	JC
Stick Pin Dia. (mm)	65	70	70	80	80	90	100	110	120	120	130	130	140
Link Pin Dia. (mm)	65	70	70	80	80	90	90	100	110	110	120	120	130
Face Spread (mm)	221	281	281	311	311	351	385	441	501	501	551	551	651
Pin Spread (mm)	407	430	463	445/485*	445/485*	485/512*	500/528*	587	635	635	675	650	700

### Small Excavators

311D/F	1PB												
312D/E	1PB/VAB												
312D2/D2 GC	1PB												
313D2/D2 GC													
312F GC/313F GC													
312F/313F	1PB/VAB												
312 GC	1PB												
313 GC													
313	1PB/VAB												
314D/E/F	1PB/VAB/POB												
315F													
315 GC	1PB												
315	1PB/VAB/POB												
315D/316E/F			1PB/VAB										
316 GC	1PB												
317 GC			1PB										
317			1PB/VAB										
318E/F			Reach										
318D2			1PB										
319D					Reach/ VAB								

\*Wider dimension accommodates Power Buckets

1PB – One Piece Boom

POB – Power (parallel) Offset Boom

Reach – Reach Boom

VAB – Variable Angle Boom

(continued on next page)

# Buckets for Hydraulic Excavators Technical Specifications

## Model-Linkage Cross Reference Chart *(continued)*

Caterpillar classifies excavator buckets according to the “linkage family” at the end of the stick. Refer to the following charts to identify which linkage family each Cat excavator uses when determining bucket compatibility.

Not all machines are available in all regions. Consult your Cat dealer for specific machines and configurations available in your region.

Linkage Family	312, A	M312/ M315	315/316	M318/ M320	B	CB	DB	TB	UB	VB2	WB2	HB2	JC
Stick Pin Dia. (mm)	65	70	70	80	80	90	100	110	120	120	130	130	140
Link Pin Dia. (mm)	65	70	70	80	80	90	90	100	110	110	120	120	130
Face Spread (mm)	221	281	281	311	311	351	385	441	501	501	551	551	651
Pin Spread (mm)	407	430	463	445/485*	445/485*	485/512*	500/528*	587	635	635	675	650	700

### Medium Excavators

320D/E/F	SLR				Reach/ VAB								
320D2/D3					Reach								
320 GC													
320	SLR												
321D					Reach/ VAB								
323D	SLR					MASS							
323D3					Reach								
323E/F													
323 GC													
323	SLR				Reach/ VAB								
325F													
325													
324D/E						Reach/ VAB							
325D	SLR					Reach	MASS						
326D2/F						Reach/ VAB							
326 GC						Reach							
326	SLR					Reach/ VAB							
328D													
329D/E/F	SLR					Reach	MASS						
330D					LRE		Reach	MASS					
330D2/F	SLR												
330 GC							MASS						
330	SLR					Reach							
335F													
335													

\*Wider dimension accommodates Power Buckets

LRE – Long Reach Excavation

MASS – Mass Boom

Reach – Reach Boom

SLR – Super Long Reach Boom

VAB – Variable Angle Boom

*(continued on next page)*

# Buckets for Hydraulic Excavators Technical Specifications

## Model-Linkage Cross Reference Chart *(continued)*

Caterpillar classifies excavator buckets according to the “linkage family” at the end of the stick. Refer to the following charts to identify which linkage family each Cat excavator uses when determining bucket compatibility.

Not all machines are available in all regions. Consult your Cat dealer for specific machines and configurations available in your region.

Linkage Family	312, A	M312/ M315	315/316	M318/ M320	B	CB	DB	TB	UB	VB2	WB2	HB2	JC
Stick Pin Dia. (mm)	65	70	70	80	80	90	100	110	120	120	130	130	140
Link Pin Dia. (mm)	65	70	70	80	80	90	90	100	110	110	120	120	130
Face Spread (mm)	221	281	281	311	311	351	385	441	501	501	551	551	651
Pin Spread (mm)	407	430	463	445/485*	445/485*	485/512*	500/528*	587	635	635	675	650	700

### Large Excavators

336D/D2/E					LRE								
336D2 GC								Reach	MASS				
336D2 XE													
336E H													
336F					LRE		Reach/SB						
336F XE													
336 GC								Reach	MASS				
336													
340D2													
340F					LRE								
340F UHD					UHD^		RETRO						
340					LRE		Reach/SB	MASS					
340 UHD					UHD^		RETRO						
345 GC								Reach					
345D/349D								Reach/LR					
349D2								Reach					
349E/F								Reach/LR	MASS				
349								Reach					
350								Reach					
352F					LRE			Reach					
352													
352 UHD					UHD^			RETRO					
374D/F										Reach	MASS		
374													
390D/F												Reach/ GP	MASS
395													

\*Wider dimension accommodates Power Buckets

GP – General Purpose

LR – Long Reach Boom

LRE – Long Reach Excavation

MASS – Mass Boom

Reach – Reach Boom

SB – Straight Boom

UHD – Ultra High Demolition

^Pin and Face Spread measurements vary from standard B linkage

RETRO – Earthmoving front for UHD machine

*(continued on next page)*

# Buckets for Hydraulic Excavators Technical Specifications

## Model-Linkage Cross Reference Chart *(continued)*

Caterpillar classifies excavator buckets according to the “linkage family” at the end of the stick. Refer to the following charts to identify which linkage family each Cat excavator uses when determining bucket compatibility.

Not all machines are available in all regions. Consult your Cat dealer for specific machines and configurations available in your region.

Linkage Family	312, A	M312/ M315	315/316	M318/ M320	B	CB	DB	TB	UB	VB2	WB2	HB2	JC
Stick Pin Dia. (mm)	65	70	70	80	80	90	100	110	120	120	130	130	140
Link Pin Dia. (mm)	65	70	70	80	80	90	90	100	110	110	120	120	130
Face Spread (mm)	221	281	281	311	311	351	385	441	501	501	551	551	651
Pin Spread (mm)	407	430	463	445/485*	445/485*	485/512*	500/528*	587	635	635	675	650	700

### Wheeled Excavators

M313D		1PB/VAB‡											
M314F													
M314	1PB/VAB‡												
M315D/D2/F		1PB/VAB‡											
M315	1PB/VAB‡												
M316D/F		1PB/VAB‡											
M316			1PB/VAB‡										
M317D2/F		1PB/VAB‡											
M317			1PB/VAB‡										
M318D				1PB/VAB									
M318F		1PB/VAB‡											
M318			1PB/VAB‡										
M319													
M320D2/F				1PB/VAB									
M320					1PB/VAB								
M322D/D2/F				1PB/VAB									

### Material Handlers\*\*

MH3022 (F Series)				1PB/VAB									
MH3022					1PB/VAB								
MH3024 (F Series)				1PB/VAB									
MH3024					1PB/VAB								
MH3026 (F Series)				1PB/VAB									
MH3026					1PB/VAB								

### Forest Machines\*\*

538 GF					Reach								
548 GF						Reach							
558 GF							Reach						
568 GF								Reach					

\*Wider dimension accommodates Power Buckets

\*\*When equipped with appropriate stick and bucket linkage

‡When using Pin Grabber Coupler with bucket, rotation difference will occur

1PB – One Piece Boom

Reach – Reach Boom

VAB – Variable Angle Boom

# Buckets for Hydraulic Excavators Technical Specifications

## Pin-on Cat® Pin Grabber Buckets

Use pinned to the machine or with a Cat Pin Grabber Coupler.

Capacity based on ISO 7451.

Bucket weights do not include tips, unless otherwise indicated.

Bucket part numbers shown include adapters, tips ordered separately unless otherwise indicated.

Not all attachments are available in all regions. Consult your Cat dealer for specific configurations available in your region.

### 312-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Utility Duty</b>								
571-2849 *	900	36	0.53	0.69	70	5	413	910
<b>General Duty</b>								
571-2854	900	36	0.53	0.69	70	6	400	882
571-2858 *	900	36	0.53	0.69	70	5	414	914
571-2945 *	900	36	0.53	0.69	70	6	441	972
591-0062 **x	1000	39	0.53	0.69	J250	5	417	918
571-2944 *	1000	39	0.60	0.78	70	5	454	1001
571-2885 *	1050	42	0.65	0.85	70	6	509	1123
571-2872 *	1100	43	0.70	0.92	70	6	518	1143
568-3280 *	1200	49	0.76	0.99	J250	6	532	1174
<b>Heavy Duty</b>								
568-3290 *	1200	49	0.76	0.99	J250	6	551	1215
<b>Severe Duty</b>								
550-9227 *	1050	42	0.65	0.85	80	5	590	1300
568-3270 *	1050	41	0.65	0.85	J300	5	609	1342

\*Tips included

\*\*Bucket profile specifically for GX machines

### M312/M315-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
573-4974	450	18	0.20	0.27	70	3	253	558

**NOTE:** bucket profile specifically for M313D, M314F, M315D2/F

### M312/M315-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
550-9421	1100	43	0.80	1.04	80	4	573	1263
573-4976	1200	47	0.91	1.19	80	5	629	1388

**NOTE:** bucket profile specifically for M316F, M317D2/F, M318F

### 315/316-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
550-9300 *	1100	43	0.80	1.04	80	5	678	1495
550-9303 *	1200	47	0.80	1.05	80	6	677	1492
<b>Severe Duty</b>								
550-9338 *	1050	42	0.76	1.00	90	5	737	1624

\*Tips included

### M318/M320-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
552-8196	600	24	0.39	0.50	80	3	454	1002
552-8198	1200	48	0.98	1.28	80	5	672	1482
550-9442 *	1200	48	1.00	1.31	80	5	704	1551
552-8199	1400	55	1.18	1.54	80	5	729	1607

\*Tips included

**NOTE:** bucket profile specifically for M318D, M320D2/F

### A-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Ditch Cleaning</b>								
441-6077 *	1200	48	0.57	0.74	BOCE		386	852

\*Tips included

BOCE – Bolt-on Cutting Edge included

(continued on next page)

# Buckets for Hydraulic Excavators Technical Specifications

## Pin-on Cat® Pin Grabber Buckets (continued)

Use pinned to the machine or with a Cat Pin Grabber Coupler.

Capacity based on ISO 7451.

Bucket weights do not include tips, unless otherwise indicated.

Bucket part numbers shown include adapters, tips ordered separately unless otherwise indicated.

Not all attachments are available in all regions. Consult your Cat dealer for specific configurations available in your region.

### B-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
579-6300 *	1150	46	0.92	1.20	J350	5	787	1736
550-9516 *	1150	46	0.90	1.18	90	5	782	1725
550-9510 *	1150	46	0.90	1.18	90	5	818	1804
573-4977	1200	48	1.19	1.56	80	5	771	1700
573-4978 *	1200	48	1.19	1.56	90	5	878	1935
532-6000 *	1250	50	1.00	1.31	J350	5	806	1777
550-9517 *	1250	50	1.00	1.31	90	5	816	1800
550-9511 *	1250	50	1.00	1.31	90	5	852	1877
576-4849	1300	51	1.07	1.41	80	5	701	1546
550-9518 *	1400	56	1.14	1.49	90	6	882	1945
<b>Heavy Duty</b>								
550-9599 *	1050	42	1.00	1.31	90	5	937	2066
550-9596 *	1050	42	1.00	1.31	90	5	955	2106
550-9600 *	1200	48	1.19	1.56	90	5	1009	2224
528-0290 *	1250	49	1.00	1.31	J350	5	862	1900
550-9601 *	1350	54	1.40	1.83	90	5	1071	2361
<b>Severe Duty</b>								
540-4105 *	1100	43	1.00	1.31	100	4	1042	2297
540-4106 *	1250	49	1.19	1.56	100	5	1140	2513
546-5050 *	1450	57	1.20	1.57	J350	6	1032	2275
<b>Clean-up</b>								
439-7308 *	1800	72	1.60	2.09	BOCE		979	2157

\*Tips included

BOCE – Bolt-on Cutting Edge included

**NOTE:** when using a wheeled excavator, bucket profile specifically for M322D/D2/F

### CB-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
540-4090 *	1400	55	1.54	2.01	100	6	1187	2617
370-5824 *	1400	55	1.54	2.02	J400	6	1165	2568
573-4997 *	1700	67	2.00	2.60	100	6	1345	2965

\*Tips included

### CB-Family (continued)

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Heavy Duty</b>								
565-6339	1450	58	1.60	2.09	100	5	1211	2670
609-7901 *	1450	58	1.60	2.09	J400	5	1290	2844
566-2007 *	1450	58	1.60	2.09	100	5	1323	2917
609-7902 *	1600	63	1.80	2.35	J400	6	1388	3060
566-2008 *	1600	63	1.80	2.35	100	6	1410	3109
573-5015 *	1650	67	1.90	2.48	100	5	1418	3126
566-6627 *	1750	69	2.00	2.61	100	5	1397	3080
573-5016 *	1750	69	2.00	2.61	100	5	1446	3188
<b>Severe Duty</b>								
528-4596 *	1300	51	1.36	1.78	110	4	1395	3075
528-4598 *	1400	56	1.54	2.01	110	5	1496	3298

\*Tips included

### DB-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
540-4079 *	1500	60	1.87	2.44	100	5	1365	3009
<b>Heavy Duty</b>								
528-4565 *	1350	55	1.64	2.14	110	5	1572	3466
528-4566 *	1500	61	1.88	2.46	110	5	1670	3682
528-4568 *	1500	61	1.88	2.46	110	5	1682	3708
528-4567 *	1650	67	2.12	2.77	110	5	1768	3898
528-4569 *	1650	67	2.12	2.77	110	5	1780	3924
559-4170 *	1800	73	2.40	3.14	110	5	1848	4074
<b>Severe Duty</b>								
525-4050 * <sup>S</sup>	1550	61	1.90	2.48	130	4	1948	4295
528-8130 *	1700	67	2.12	2.77	130	5	2094	4616
563-2899 *	1850	73	2.31	3.02	130	5	2191	4830

\*Tips included

S – Spade Edge Bucket

(continued on next page)

# Buckets for Hydraulic Excavators Technical Specifications

## Pin-on Cat® Pin Grabber Buckets (continued)

Use pinned to the machine or with a Cat Pin Grabber Coupler.

Capacity based on ISO 7451.

Bucket weights do not include tips, unless otherwise indicated.

Bucket part numbers shown include adapters, tips ordered separately unless otherwise indicated.

Not all attachments are available in all regions. Consult your Cat dealer for specific configurations available in your region.

### TB-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
577-0356 *	1800	71	2.60	3.40	110	6	2325	5126
<b>Heavy Duty</b>								
519-2233 *	1650	65	2.41	3.15	130	5	2488	5485
518-9358 *	1650	65	2.41	3.15	130	5	2503	5518
577-0353 *	1750	69	2.50	3.27	110	6	2464	5432
566-6632 <sup>SS</sup>	1850	72	2.69	(3.52)	110	5	2317	5108
568-7612 *	1850	73	2.69	3.52	130	5	2638	5816
528-8132 *	1950	77	3.08	4.03	130	5	2821	6219
<b>Severe Duty</b>								
566-6635 <sup>SS</sup>	1350	54	1.87	2.44	110	4	2135	4707
519-2234 <sup>SS</sup>	1550	61	2.14	2.80	130	4	2338	5154
577-0350 *	1600	63	2.20	2.88	130	4	2309	5090
519-2235 *	1650	65	2.41	3.15	130	5	2584	5697
528-4593 <sup>SS</sup>	1650	66	2.41	3.15	110	5	2452	5406
518-9326 <sup>S</sup>	1750	69	2.40	3.14	130	4	2463	5430

\*Tips included

S – Spade Edge Bucket

### UB-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
528-8134 *	1950	77	3.43	4.49	130	5	2929	6457
518-9353 *	2000	79	3.60	4.71	130	5	2789	6149
<b>Severe Duty</b>								
568-7616 <sup>SS</sup>	1450	59	2.39	3.12	130	4	2635	5809
519-2236 <sup>SS</sup>	1550	61	2.61	3.41	130	4	2740	6041
519-2237 <sup>SS</sup>	1850	73	3.21	4.20	130	5	3078	6786

\*Tips included

S – Spade Edge Bucket

### VB-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Heavy Duty</b>								
568-7614 *	1500	61	2.50	3.27	130	4	2563	5650
568-7615 *	1750	70	3.00	3.92	130	4	2770	6107

\*Tips included

### WB2-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>Heavy Duty</b>								
543-2769	2300	91	5.30	6.93	150	5	4444	9797
<b>Severe Duty</b>								
519-5394 <sup>SS</sup>	2200	87	4.60	6.02	170	4	5248	11570
519-5407 <sup>S</sup>	2250	89	5.00	6.54	170	4	5101	11246
584-2240 <sup>SS</sup>	2250	89	5.00	6.54	170	4	5109	11263
<b>Extreme Duty</b>								
519-5397 <sup>SS</sup>	2150	85	4.60	6.02	170	4	5949	13115

\*Tips included

S – Spade Edge Bucket

### JC-Family

Part No.	Width		Capacity		Adapters		Weight	
	mm	in	m <sup>3</sup>	yd <sup>3</sup>	GET	Qty.	kg	lb
<b>General Duty</b>								
528-8138 *	2550	100	6.00	7.85	170	6	6065	13371
528-8163	2600	102	6.50	8.50	170	6	5985	13195
584-2241 *	2600	102	6.50	8.50	170	6	5985	13195
588-7529 *	2800	110	7.00	9.15	170	6	6256	13792
<b>Heavy Duty</b>								
592-0656 *	2650	104	6.60	8.63	170	6	6312	13916
<b>Severe Duty</b>								
519-5461 <sup>SS</sup>	2500	95	6.00	7.85	200	5	7282	16054
552-8359 <sup>SS</sup>	2650	104	6.50	8.50	200	5	7087	15624
<b>Extreme Duty</b>								
519-5463 <sup>SS</sup>	2350	93	5.40	7.06	200	4	7541	16625
588-1490 <sup>SS</sup>	2550	100	6.00	7.85	200	4	8302	18303

\*Tips included

S – Spade Edge Bucket



# Buckets for Hydraulic Excavators Technical Specifications

## Ground Engaging Tools (GET)

Part numbers include tip and retainer unless otherwise indicated.

### Cat Advansys™ Tips

	70	80	90	100	110	130	150	170	200
<b>Double Spike</b>		505-4085	505-4095	505-4105	505-4115	381-4092	368-3788	368-3871	
<b>General Duty</b>	539-5678	505-4086	505-4096	505-4106	505-4116	381-4088	368-3789	368-3872	385-4811
<b>Heavy Duty</b>		505-3982	505-3996	505-4002	505-4012	368-3791	368-3786	368-3867	385-4814
<b>Heavy Duty Long Life (ARM)</b>		505-3983	505-3993	505-4003	505-4013	368-3857	368-3861	387-6856	387-6867
<b>Leveling Edge Conversion (LEC)</b>		505-3985	505-3995	505-4005					
<b>Penetration</b>	539-5677	505-4081	505-4091	505-4101	505-4111	381-4093	368-3785	368-3868	368-3877
<b>Penetration Long Life (ARM)</b>		505-4082	505-4092	505-4102	505-4112	368-3858	368-3874	387-6866	387-6868
<b>Penetration Plus</b>	539-5673	505-4083	505-4097	505-4103	505-4113	381-4089	368-3783	368-3869	368-3878
<b>Spike</b>		505-4084	505-4098	505-4104	505-4114	381-4090	368-3787	368-3870	
<b>Wide</b>		505-4080	505-4096	505-4100	505-4110	381-4091	368-3790	368-3866	

ARM – Abrasion Resistant Material

LEC – Leveling Edge Conversion

### J Series Tips

	J250	J300	J350	J400
<b>Abrasion, Heavy Duty</b>	8E-3755	8E-3756		
<b>Double Spike</b>			135-9357	135-9408
<b>General Duty</b>			1U-3352	7T-3402
<b>Long</b>	9J-3169	9J-3167		
<b>Long, Heavy Duty</b>	8E-3750	8E-3751		
<b>Penetration</b>	100-6462	3G-3237	9J-4359	6Y-7409
<b>Penetration Long Life (ARM)</b>			119-9359	124-7409
<b>Penetration Plus</b>		195-9180	168-1359	168-1409
<b>Short</b>	9J-3178	9J-3175		
<b>Spike</b>			168-1350	159-0400
<b>Twin Sharp</b>	229-7137			
<b>Wide</b>	101-2927	4T-2215	107-3350	107-3400

ARM – Abrasion Resistant Material

### Sidcutters and Protectors

Machine Model or Linkage Family	Sidebar Protectors	Sidcutters		
	4 Piece Set	GD	HD	SD
<b>311, 312, 313, 314</b>		380-1203		380-1203
<b>315, 316, M313-M318</b>		380-1204	380-1204	380-1204
<b>318</b>		380-1204	380-1204	380-1204
<b>B, CB, DB</b>	357-2691	7Y-0366	357-2698	357-2698
<b>M320, M322</b>	195-7216	380-1204	380-1204	
<b>TB, UB, VB, HB</b>	357-2687		357-2685	357-2685
<b>VB2, WB2, HB2</b>	329-5956		357-2686	357-2686
<b>JC</b>	357-2688		357-2686	357-2686

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

© 2021 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

GEJQ3369-03 (04-2021)  
Replaces GEJQ3369-02  
(India, Indonesia, SE Asia)

