



Cat[®] VCE Coupler System

for Wheel Loaders

The Cat[®] VCE Coupler System brings compliance with ISO 23727:2009, compatibility with a host of attachments, and better performance and flexibility for your Cat wheel loader. Enjoy 100% attachment compatibility, improved breakout forces and system support from your local Cat dealer.

Not all attachments are available in all regions. Consult your Cat dealer for specific configurations available in your region.

100% Compatibility

- Use your Cat loader with commonly available work tools that you may already have.
- Simplify tool management in mixed fleets.
- Meets ISO 23727:2009 for wheel loader couplers.

More Breakout Force, Better Performance

- No need to compromise on performance – this coupler system is designed and built for your Cat wheel loader.
- Static tipping load is 2% better, breakout force 4% better than third party or OEM couplers.
- Coupler weight and offset are also reduced.

Complete One-Source Solution

- Select the complete OEM solution for job site productivity.
- You'll have one point of everything – from tooth tip to radiator – from your local Cat dealer.
- The coupler is backed by a line of VCE-compatible buckets and attachments optimized for Cat loaders.

Cat® VCE Coupler System for Wheel Loaders

Technical Specifications

Couplers				
	Machine	Interchangeability	Weight	
			kg	lb
VCE Quick Coupler	950H, 950L	L90-L120	455	1003
VCE Quick Coupler	950M, 962M	L90-L120	458	1010
VCE Quick Coupler	966M	L150-L180	762	1680
VCE Quick Coupler	972M	L150-L180	762	1680
VCE Quick Coupler	980M	L220	1025	2260

Related Attachments

Buckets								
		Compatible Machines	Width		Capacity		Weight	
			mm	in	m ³	yd ³	kg	lb
General Purpose	General Purpose Bucket 3.2 m ³ (4.25 yd ³) Performance Series	950M, 962M	2894	114	3.3	4.25	1487	3278
	General Purpose Bucket 3.4 m ³ (4.50 yd ³) Performance Series	950M, 962M	2894	114	3.4	4.5	1509	3327
	General Purpose Bucket 4.0 m ³ (5.25 yd ³) Performance Series	966M, 972M	3201	126	4	5.25	2035	4486
	General Purpose Bucket 4.4 m ³ (5.75 yd ³) Performance Series	966M, 972M	3201	126	4.4	5.75	2140	4718
Flat Floor	Flat Floor Bucket 3.4 m ³ (4.50 yd ³) Performance Series	950M, 962M	2894	114	3.4	4.5	1501	3309
	Flat Floor Bucket 3.6 m ³ (4.75 yd ³) Performance Series	950M, 962M	2894	114	3.6	4.75	1532	3377
	Flat Floor Bucket 4.2 m ³ (5.50 yd ³) Performance Series	966M, 972M	3201	126	4.2	5.5	2132	4700
	Flat Floor Bucket 4.4 m ³ (5.75 yd ³) Performance Series	966M, 972M	3201	126	4.4	5.75	2174	4793
	Flat Floor Bucket 4.8 m ³ (6.25 yd ³) Performance Series	966M, 972M	3193	126	4.8	6.25	2311	5095

Forks								
		Compatible Machines	Tine Length		Carriage Width		Operating Weight	
			mm	in	mm	in	kg	lb
Pallet Fork	Carriage Width 2000 mm (79 in), Tine Length 1500 mm (59 in)	950H, 950L, 950M	1500	59	2000	79	825	1815
	Carriage Width 2500 mm (98 in), Tine Length 1500 mm (59 in)	950H, 950L, 950M	1500	59	2500	98	1000	2200
	Carriage Width 2000 mm (79 in), Tine Length 1750 mm (69 in)	966M, 972M, 980M	1750	69	2000	79	1133	2493

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

GEHQ9300-00 (09-2019)
(EU)

© 2019 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

