



# VCE Couplers and Tools

for Cat® Wheel Loaders

## Technical Specifications

Contact your Cat® dealer for attachment compatibility based on your application and machine configuration.

**Not all attachments are available in all regions. Consult your Cat dealer for models available in your region.**

### Table of Contents

<b>VCE Couplers</b> .....	<b>2</b>
Specifications and Dimensions .....	2
<b>Buckets</b> .....	<b>3</b>
Specifications and Dimensions .....	3
<b>Pallet Forks</b> .....	<b>4</b>
Specifications and Dimensions .....	4

# VCE Couplers and Tools Technical Specifications

## VCE Couplers

### Specifications and Dimensions



Part Number	Machine	Interchangeability	Weight	
			kg	lb
324-3390	950H, 950L	L90-L120	455	1003
363-5810	950M, 962M	L90-L120	458	1010
542-8611	966M	L150-L180	762	1680
542-8611	972M	L150-L180	762	1680
208-6529	980M	L220	1025	2260

# VCE Couplers and Tools Technical Specifications

## Buckets

### General Purpose Specifications and Dimensions



Part Number	Machine	Description	Width		Capacity		Weight	
			mm	in	m <sup>3</sup>	yd <sup>3</sup>	kg	lb
450-9832	950M, 962M	3.2 m <sup>3</sup> (4.25 yd <sup>3</sup> ) Performance Series	2894	114	3.3	4.25	1487	3278
450-9833	950M, 962M	3.4 m <sup>3</sup> (4.50 yd <sup>3</sup> ) Performance Series	2894	114	3.4	4.5	1509	3327
450-9834	966M, 972M	4.0 m <sup>3</sup> (5.25 yd <sup>3</sup> ) Performance Series	3201	126	4	5.25	2035	4486
450-9835	966M, 972M	4.4 m <sup>3</sup> (5.75 yd <sup>3</sup> ) Performance Series	3201	126	4.4	5.75	2140	4718

### Flat Floor Specifications and Dimensions



Part Number	Machine	Description	Width		Capacity		Weight	
			mm	in	m <sup>3</sup>	yd <sup>3</sup>	kg	lb
450-9837	950M, 962M	3.4 m <sup>3</sup> (4.50 yd <sup>3</sup> ) Performance Series	2894	114	3.4	4.5	1501	3309
450-9838	950M, 962M	3.6 m <sup>3</sup> (4.75 yd <sup>3</sup> ) Performance Series	2894	114	3.6	4.75	1532	3377
450-9839	966M, 972M	4.2 m <sup>3</sup> (5.50 yd <sup>3</sup> ) Performance Series	3201	126	4.2	5.5	2132	4700
450-9840	966M, 972M	4.4 m <sup>3</sup> (5.75 yd <sup>3</sup> ) Performance Series	3201	126	4.4	5.75	2174	4793
466-0124	966M, 972M	4.8 m <sup>3</sup> (6.25 yd <sup>3</sup> ) Performance Series	3193	126	4.8	6.25	2311	5095

# VCE Couplers and Tools Technical Specifications

## Pallet Forks

### Specifications and Dimensions



Part Number	Machine	Description	Tine Length		Tine Thickness		Tine Width		Carriage Height	
			mm	in	mm	in	mm	in	mm	in
268-1289	950H, 950L, 950M	Carriage Width 2000 mm (79 in), Tine Length 1500 mm (59 in)	1500	59.1	60	2.4	200	7.9	965	38.0
299-0405	950H, 950L, 950M	Carriage Width 2500 mm (98 in), Tine Length 1500 mm (59 in)	1500	59.1	60	2.4	200	7.9	989	38.9
296-1595	966M, 972M, 980M	Carriage Width 2000 mm (79 in), Tine Length 1750 mm (69 in)	1750	68.9	70	2.8	200	7.9	1209	47.6

  

Part Number	Machine	Description	Carriage Width		Minimum Tine Spacing		Maximum Tine Spacing		Operating Weight	
			mm	in	mm	in	mm	in	kg	lb
268-1289	950H, 950L, 950M	Carriage Width 2000 mm (79 in), Tine Length 1500 mm (59 in)	2000	78.7	50	2.0	1550	61.0	825	1815
299-0405	950H, 950L, 950M	Carriage Width 2500 mm (98 in), Tine Length 1500 mm (59 in)	2500	98.4	50	2.0	1950	76.8	1000	2200
296-1595	966M, 972M, 980M	Carriage Width 2000 mm (79 in), Tine Length 1750 mm (69 in)	2000	78.7	50	2.0	1550	61.0	1133	2493

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

GEJQ9388-00 (10-2019)  
(EU)

© 2019 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

