



Cat[®] 150

Motor Grader

Performance

- Cat[®] C7 engine meets Brazil MAR-1 emission standards, equivalent to U.S. EPA Tier 3 and EU Stage IIIA.
- Programmable Autoshift option simplifies operation by allowing transmission to be programmed to shift at optimal points to match application.
- Power Shift Countershaft Transmission matches to engine, maximizing power to the ground.
- Electronic Throttle Control helps improve productivity by providing best match of horsepower and torque for application demands.

Efficiency

- Aggressive blade angle, optimized moldboard curvature and large throat clearance allows material to roll more freely along blade, increasing efficiency.
- Hydraulic demand fan automatically adjusts speed according to cooling requirements resulting in more power to the ground and improved fuel efficiency.
- Engine idle shutdown timer is available to shut down engine after a set period of time saving fuel and helping reduce emissions.

Ease of Operation

- Selectable blade lift modes – Fine, Normal, or Coarse – allow you to choose the blade lift modulation mode that best fits your application or operating style.
- Joystick controls with electronically adjustable control pods reduce hand and arm movement by 78%, helping reduce operator fatigue.
- Left joystick controls steering, articulation, return-to-center, wheel lean, gear selection, left moldboard lift cylinder and float.
- Right joystick controls drawbar, circle and moldboard functions as well as electronic throttle control and manual differential lock/unlock.
- Articulation Return-to-Center automatically returns machine to a straight frame position from any angle with the touch of a button.
- Rocker and control switches are in easy reach.

Serviceability

- Durable nylon composite wear inserts maximize circle torque and component life.
- Sacrificial brass wear strips between blade mounting group and moldboard can be easily adjusted and replaced.
- Shimless Moldboard Retention System uses vertical and horizontal adjusting screws to keep moldboard wear strips aligned for reduced blade chatter and precise blade control.

Comfort

- Control pods can be adjusted electronically, making it easy to set to ideal operating position.
- Standard Cat Comfort Series suspension seat is fully adjustable.
- High capacity Heating, Ventilation and Air Conditioning (HVAC) system dehumidifies and pressurizes cab, sealing out dust and helping keep windows clear.

Technology

- Shuttle Shift allows smooth, fast direction shifts without requiring manipulating throttle or inching pedal.
- Cat Product Link[™] aids equipment management with remote monitoring capabilities.
- Optional Cat Grade Control Cross Slope helps maintain desired cross slope by automatically controlling one side of the blade.
- Optional factory-installed 3D mastless Cat Grade enables operators to improve grading efficiency, accuracy, and productivity in both rough grading and finish grading applications. When mastless Grade is installed at factory, e-fence is not included.
- Optional Cat Grade uses positioning and guidance technologies, machine sensors, and automatic blade control to help get to grade faster, easier and more efficiently.
- Optional Cat Advanced Control Joysticks (ACJs) allows control of automated grading solutions efficiently and safely without removing hands from the joysticks.

Safety

- Angled cab doors, tapered engine enclosure and sloped rear window make it easy to see moldboard and tires, as well as behind the machine.
- Optional rear vision camera enhances sight to the rear of the machine.



Cat® 150 Motor Grader

Engine

Engine Model	Cat C7	
Emissions	Brazil MAR-1, equivalent to U.S. EPA Tier 3 and EU Stage IIIA	
Base Power (1st gear) – Net	136 kW	183 hp
Base Power (1st gear) – Net (Metric)	186 hp	
VHP Plus Range – Net	136-174 kW	183-233 hp
VHP Plus Range – Net (Metric)	186-237 hp	
Displacement	7.2 L	439 in ³
Bore	110 mm	4.3 in
Stroke	127 mm	5 in
Torque Rise (VHP Plus)	39%	
Maximum Torque (VHP Plus)	1159 N·m	855 lbf·ft
Speed @ Rated Power	2,000 rpm	
Number of Cylinders	6	
Derating Altitude	3048 m	10,000 ft
Standard – Maximum Fan Speed	1,450 rpm	
Standard – Minimum Fan Speed	600 rpm	
Standard – Ambient Capability	43° C	109° F
High Ambient – Maximum Fan Speed	1,650 rpm	
High Ambient – Minimum Fan Speed	600 rpm	
High Ambient Capability	50° C	122° F

- Maximum torque (VHP Plus) measured at 1,000 rpm.
- Net power is tested per ISO 9249, SAE J1349, and EEC 80/1269 Standards in effect at the time of manufacture.
- Net power advertised is the power available at rated speed of 2,000 rpm, measured at the flywheel when engine is equipped with fan running at minimum speed, air cleaner, muffler and alternator.
- Power as declared per ISO 14396
Rated Speed = 2,000 rpm
VHP Plus = 175 kW (234 hp)
- No engine derating required up to 3048 m (10,000 ft).

Frame

Circle Diameter	1530 mm	60.2 in
Drawbar – Height	152 mm	6 in
Drawbar – Width	76.2 mm	3 in
Front Frame Structure – Height	305 mm	12 in
Front Frame Structure – Width	305 mm	12 in
Front Axle – Wheel Lean, Left/Right	18 degrees	
Front Axle – Total Oscillation Per Side	32 degrees	

Weights

Gross Vehicle Weight – Base		
Total	16 581 kg	36,554 lb
Front Axle	4337 kg	9,561 lb
Rear Axle	12 244 kg	26,993 lb
Gross Vehicle Weight – Maximum		
Total	23 538 kg	51,892 lb
Front Axle	7532 kg	16,606 lb
Rear Axle	16 006 kg	35,287 lb
Gross Vehicle Weight – Typically Equipped		
Total	18 991 kg	41,868 lb
Front Axle	5314 kg	11,716 lb
Rear Axle	13 677 kg	30,152 lb

- Base operating weight calculated on standard machine configuration with 14.00R24 tire with multi-piece rim, full fuel tank, coolant, lubricants and operator.

Moldboard

Moldboard – Width	3.7 m	12 ft
Moldboard – Height	610 mm	24 in
Arc Radius	413 mm	16.3 in
Throat Clearance	166 mm	6.5 in

Blade Range

Circle Centershift – Right	728 mm	28.7 in
Circle Centershift – Left	695 mm	27.4 in
Moldboard Sideshift – Right	660 mm	26 in
Moldboard Sideshift – Left	510 mm	20.1 in
Blade Tip Range – Forward	40 degrees	
Blade Tip Range – Backward	5 degrees	
Maximum Shoulder Reach Outside of Tires – Right	1978 mm	77.9 in
Maximum Shoulder Reach Outside of Tires – Left	1790 mm	70.5 in
Maximum Lift Above Ground	480 mm	18.9 in
Maximum Depth of Cut	715 mm	28.1 in



For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2024 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Advansys, S•O•S, Product Link, SmartBoom, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEXQ1975-02 (01-2024)
Replaces AEXQ1975-01
Build Number: 14A
(Brazil)

