



Image shown may not represent actual configuration

## C13 High Ambient Enclosures

50 Hz / 60 Hz

These high ambient, factory installed enclosures incorporate internally mounted residential level silencers, designed for safety and aesthetic value on integral fuel tank base or optional dual wall integral fuel tank base for total fluid containment. These enclosures are of extremely rugged construction to withstand exposure to the elements and provide weather protection.

### Features

#### Robust / Highly Corrosion Resistant Construction

- Factory installed on integral fuel tank base
- Environmentally friendly, polyester powder baked paint
- 1.6mm (0.063in) galvanized steel
- All round overhanging base to protect enclosure
- High-grade engineering thermoplastic corner posts for protection
- Integral lifting frame
- Compression door latches giving solid door seal
- Zinc plated or black coated stainless steel fasteners
- Internally mounted super critical exhaust silencing system

#### Excellent Access

- Large cable entry area for installation ease
- Accommodates rear mounted breaker and control panel
- Double doors on both sides
- Vertically hinged doors with solid bar door stays to hold doors open at 135° rotation
- Lube oil and coolant drains pipes to exterior of enclosure and terminated drain valves
- Radiator fill cover

#### Security and Safety

- Lockable access doors which give full access to control panel and breaker
- Cooling fan and battery charging alternator fully guarded
- Fuel fill, oil fill and battery can only be reached via lockable access
- Externally mounted emergency stop button
- Designed for spreader-bar lifting to ensure safety
- Control panel viewing window
- Stub-up area is rodent proof

#### Options

- Caterpillar Yellow or white paint
- Integral dual wall fuel tank base for total fluid containment (fuel, oil and coolant)

### Enclosure Package Operating Characteristics

Model	kVA	ekW	SB/PP	Sound Pressure Levels dBA				Air Flow Rate		Ambient Capability at 100% Load*	
				1m (3.3 ft)		7m (23 ft)					
				75% Load	100% Load	75% Load	100% Load	m³/s	cfm		
<b>50 Hz</b>											
DE400E0	350	280	PP	81	83	73	74	5.6	11866	54	129
	400	320	SB	82	84	73	76	5.6	11866	54	129
DE450E0	400	320	PP	82	84	73	76	5.6	11866	49	120
	450	360	SB	83	85	74	77	5.6	11866	49	120
<b>60 Hz</b>											
DE350SE0	400	320	PP	83	84	75	76	7.9	16739	56	133
	438	350	SB	83	85	75	76	7.9	16739	57	135
DE400SE0	438	350	PP	83	85	75	76	7.9	16739	52	126
	500	400	SB	84	86	75	77	7.9	16739	51	124

\*Ambient capability measured with the Cat extended life coolant at sea level.



Approximate weight of enclosure package: 4780 kg (10,538 lb). Exact weight is dependent on options. Enclosure weight includes: high ambient enclosure, exhaust system, base and generator set.

[www.cat.com/electricpower](http://www.cat.com/electricpower)

©2016 Caterpillar  
All rights reserved.

ENCSA70  
ENCSA71

LEHE0445-01 (11/16)

Materials and specifications are subject to change without notice.  
CAT, CATERPILLAR, their respective logos ACERT, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.