



Cat[®] Compaction Wheels

for Excavators

Cost-Effective Trench Compaction

Economical Performance

- Tapered feet compact cohesively and smoothly.
- Deep compaction achieved by open rim design.
- Move dirt and smooth trench floor with the standard backfill blade.

Rugged and Reliable

- Designed to handle impact and thrust loads of the machine.
- Proprietary tapered roller bearings and axle roll smoothly even under full load.
- Requires no hydraulics.

One Source, Complete Solution

- Designed to work with the Cat[®] excavator.
- Complete system support from one source – your Cat dealer.
- Fast local service wherever you are to keep you up and running

Cat® Compaction Wheels

Specifications Table

Sales Model	Machine Model	Machine Class	Compaction Width		Number of Wheels	Number of Pads	Weight		Overall Length		Overall Height		Overall Width	
			mm	in			kg	lb	mm	in	mm	in	mm	in
610 mm (24 in) 12.5 ton	311-312	12.5-13.75	610	24	3	27	572	1261	991	39	1168	46	584	23
915 mm (36 in) 12.5 ton	311-312	12.5-13.75	915	36	5	45	858	1892	1092	43	1168	46	889	35
610 mm (24 in) 16 ton	313, 314, 315F	16-18	610	24	3	30	990	2183	1194	47	1428	56	584	23
915 mm (36 in) 16 ton	313, 314, 315F	16-18	915	36	4	40	1246	2745	1194	47	1428	56	889	35
610 mm (24 in) 20 ton	315D, 316, 318	20-22	610	24	3	30	1012	2231	1194	47	1428	56	584	23
915 mm (36 in) 20 ton	315D, 316, 318	20-22	915	36	4	40	1267	2793	1194	47	1428	56	889	35
610 mm (24 in) 23 ton	320-325	23-25	610	24	3	30	1012	2231	1194	47	1428	56	584	23
915 mm (36 in) 23 ton	320-325	23-25	915	36	4	40	1273	2807	1194	47	1428	56	889	35
610 mm (24 in) 34 ton	324-329; 330D2-335F	34-38	610	24	3	30	1459	3217	1397	55	1584	62	584	23
915 mm (36 in) 34 ton	324-329; 330D2-335F	34-38	915	36	4	40	1835	4046	1397	55	1584	62	889	35
610 mm (24 in) 34 ton	330D; 336-340	34-38	610	24	3	30	1479	3261	1397	55	1584	62	584	23
915 mm (36 in) 34 ton	330D; 336-340	34-38	915	36	4	40	1856	4092	1397	55	1584	62	889	35
610 mm (24 in) 50 ton	345-352	50-55	610	24	3	36	1807	3984	1473	58	1757	69	616	24
915 mm (36 in) 50 ton	345-352	50-55	915	36	4	48	2225	4905	1473	58	1757	69	889	35

GEHQ0306-00 (2-2020)
(N Am)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com.

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.
© 2020 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

