

		2020 CAT Extend CVA and CAT Protect Planned Maintenance Schedules - Track Type Loaders See contract for number of applicable planned intervals			
		Sales Model	953K	963K	973K
Interval	Contract Type	Serial Number	LJT	LBL	MKL
PM1 - every 250 & 750 Hours	Both	Fluids SOS - Number of bottles and analysis	1	1	1
PM 2 - 500, 1,500, 2,500, 3,500, 4,500, etc. Hours	CAT Extend CVA	SOS Coolant Sample Level 1 bottle and analysis	X	X	X
		Fluids SOS - Number of bottles and analysis	4	4	4
		Eng Oil Filter Element	X	X	X
		Fuel In-line	X	X	-
		Fuel Water Separator Primary	X	X	X
		Fuel Secondary	X	X	X (x2 qty.)
	CAT Protect CVA adds fluids and labor	Fluids - CAT Diesel Engine Oil (in liters)	16	16	24.5
		Dealer Labor Included (excludes Travel Time & Mileage)	X	X	X
		SOS Coolant Sample Level 1 bottle and analysis	X	X	X
		Fluids SOS - Number of bottles and analysis	4	4	4
PM 3 - 1,000, 3,000, 5,000, 7,000, 9,000 Hours	CAT Extend CVA	Engine Air Primary Element	X	X	X
		Engine Air Secondary Element	X	X	X
		Eng Oil Filter Element	X	X	X
		Fuel In-line	X	X	-
		Fuel Water Separator Primary	X	X	X
		Fuel Secondary	X	X	X (x2 qty.)
		Fuel Tank Cap	-	-	X
		Transmission Filter Element	X	X	X
		Crankcase Breather Filter	X	X	-
	CAT Protect CVA adds fluids and labor	Fluids - CAT Diesel Engine Oil (in liters)	16	16	24.5
		Fluids - Final Drive Oil - CAT TDO (in liters)	30	30	57
		Dealer Labor Included (excludes Travel Time & Mileage)	X	X	X
		SOS Coolant Sample Level 2 bottle and analysis	X	X	X
		Fluids SOS - Number of bottles and analysis	4	4	4
PM 4 - 2,000, 4,000, 6,000, 8,000, & 10,000 Hours	CAT Extend CVA	Engine Air Primary Element	X	X	X
		Engine Air Secondary Element	X	X	X
		Eng Oil Filter Element	X	X	X
		Fuel In-line	X	X	-
		Fuel Water Separator Primary	X	X	X
		Fuel Secondary	X	X	X (x2 qty.)
		Fuel Tank Cap	-	-	X
		Thermostat AS	X	X	-
		Crankcase Breather Filter	X	X	X
		Hydraulic Tank Breather AS	X	X	X
		Transmission Filter Element	X	X	X
	CAT Protect CVA adds fluids and labor	Fluids - CAT Diesel Engine Oil (in liters)	16	16	24.5
		Fluids - Hydraulic System - CAT HYDO 10 (in liters)	75	75	189
		Fluids - Final Drive Oil - CAT TDO (in liters)	30	30	57
		Dealer Labor Included (excludes Travel Time & Mileage)	X	X	X

CAT Extend CVA Contracts include parts kits only and do not contain CAT fluids or dealer supplied Labor.
CAT Protect CVA Contracts include parts kits, CAT fluids, Component Protection Plan, and dealer supplied labor.
Consult your CVA agreement for information on contract starting point and interval arrangement.

EXCLUSIONS

Ensure that all safety information, warnings, and instructions are read and understood before any operation or any maintenance procedures are performed. The user is responsible for the performance of maintenance, including all adjustments, the use of proper lubricants, fluids, filters, and the replacement of components due to normal wear and aging. Failure to adhere to proper maintenance intervals and procedures may result in diminished performance of the product and/or accelerated wear of components. Use mileage, fuel consumption, service hours, or calendar time, WHICHEVER OCCURS FIRST, to determine the maintenance intervals. Models in the above table with 1,000 hour oil drain intervals assumes the machine is operated in a Standard Service Application, utilizes Cat Recommended Fluids and maintains timely SOS sampling. Consult model and serial number specific OMM for alternate drain and maintenance options. The maintenance activities in the table above reflect commonly required activities. Machines may require more frequent maintenance and/or additional parts, depending on factors such as severe applications or extreme operating and environmental conditions. This chart is not intended to be a comprehensive list of all maintenance activities that may be recommended or required and may not contain fluids, maintenance schedules or additional requirements associated with the above maintenance activities. Refer to your CVA contract for specific terms associated with the agreement.

Some recommended maintenance activities excluded from CVA contracts are listed below.

- * Valve gaskets excluded for valve lash checks.
- ** Coolant is recommended to be replaced every 2 years, unless extended by utilizing Extended Life Coolant (ELC) additive.
- *** The maintenance manual recommends cleaning or replacing the DPF with a new or remanufactured DPF every 5000 hours
- **** Seat Belts are recommended to be replaced every 3 years.
- ***** A/C Dryers are recommended to be replaced every 2000 hour interval.
- ***** Radiator caps are recommended to be replaced every 3000 hour interval.

This marketing tool does not represent a contract or obligation of any kind between Caterpillar Financial Aftermarket Solutions Corporation or its affiliates, and the equipment owner. For details on any Cat® Customer Value Agreement (CVA), including a complete description of the terms, conditions, and/or exclusions, contact a participating Cat dealer.

All graphics and lists in this marketing tool are provided solely for general information purposes and are not intended to be a solicitation or an offer to purchase any product or service.

To the extent that the above publication(s), bulletin(s), and/or any designated contract(s) are ambiguous or inconsistent with the CVA contract language, the terms of the CVA contract shall govern.

© 2020 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

