

		2020 CAT Extend CVA and CAT Protect CVA Planned Maintenance Schedules - Medium Wheel Loaders																
		See contract for number of applicable planned intervals																
		Sales Model	950H	980H	980H	980H	980K	980M	982M	950 GC	950M	962M	966M	972M	966M XE	972M XE	980M	982M
Interval	Contract Type	Serial Number Prefix	K5K	JMS00001-03999	JMS04000-05107	JMS05108-99999	W7K	KRS	K1Y	M5T	J1S, KSA	RKH, J2S	GMS, EJA	LSJ, A78	XCR, B8P	AN3, R1Z	XDJ, MK2	XDL, MK6
PM1 - every 250 & 750 Hours	Both	Fluids SOS - Number of bottles and analysis	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
PM 2 - 500, 1,500, 2,500, 3,500, 4,500, etc. Hours	CAT Extend CVA	SOS Coolant Sample Level 2 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Fluids SOS - Number of bottles and analysis	5	9	9	9	5	9	9	5	5	5	5	5	5	5	9	9
		Engine Oil Filter Element	X	X	X	X	X	-	-	X	-	-	-	-	-	-	-	-
		Fuel Water Separator Element	X	X	X	X	X	X	X	X	-	X	X	X	X	X	X	X
		Fuel Secondary Element	X	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X	X	X	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)
		In-Line Fuel Filter	-	-	-	-	-	-	-	X	X	X	X	-	-	-	-	-
		Hydraulic Oil Filter	X	X	X	X	X	-	-	X	-	-	-	-	-	-	-	-
		Transmission Oil Filter	-	-	-	-	X	X	X	X	-	X	X	X	-	-	X	X
		Fluids - CAT Diesel Engine Oil (in liters)	30	34	60	34	37	-	-	15.8	-	-	-	-	-	-	-	-
		Dealer Labor Included (excludes Travel Time & Mileage)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	CAT Protect CVA adds fluids and labor																	
PM 3 - 1,000, 3,000, 5,000, 7,000, 9,000 Hours	CAT Extend CVA	SOS Coolant Sample Level 1 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Fluids SOS - Number of bottles and analysis	5	9	9	9	5	9	9	5	5	5	5	5	5	5	9	9
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Engine Oil Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Fuel Water Separator Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Fuel Secondary Element	X	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X	X	X	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)
		In-Line Fuel Filter	-	-	-	-	-	-	-	X	X	X	-	-	-	-	-	-
		Transmission Oil Filter	X	X	X	X	X	X	X	X	X	X	X	X	-	-	X	X
		Hydraulic Oil Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Hydraulic Oil Filter Tank Return	X	-	-	-	X	X	X	-	X	X	X	X	X	X	X	X
		Fluids - CAT Diesel Engine Oil (in liters)	30	34	60	34	37	37	37	15.8	22	22	24.5	24.5	24.5	24.5	37	37
		Fluids - Transmission Oil - CAT TDTO (in liters)	34	62	62	62	66	-	-	-	-	-	-	-	-	-	-	-
		Dealer Labor Included (excludes Travel Time & Mileage)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	CAT Protect CVA adds fluids and labor																	
PM 4 - 2,000, 4,000, 6,000, 8,000, & 10,000 Hours	CAT Extend CVA	SOS Coolant Sample Level 2 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Fluids SOS - Number of bottles and analysis	5	9	9	9	5	9	9	5	5	5	5	5	5	5	9	9
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Engine Oil Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Fuel Water Separator Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Fuel Secondary Element	X	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X	X	X	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)	X (x2 qty.)
		In-Line Fuel Filter	-	-	-	-	-	-	-	X	X	X	-	-	-	-	-	-
		Transmission Oil Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Hydraulic Oil Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		Hydraulic Oil Filter Tank Return	X	-	-	-	X	X	X	-	X	X	X	X	X	X	X	X
		Hydraulic Tank Breather	-	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X
		Fuel Tank Cap Filter	-	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X
		Fumes Disposal Filter	-	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X
		Transmission Breather	-	-	-	-	-	-	-	-	-	-	-	-	X	X	-	-
	CAT Protect CVA adds fluids and labor	Fluids - CAT Diesel Engine Oil (in liters)	30	34	60	34	37	37	37	15.8	22	22	24.5	24.5	24.5	24.5	37	37
		Fluids - Transmission Oil - CAT TDTO (in liters)	34	62	62	62	66	77	77	45	43	43	58.5	58.5	60	60	77	77
		Fluids - Differential Oil Front/Rear - CAT TDTO (in liters)	72	174	174	174	168	168	168	78	86	86	114	114	115	115	168	168
		Dealer Labor Included (excludes Travel Time & Mileage)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

CAT Extend CVA Contracts include parts kits only and do not contain CAT fluids or dealer supplied Labor

CAT Protect CVA Contracts include parts kits, CAT fluids, Component Protection Plan, and dealer supplied labor.

Consult your CVA agreement for information on contract starting point and interval arrangement.

EXCLUSIONS

Ensure that all safety information, warnings, and instructions are read and understood before any operation or any maintenance procedures are performed. The user is responsible for the performance of maintenance, including all adjustments, the use of proper lubricants, fluids, filters, and the replacement of components due to normal wear and aging. Failure to adhere to proper maintenance intervals and procedures may result in diminished performance of the product and/or accelerated wear of components. Use mileage, fuel consumption, service hours, or calendar time, WHICH EVER OCCURS FIRST, to determine the maintenance intervals. Models in the above table with 1,000 hour oil drain intervals assumes the machine is operated in a Standard Service Application, utilizes Cat Recommended Fluids and maintains timely SOS sampling. Consult model and serial number specific OMM for alternate drain and maintenance options. The maintenance activities in the table above reflect commonly required activities. Machines may require more frequent maintenance and/or additional parts, depending on factors such as severe applications or extreme operating and environmental conditions. This chart is not intended to be a comprehensive list of all maintenance activities that may be recommended or required and may not contain fluids, maintenance schedules or additional requirements associated with the above maintenance activities. Refer to your CVA contract for specific terms associated with the agreement.

Some recommended maintenance activities excluded from CVA contracts are listed below.

Valve gaskets excluded for valve lash checks.

Coolant is recommended to be replaced every 2 years, unless extended by utilizing Extended Life Coolant (ELC) additive.

The maintenance manual recommends cleaning or replacing the DPF with a new or remanufactured DPF every 5000 hours

Seat Belts are recommended to be replaced every 3 years.

A/C Dryers are recommended to be replaced every 2000 hour interval.

Radiator caps are recommended to be replaced every 3000 hour interval.

This marketing tool does not represent a contract or obligation of any kind between Caterpillar Financial Aftermarket Solutions Corporation or its affiliates, and the equipment owner. For details on any Cat® Customer Value Agreement (CVA), including a complete description of the terms, conditions, and/or exclusions, contact a participating Cat dealer.

All graphics and lists in this marketing tool are provided solely for general information purposes and are not intended to be a solicitation or an offer to purchase any product or service.

To the extent that the above publication(s), bulletin(s), and/or any designated contract(s) are ambiguous or inconsistent with the CVA contract language, the terms of the CVA contract shall govern.

© 2020 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

