



Cat[®] M316

Wheeled Excavator

The Cat[®] M316 Excavator provides top performance with up to 14 percent more swing torque to get the job done faster. Save time and money with up to 10 percent overall savings in maintenance costs, longer service intervals, and 100 percent daily ground level maintenance. The M316 gives you the power to work longer while putting money in your pocket.

Not all features are available in all regions. Consult your Cat dealer for specific configurations available in your region.

High Performance with Lower Fuel Consumption

- The Cat engine matches to your performance and production needs. The engine meets U.S. EPA Tier 4 Final emission standards.
- Travel between sites easier with travel speeds up to 35 kph (21.7 mph).
- From dirt to asphalt, the excavator matches your needs to get the job done in a timely, efficient manner.
- The advanced hydraulic system provides the optimum balance of power and efficiency while giving you the control you need for precise working requirements.
- With up to 14 percent more swing torque, you can get the job done faster to move on to the next one. The dedicated swing pump provides consistent power for better multitasking capabilities.
- Auxiliary hydraulic options give you the versatility to use a wide range of Cat attachments.
- Don't let the temperature stop you from working. The excavator has a standard high-ambient temperature capability of 52°C (125°F) and cold start capability of -18°C (0°F).
- Standard Product Link™ provides location, machine hours, fuel usage, productivity, idle time, diagnostic codes, and other machine data on demand through the VisionLink online interface, helping you improve jobsite efficiency and lowering operating costs.

Lower Maintenance Costs

- Quickly check and service your machine with daily maintenance points accessible from ground level.
- Check the engine oil level quickly and safely from the ground.
- Save up to 10 percent in maintenance parts with the new, longer lasting filters.
- Track your machine's filter life and maintenance intervals on the in-cab monitor.
- Two levels of fuel filtration protect the engine from dirty diesel.
- The new hydraulic oil filter provides improved filtration performance, anti-drain valves to keep oil clean when the filter is replaced, and longer life with a 3,000-hour replacement interval – 50 percent longer than previous filter designs.
- S•O•SSM ports are located at ground level, simplifying maintenance and allowing for quick, easy extraction of fluid samples for analysis.
- Stow your gear with plenty of in-cab storage beneath and behind the seat, overhead, and in the consoles. A cup holder, bottle holder, and coat hook are also provided.
- Bluetooth[®] integrated radio allows for seamless mobile phone connection to listen to music and podcasts and for hands-free calling.
- Easily adjust to your ideal temperature with the touchscreen monitor or jog dial.



Cat® M316 Wheeled Excavator

Work in Comfort

- Choose between Deluxe and Premium cab options.
- The Deluxe seat is heated and air adjustable while the Premium seat is heated, cooled, and adjusts automatically.
- Get in and out of the cab easier using the tip-up left console.
- Feel more comfortable in the cab while you work with reduced cab vibrations from advanced viscous mounts.
- Control the excavator comfortably with easy-to-reach controls.

Simple to Operate

- Start the engine with the push-to-start button, a Bluetooth key fob, or the unique Operator ID function.
- Program your power mode and joystick preferences using Operator ID; the excavator remembers your settings each time you go to work.
- Navigate quickly on the standard high-resolution 254 mm (10 in) touchscreen monitor or with the aid of the jog dial control.
- Not sure how a function works or how to maintain the excavator? Simply access the operator's manual on the touchscreen monitor.
- The auto axle lock presses the pedal for you to reduce your overall number of actions. The machine automatically detects when the service brake and axle need to be locked or unlocked. It releases automatically when you press the travel pedal.

Safety

- Access daily maintenance points from ground level.
- Keep your excavator secure with Operator ID. Use your PIN code on the monitor to enable the pushbutton starting feature.
- The standard ROPS cab meets ISO 12117-2:2008 requirements.
- Enjoy better visibility into trenches, in each swing direction, and behind you with the help of smaller cab pillars, larger windows, and a flat engine hood design. Rearview and side-view cameras are standard.
- The service platform design provides easy, safe, and quick access to upper service platform; the service platform steps use anti-skid punch plate to prevent slipping.
- The standard hydraulic lockout lever isolates all hydraulic and travel functions in the lowered position.
- Swing lock prevents front linkage from moving as you travel.
- Ground-level shut-off switch stops all fuel to the engine when activated and shuts down the machine.

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
CAB			UNDERCARRIAGE AND STRUCTURES		
ROPS, sound suppression	✓		10.00-20 16 PR, dual tires		✓
Deluxe cab		✓	10.00-20 solid, dual tires		✓
Premium cab		✓	445/70R 19.5, single tires		✓
High-resolution 254 mm (10 in) LCD touchscreen monitor	✓		Automatic brake/axle lock	✓	
CAT TECHNOLOGY			2600 kg (5,732 lb) counterweight	✓	
Cat Product Link	✓		3300 kg (7,280) counterweight		✓
Remote flash/troubleshoot capability	✓		All wheel drive	✓	
ENGINE			ELECTRICAL SYSTEM		
Power mode selector	✓		LED lights on boom and cab	✓	
One-touch low idle with auto engine speed control	✓		LED lights on chassis (left-hand, right-hand) and counterweight		✓
Auto engine idle shutdown	✓		Programmable time-delay LED working lights	✓	
52°C (125°F) high-ambient cooling capacity	✓		Roading and indicator lights, front and rear	✓	
-18°C (0°F) cold start capability	✓		Maintenance free batteries	✓	
Double element air filter with integrated precleaner	✓		Centralized electrical disconnect switch	✓	
Biodiesel capability up to B20	✓		Electrical refueling pump		✓
HYDRAULIC SYSTEM			SERVICE AND MAINTENANCE		
Automatic swing brake	✓		Sampling ports for Scheduled Oil Sampling (S•O•S)	✓	
Auto hydraulic oil warm up	✓		Ground-level and platform-level engine oil dipsticks	✓	
Electronic main control valve	✓		Automatic lubrication system for implement and swing system		✓
Boom and stick drift reduction valves	✓		SAFETY AND SECURITY		
Slider joysticks (2 types)		✓	Rear and side-view cameras	✓	
Combined flow/high-pressure auxiliary circuit	✓		360° visibility		✓
Quick coupler circuit	✓		Wide angle mirrors	✓	
Boom and stick lowering check valves		✓	Ground-level engine shutoff switch	✓	
SmartBoom™		✓	Anti-skid plate	✓	
Ride control		✓	Signaling/warning horn	✓	
Joystick steering		✓			
Separate dedicated swing pump	✓				
BOOM AND STICKS					
5205 mm (17'1") Variable Adjustable boom		✓			
2500 mm (8'2") stick	✓				

Not all features are available in all regions. Please check with your local Cat dealer for specific offering availability in your area.

For additional information and additional regional offerings, refer to the Technical Specifications brochure available at www.cat.com or your Cat dealer.

Cat® M316 Wheeled Excavator

Technical Specifications

Engine

Engine Model	C4.4	
Engine Power (ISO 14396:2002)	110 kW	148 hp
Bore	105 mm	4 in
Stroke	127 mm	5 in
Displacement	4.4 L	268.5 in ³
<ul style="list-style-type: none"> Meets U.S. EPA Tier 4 Final emission standards. Recommended for use up to 3000 m (9,843 ft) altitude with engine power derate above 3000 m (9,843 ft). Rated speed 2,000 rpm. 		

Hydraulic System

Main System – Maximum Flow – Implement	275 L/min	73 gal/min
Maximum Pressure – Equipment	35 000 kPa	5,076 psi
Maximum Pressure – Travel	35 000 kPa	5,076 psi
Maximum Pressure – Swing	35 000 kPa	5,076 psi

Swing Mechanism

Swing Speed	10.2 rpm	
Maximum Swing Torque	44 kN-m	32,560 lb-ft

Machine Weight

Operating Weight	16 510 kg	36,400 lb
<ul style="list-style-type: none"> Operating weight includes full fuel tank, operator, 10.00-20 tires, VA boom, 2500 mm (8' 2") stick, 2600 kg (5,732 lb) counterweight, undercarriage, and 4 outriggers. 		

Service Refill Capacities

Fuel Tank	350 L	92.5 gal
Cooling System	24 L	6.3 gal
Engine Oil	13 L	3.4 gal
Diesel Exhaust Fluid (DEF)	30 L	7.9 gal
Final Drive	2.5 L	0.7 gal
Hydraulic System (including tank)	260 L	68.7 gal
Hydraulic Tank	120 L	31.7 gal

Dimensions

Boom	5205 mm (17' 1")	
Stick	2.5 m (8' 2")	
Bucket	GD 0.8 m ³ (1.05 yd ³)	
Shipping Height (top of cab)	3194 mm	10' 6"
Support Point	3870 mm	12' 8"
Shipping Length	8630 mm	28' 4"
Tail Swing Radius	2350 mm	7' 9"
Counterweight Clearance	1301 mm	4' 3"
Ground Clearance	395 mm	1' 4"
Undercarriage Length	4970 mm	16' 4"
Wheel Base	2550 mm	8' 4"

Working Ranges and Force

Boom Type	VA Boom	
Stick	R2.5 (8' 2")	
Bucket	GD 0.8 m ³ (1.05 yd ³)	
Loading Height	7140 mm	23' 5"
Cutting Height	10 110 mm	33' 2"
Digging Depth	5630 mm	18' 6"
Reach at Ground Level	8970 mm	29' 5"
Vertical Wall Digging Depth	4410 mm	14' 6"

- Range values are with dual pneumatic tires (10.00-20).
- Range values are calculated with a GD bucket (CW) and CW-30 quick coupler with a tip radius of 1484 mm (4' 10").

Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.85 kg of refrigerant which has a CO₂ equivalent of 1.216 metric tonnes.

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com.

© 2020 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Product Link, SmartBoom, S•O•S, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ3003-01 (11-2020)
Replaces AEXQ3003
Build Number: 07A
(N Am)

