

CAT® C1.1

EU STAGE V/U.S. EPA TIER 4 FINAL

18.4 KW/24 HP

INDUSTRIAL ENGINE



The C1.1 is an indirect injection industrial diesel engines that meets both EU Stage V and U.S. EPA Tier 4 Final without the need for electronic control, aftertreatment or exhaust gas recirculation. Naturally aspirated or turbocharged for improved low speed torque, the C1.1 is available with factory configurable options to minimize the cost of machine development and of manufacturing.



FEATURES AND BENEFITS

RELIABLE POWER

Manufactured in some of the world's most modern and highly-automated production facilities, the Cat® C1.1 is proven to deliver durable power and offers a wide range of customization options that refuse to compromise quality and durability.

COMPACT SIZE

With a 18.4 kW (24 hp) power rating, the C1.1 and the C1.1 turbo allows OEMs to consider different installation, operating and commercial requirements. These models are particularly adapted to machines where power from a small package is crucial. And for jobs that require that extra bit of power, there's a turbocharged option that delivers in almost any condition, at any altitude.

QUIET WORK

The stiff block and indirect injection system in the C1.1 were built for quiet so worksites are safer, operators are less fatigued and noise levels in regulated areas aren't exceeded.

SPECIFICATION

Cylinders	3
Displacement, litres (in ³)	1.1 (67.1)
Aspiration	Naturally aspirated or turbocharged
Bore and stroke, mm (in)	77 x 81 (3.0 x 3.2)
Maximum power, kW (hp)	18.4 (24)
Rated speed, rpm	2800
Maximum torque, Nm (lb ft) @ rpm	86 (63.4) @ 1600
Combustion system	Indirect injection
Weight, kg (lb)	96 (211)
Rotation (viewed from flywheel)	Anti-clockwise

For additional information on all your power requirements, visit www.cat-industrial.com

All information in this document is substantially correct at time of printing and may be altered subsequently.
Photographs are for illustrative purposes only and may not reflect final specification.
Final weight and dimensions will depend on completed specification.
Information subject to selected configuration, and subject to change without notice.
Performance measured per ISO 14396:2002

LEHH20149-00 (01-21)

© 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.





CAT® C1.1

EU STAGE V/U.S. EPA TIER 4 FINAL

18.4 KW/24 HP



INDUSTRIAL ENGINE



	Naturally aspirated	Turbocharged
Length (including fan), mm (in)	491 (19.3)	500 (19.7)
Width, mm (in)	400 (15.8)	513 (20.2)
Height, mm (in)	576 (22.7)	588 (23.1)
Weight, kg (lb)	96 (211)	108 (240)

For additional information on all your power requirements, visit www.cat-industrial.com

All information in this document is substantially correct at time of printing and may be altered subsequently. Photographs are for illustrative purposes only and may not reflect final specification. Final weight and dimensions will depend on completed specification. Information subject to selected configuration, and subject to change without notice. Performance measured per ISO 14396:2002

LEHH20149-00 (01-21)

© 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.