



OPTIONS AND ACCESSORIES KIT GUIDE

FOR COMPACT WHEEL LOADERS

MODEL (SERIAL NUMBER PREFIX):

910 (JW2), 914 (JC3), 920 (SL4)

910M (H22), 914M (H24), 918M (H26)

910K (AY4, L22), 914K (BF4, CD2, L24), 920K (B98)



Option/Accessory.....	Page Number
GLOBALLY AVAILABLE KITS.....	3-21
COMFORT AND CONVENIENCE.....	3
Ride Control.....	3
Tool Box.....	3
EMISSIONS AND REGULATIONS.....	4
License Plate.....	4
Software Option for 40 kph (25 mph) Speed.....	4
ENHANCEMENTS AND VISIBILITY.....	5-6
Front View Camera.....	5
Rear View Camera.....	5
Working Lights – LED.....	6
GUARDING.....	7-12
Crankcase Guard.....	7
Driveshaft Guard.....	7
Fender Mud Flaps.....	8
Fender Rear – Standard.....	8
Fender Rear – Wide.....	9
Front Fenders – Metal.....	9
Front Roding Light Guard.....	10
Hitch Guard.....	10
Powertrain Guard.....	11
Rear Lights Guarding.....	11
Rear Radiator Guard.....	12
MAINTENANCE IMPROVEMENT.....	13
Engine Bay Lights.....	13
Product Link, Elite.....	13
PERFORMANCE AND PRODUCTIVITY.....	14-21
Aggregate Counterweight.....	14
Snow / Middle Counterweights.....	14
Engine Heater 120V.....	15
Engine Heater 240V.....	15
Kickout Sensors.....	15
High Flow Jumper Lines.....	16
Standard Flow Single Jumper Lines.....	16
Hydraulic Supply – Coupler Ready – All Couplers.....	17
Hydraulic Supply for Quick Coupler IT and ISO.....	17
Hydraulic Valve Conversion from 2 Valve to 3 Valve.....	18
Hydraulic Valve Conversion from 3 Valve to 4 Valve.....	18
Quick Coupler – Fusion.....	19
Quick Coupler – ISO.....	19
Quick Coupler – IT.....	20
Reversing Fan.....	20
Work Tool Harness.....	21
SECURITY.....	21
Machine Security System (MSS).....	21


Option/Accessory.....	Page Number
JAPAN ONLY KITS.....	22-27
EMISSIONS AND REGULATIONS.....	22-23
Beacon Ready – Mount.....	22
LED Beacon.....	22
Xenon Beacon.....	23
Tachograph.....	23
GUARDING.....	24
Fender Mud Flaps.....	24
PERFORMANCE AND PRODUCTIVITY.....	25-26
Hydraulic Valve Conversion from 2 Valve to 4 Valve.....	25
Standard Twin Jumper Lines.....	25
Rims.....	26
SECURITY.....	27
Machine Security System – Two Man Cab.....	27

GLOBALLY AVAILABLE KITS

COMFORT AND CONVENIENCE

Ride Control


Improves ride quality when traveling. Provides multi-accumulator system to absorb shock and reduce machine bounce when traveling.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	588-8015	Recommended Dealer Install

Tool Box

Kit provides a tool box kit which can be installed on a finished built machine to add an external tool box behind the left-hand access ladder.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	532-6741*	1.0 Hour
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

*Cannot be used on Japan models with mid-mount snow counterweights.

EMISSIONS AND REGULATIONS

License Plate


Provides a square plate to mount the registered license plate to be shown on the rear of the machine, including the light to road at night.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	599-1337	1.0 Hour
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	AY4, L22, BF4, CD2, L24, B98		

Software Option for 40 kph (25 mph) Speed

Kit provides the link to the software option key to upgrade a machine from 20 kph (12 mph) to 40 kph (25 mph). Includes the 40 kph (25 mph) decals Enable through ET software.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	599-9655*	Recommended Dealer Install

*This kit has software enabled features that must be activated by a Cat dealer. Image used is for illustrative purposes only. Machine features may differ from photo due to reproduction limitations of the photograph.

ENHANCEMENTS AND VISIBILITY

Front View Camera

Includes a camera, display, harness, brackets and hardware to mount the forward facing camera system. The camera is mounted to an external breakaway bracket in the top right corner of the cab. The display is mounted in the upper right corner of the cab and replaces an internal mirror. The forward camera may be required for local European Union (EU) requirements.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	592-3039*	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

*This kit has software enabled features that must be activated by a Cat dealer.

Rear View Camera

Includes rear view camera, harness, display and mounting. Display will mount and replace the existing rear view mirror and bracket. Rear camera located in the top of the rear radiator guard door.




Note: Camera image may vary depending on part number.

Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	598-6178*	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		
914K, 920K	BF4, B98		

*This kit has software enabled features that must be activated by a Cat dealer.

Working Lights – LED

Kit provides two (2) additional forward facing and two (2) rear facing cab mounted LED, wide flood work lights. LED lighting provides brighter lighting and longer life.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	598-6440	1.0 Hour

GUARDING


Crankcase Guard

Provides engine crankcase guard that mounts underneath the rear frame.

540-7051





588-8081



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914	JW2, JC3	540-7051	1.0 Hour
910M, 914M	H22, H24		
910K, 914K	L22, BF4, L24		
920	SL4	588-8081	
918M	H26		

Driveshaft Guard

Provides driveshaft guard that mounts underneath the front frame.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914	JW2, JC3	546-6667	1.5 Hours
910M, 914M	H22, H24		
910K, 914K	L22, BF4, L24		
920	SL4	546-6668	
918M	H26		
920K	B98		

Fender Mud Flaps

Provides mud flaps that attach to non-metal fenders to extend the rear coverage of the front and rear fenders.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	593-1439*	1.0 Hour
910M, 914M, 918M	H22, H24, H26		
910K, 914K	L22, L24		

*Not for use with 20.5" tires.

Fender Rear – Standard

Provides extended coverage of the rear tires with non-metallic rear fenders. For use only with 15.5" or 17.5" tires.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	593-1500*	2.0 Hours
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	AY4, L22, BF4, CD2, L24, B98		

*Not for use with 20.5" tires.

Fender Rear – Wide

Provides extended coverage of the rear tires with non-metallic rear fenders. For use only with 20.5" tires. Solid tire shown in photo is not typical of application.



Model	Serial Number Prefix	Part Number	Estimated Install Time
920	SL4	593-1499	2.0 Hours
918M	H26		
920K	B98		

Front Fenders – Metal

Kit provides front metal fenders for use in severe applications such as waste and scrap. The metal fenders will not prevent tire spray and is designed for waste and scrap applications.



Model	Serial Number Prefix	Part Number	Estimated Install Time
914, 920	JC3, SL4	593-1336	0.5 Hour
914M, 918M	H24, H26		
914K	CD2, L24		

Front Roding Light Guard


Provides two (2) front light guards that mount over the headlights.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	541-9748	1.5 Hours
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

Hitch Guard


Provides protection to hitch area of the rear frame, preventing debris from entering the frame, while allowing visibility to service points.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	546-6665	1.0 Hour
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

Powertrain Guard

Provides lower transmission guard that mounts underneath the rear frame.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	546-6666	1.5 Hours
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

Rear Lights Guarding

Provides two (2) rear light guards that mount over the taillights.





Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	588-8080*	1.0 Hour

* Not compatible with Heavy Duty Rear Guard

Rear Radiator Guard

Provides protection to rear of the machine and cooling package. Includes swing out guard for cooling access and mounting for rear camera.




Model	Serial Number Prefix	Part Number	Estimated Install Time
914, 920	JC3, SL4	588-8082	2.5 Hours

MAINTENANCE IMPROVEMENT

Engine Bay Lights


Provides four (4) LED engine enclosure lights to illuminate the way for checking oil and coolant levels, along with refueling the machine in dark conditions. LED lighting provides brighter lighting and longer life.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	598-8610	Recommended Dealer Install

Product Link, Elite

Includes Network Manager for conversion of Product Link Pro to Product Link Elite. Required to field install Cat Production software.





Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	595-3908*	Recommended Dealer Install

*This kit has software enabled features that must be activated by a Cat dealer.

PERFORMANCE AND PRODUCTIVITY

Aggregate Counterweight



Provides additional frame mounted counterweights of 320 kg (705 lb).



Model	Serial Number Prefix	Part Number	Estimated Install Time
914, 920	JC3, SL4	588-8158	2.0 Hours

Snow/Middle Counterweights

Frame mounted counterweights, that provides an additional 320 kg (705 lb) to the machine, to increase traction capability.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	556-8805*	1.0 Hour
910M, 914M, 918M	H22, H24, H26		

*Cannot be used with tool box.

Engine Heater 120V


Provides 120V block heater to improve cold start performance.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	595-1854	1.0 Hour

Engine Heater 240V




Provides 240V block heater to improve cold start performance.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	595-1855	1.0 Hour

Kickout Sensors

Provides sensors and electrical harnesses to add return to dig (kickout) and parallel lift electronic control to the loader arm.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914	JW2, JC3	592-9244*	4.0 Hours

*This kit has software enabled features that must be activated by a Cat dealer.

High Flow Jumper Lines

Provides 3rd Function High Flow jumper lines and threaded flat face, connect under pressure, quick disconnects mounted to the coupler. Extra parts included for both standard and high lift machines.




Model	Serial Number Prefix	Part Number	Estimated Install Time
920	SL4	592-4024*	Recommended Dealer Install
918M	H26		
920K	B98		

* Recommended for use with High flow auxiliary function work tools.

Standard Flow Single Jumper Lines

Provides 3rd function standard flow jumper lines twist to connect couplings mounted to the coupler. Recommended for use with standard flow auxiliary function work tools. Contains extra parts for both standard and high lift machines.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910*, 914, 920	JW2*, JC3, SL4	592-4025	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

*Provides 3rd and 4th function.

Hydraulic Supply – Coupler Ready – All Couplers


Provides coupler valve and hydraulic lines to convert a 2-valve pin on standard lift machine into a 2-valve coupler ready machine.



Model	Serial Number Prefix	Part Number	Estimated Install Time
914	JC3	593-3141	Recommended Dealer Install
920	SL4	593-5422	
918M	H26		
920K	B98		

Hydraulic Supply for Quick Coupler IT and ISO

Provides coupler valve and hydraulic lines to convert a 2-valve pin on standard lift machine into a 2-valve coupler ready machine.





Model	Serial Number Prefix	Part Number	Estimated Install Time
910	JW2	592-7863*	Recommended Dealer Install
910M	H22		
910K	L22		

*Not for use with a Fusion Coupler.

Hydraulic Valve Conversion from 2 Valve to 3 Valve

Provides joystick and hydraulic lines to convert a 2-valve machine to 3-valve.





Model	Serial Number Prefix	Part Number	Estimated Install Time
910	JW2	592-8386*	Recommended Dealer Install
914	JC3	592-8387*	
920	SL4	592-8427*	

*Valve and tie rods not included but are required to complete install. Please contact your Cat dealer.

Hydraulic Valve Conversion from 3 Valve to 4 Valve

Provides joystick and hydraulic lines to convert a 3-valve machine to 4-valve.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910	JW2	593-0278*	Recommended Dealer Install
914	JC3	593-0279*	
920	SL4	593-0280*	

*Valve and tie rods not included but are required to complete install. Please contact your Cat dealer.

Quick Coupler – Fusion

Provides constant pressure wedge fusion coupler, along with an electro-hydraulic actuation system, activated from the cab.




Model	Serial Number Prefix	Part Number	Estimated Install Time
914, 920	JC3, SL4	592-6217*	Recommended Dealer Install
918M	H26		
920K	B98		

*Compatible with machines that have coupler hydraulic lines and valve installed.

Quick Coupler – ISO 23727

Provides an ISO interface coupler, with lock valve cylinder, along with an electro-hydraulic actuation system, activated from the cab. This coupler is compatible with many work tools from other manufacturers.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	592-6215*	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

*Compatible with machines that have coupler hydraulic lines and valve installed.

Quick Coupler – IT

Provides constant pressure horizontal pin IT coupler, along with an electro-hydraulic actuation system, activated from the cab.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914	JW2, JC3	592-6210*	Recommended Dealer Install
910M, 914M	H22, H24		
910K, 914K	L22, BF4, L24		
920	SL4	592-6213*	
918M	H26		
920K	B98		

*Compatible with machines that have coupler hydraulic lines and valve installed.

Reversing Fan


Kit provides a hydraulically operated demand fan with reversing option and additional heat wrap for various components. Includes automatic and manual controls for fan reversal. Recommended for applications with a high content of airborne debris.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	588-7091	Recommended Dealer Install

Work Tool Harness

Provides an electrical harness to allow electro-mechanical work tools to be controlled by the machine.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	594-2120	1.5 Hours

SECURITY

Machine Security System (MSS)

Kit provides a programmable system to manage access to machine. Includes programmable keypad and headliner.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	556-8803*	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		
914K, 920K	BF4, B98		


*This kit has software enabled features that must be activated by a Cat dealer.

JAPAN ONLY KITS

EMISSIONS AND REGULATIONS

Beacon Ready – Mount

Provides mounting brackets and hardware to mount on the cab roof to accommodate a wide beacon, such as a LED or Xenon beacon.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	556-2844*	3.0 Hours
910M, 914M, 918M	H22, H24, H26		

*Beacon not included.

LED Beacon

Large double LED beacon to mount to the front cab roof.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	591-5821*	1.0 Hour
910M, 914M, 918M	H22, H24, H26		

*Requires the Beacon Ready – Mount kit 556-2844 for installation.

Xenon Beacon

Large double Xenon beacon to mount to the front cab roof.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	591-5820*	1.0 Hour
910M, 914M, 918M	H22, H24, H26		

*Requires the Beacon Ready – Mount kit 556-2844 for installation.

Tachograph

Kit provides speedometer.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	532-6746	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		

GUARDING

Fender Mud Flaps

Provides mud flaps that attach to fenders to extend the rear coverage of the front and rear fenders.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914	JW2, JC3	593-1455	1.0 Hour
910M, 914M	H22, H24		
910K, 914K	AY4, CD2		
920	SL4	593-1471	
918M	H26		

PERFORMANCE AND PRODUCTIVITY

Hydraulic Valve Conversion from 2 Valve to 4 Valve

Provides joystick and hydraulic lines to convert a 2-valve machine to 4-valve.




Model	Serial Number Prefix	Part Number	Estimated Install Time
910	JW2	593-2539*	Recommended Dealer Install
914	JC3	593-2540*	
920	SL4	593-2541*	

*Valve and tie rods not included but are required to complete install. Please contact your Cat dealer.

Standard Twin Jumper Lines


Kit provides twin function jumper lines and flat face quick disconnects mounted to the coupler. Recommended for use with work tools with auxiliary functions.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	592-4023	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		
910K, 914K, 920K	L22, BF4, L24, B98		

Rims

Provides a set of four rims for use with tires. Enables easier switching between different types of tires in the field.





Model	Serial Number Prefix	Part Number	Estimated Install Time
910	JW2	559-2497*	Recommended Dealer Install
910M	H22		
914, 920	JC3, SL4	559-2498**	
914M, 918M	H24, H26		

*15xR24
**13xR25

SECURITY

Machine Security System (MSS) – Two Man Cab

Kit provides a programmable system to manage access to machine. Includes programmable keypad.



Model	Serial Number Prefix	Part Number	Estimated Install Time
910, 914, 920	JW2, JC3, SL4	562-3462*	Recommended Dealer Install
910M, 914M, 918M	H22, H24, H26		

*This kit has software enabled features that must be activated by a Cat dealer.

AEXQ3038-01
Replaces AEXQ3038
January 2022
(Global)

© 2022 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

