2021 Cat EXTEND CVA Planned Maintenance Schedule - Compact Track Loader
See Contract for applicable Intervals. Extreme Duty Intervals are only available on select contracts.

Interval		Sales Model	239D	239D3	249D	249D3	259D	259D3	259D3LRC	279D	279D3	279D3LRC	289D	289D3	289D3LRC	299D2	299D3	299D2XHP	299D3XE	
		Serial Number Prefix	BL9	KE9, HC9	GWR	R9E, P9C	FTL	TE9, CW9	TLS, MC9	GTL	Z9E, RB9	SZ9, TB9	TAW	BT9, JX9	KX9, LA9	FD2	CY9, DY9	DX2, HLM	AN9, BX9, LB3, XES	
PM1 - every 250 & 750 Hours	CVA with SOS	Fluids SOS - Number of bottles and analysis	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
PM 2 - 500, 1,500, 2,500, 3,500, 4,500, etc. Hours	CVA with SOS	SOS Coolant Sample Level 2 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Fluids SOS - Number of bottles and analysis	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
	CAT Extend CVA	Cat GO SYN (SAE 75W-140)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	
		Engine Oil Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		In-line Fuel Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		FWS Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Breather Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Fresh Air Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Recirculating Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	
PM 3 - 1,000, 3,000, 5,000, 7,000, 9,000 Hours	CVA with SOS	SOS Coolant Sample Level 1 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Fluids SOS - Number of bottles and analysis	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
	CAT Extend CVA	A/C Compressor Belt	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Belt	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Hydraulic Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Seal (Housing)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Seal (Housing)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Seal (Plug)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Cat GO SYN (SAE 75W-140)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	
		Engine Oil Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		In-line Fuel Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		FWS Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Breather Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Fresh Air Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Recirculating Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	
PM 4 - 2,000, 4,000, 6,000, 8,000, & 10,000 Hours	CVA with SOS	SOS Coolant Sample Level 2 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Fluids SOS - Number of bottles and analysis	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
	CAT Extend CVA	A/C Compressor Belt	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Belt	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Hydraulic Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Seal (Housing)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Seal (Housing)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Seal (Plug)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Cat GO SYN (SAE 75W-140)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	
		Engine Oil Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		In-line Fuel Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		FWS Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Breather Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Fresh Air Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Recirculating Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed Cab
		Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	

CAT with SOS includes the identified SOS fluid sampling costs.
Consult your CVA agreement to determine SOS is part of your contract

Exclusions

Ensure that all safety information, warnings, and instructions are read and understood before any operation or any maintenance procedures are performed.
The user is responsible for the performance of maintenance, including all adjustments, the use of proper lubricants, fluids, filters, and the replacement of components due to normal wear and aging. Failure to adhere to proper maintenance intervals and procedures may result in diminished performance of the product and/or accelerated wear of components. Use mileage, fuel consumption, service hours, or calendar time, WHICH EVER OCCURS FIRST, to determine the maintenance intervals.
Products that operate in severe operating conditions may require more frequent maintenance. This chart is not intended to be a comprehensive list of *all* maintenance activities that may be recommended or required and does not contain fluids schedules or requirements associated with the above maintenance activities.

* Valve lash checks are recommended every 1,000 hours
** Coolant is recommended to be replaced every 2 years, unless extended by utilizing Extended Life Coolant (ELC) additive.
*** The maintenance manual recommends cleaning or replacing the DPF with a new or remanufactured DPF every 3000 hours
**** Seat Belts are recommended to be replaced every 3 years.
***** Extreme Duty Intervals only relate to select Extreme Duty Contracts
***** A/C Receiver/Dryer recommended to replace every 2000 hour interval on closed cabs

This marketing tool does not represent a contract or obligation of any kind between Caterpillar Financial Aftermarket Solutions Corporation or its affiliates, and the equipment owner. For details on any Cat® Customer Value Agreement (CVA), including a complete description of the terms, conditions, and/or exclusions, contact a participating Cat dealer.

All graphics and lists in this marketing tool are provided solely for general information purposes and are not intended to be a solicitation or an offer to purchase any product or service.

To the extent that the above publication(s), bulletin(s), and/or any designated contract(s) are ambiguous or inconsistent with the CVA contract language, the terms of the CVA contract shall govern.

© 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.