		2021 Cat EXTEND CVA Planned Maintenance Schedule - Small Wheel Loaders See Contract for applicable intervals. Extreme Duty Intervals are only available on select contracts.		
	Sales Model	926M	930M	938M
	Serial Number	LTE, W5L	KTG, F5K, J5K	J3R, P5K
CVA with SOS	Fluids SOS - Number of bottles and analysis	1	1	1
	SOS Coolant Sample Level 2 bottle and analysis	X	×	X
CVA with SOS		5	5	5
CAT Extend CVA	Eng Oil Filter Flement	×	×	X
	Fuel In-line	×	×	X
	Fuel Primary	x	x	X
	Fuel Secondary	x	x	X
	Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested
CVA with SOS				X
	Fluids SOS - Number of bottles and analysis			5
	Eng Oil Filter Element			X
	Fuel In-line		X	X
	Fuel Primary	X	X	X
	Fuel Secondary	x	X	X
CAT Extend CVA	Engine Air Primary Element	x	x	x
	Engine Air Secondary Element	X	X	X
	Fresh Air Element	X	X	X
	Recirculating Element	X	X	X
	Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested
	COC Content County Lavel 2 battle and analysis	v		X
CVA with SOS				5
	·			X
	-			X
				X
				X
	•			
	•			X X
CAT Extend CVA				X
				X
				X
	·			X
				X
	Hansmission Oil Filler	X	X	X
	CVA with EOS  CAT Extend CVA  CVA with SOS  CAT Extend CVA  CVA with SOS	Serial Number  CVA with 505 Fluids SOS - Number of bottles and analysis  SOS Coolant Sample Level 2 bottle and analysis  Eng OF Fluids SOS - Number of bottles and analysis  Eng OF Fluid SOS - Number of bottles and analysis  Eng OF Fluid Flu	Sales Model 928M  Sales Model 928M  Serial Number LTE, WSL  CVA will 906 Fluids SOS - Number of bottles and analysis 1  CVA will 906 Fluids SOS - Number of bottles and analysis 5  Fluids SOS - Number of bottles and analysis 5  Eng Oil Filter Element X  Fuel In-line X  CAT Extend CVA  Fuel Primary X  Fuel Secondary Customer Provided T/A-1 Inspection (CAT app) Requested  CVA will 900 Fluids SOS - Number of bottles and analysis 5  Eng Oil Filter Element X  Fuel Primary X  Fuel Secondary Customer Provided T/A-1 Inspection (CAT app) Requested  CVA will 900 Fluids SOS - Number of bottles and analysis 5  Eng Oil Filter Element X  Fuel In-line X  Fuel Secondary Customer Provided T/A-1 Filter Element X  Fuel Secondary Customer Provided T/A-1 Filter Element X  Fuel Secondary Customer Provided T/A-1 Filter Element X  Fuel A/A Filter Element X  Fuel SOS Coolant Sample Level 2 bottle and analysis 5  Eng Oil Filter Element X  Fuel Socondary Element X  Fuel Rescondary Element X  Fuel Rescondary Element X  Fuel Rescondary Element X  Fuel Rescondary Element X  Fuel A/A Filter Element X  Fuel Rescondary Element X  Fuel Rescondary Element X  Fuel Rescondary Element X  Fuel A/Filter Element X  Fuel Rescondary Element X  Fuel Rescondary Element X  Fuel A/Filter Element X  Fuel A/Filter Element X  Fuel A/Filter Element X  Fuel Rescondary Element X  Fuel Rescondary Element X  Fuel A/Filter Element X  Fuel A/Filter Element X  Fuel A/Filter Element X  Fuel Rescondary Elem	Sales Model   928M   930M

CAT with SOS includes the identified SOS fluid sampling costs.

Consult your CVA agreement to determine SOS is part of your contract

## EXCLUSIONS

Ensure that all safety information, warnings, and instructions are read and understood before any operation or any maintenance procedures are performed.

The user is responsible for the performance of maintenance, including all adjustments, the use of proper lubricants, fluids, filters, and the replacement of components due to normal wear and aging, failure to adhere to proper maintenance intervals and procedures may result in diminished performance of the product and/or accelerated wear of components. Use mileage, fuel consumption, service hours, or calendar time, WHICH EVER OCCURS PIRST, to determine the maintenance intervals. Products that operate in severe operating conditions may require more frequent maintenance. This chart is not intended to be a comprehensive list of all maintenance activities that may be recoming required and does not contain fluids schedules or requirements associated with the above maintenance activities.

Coolant is recommended to be replaced every 2 years, unless extended by utilizing Extended Life Coolant (ELC) additive.

The maintenance manual recommends ideaning or replacing the DPF (if applicable) with a new or remanufactured DPF every 3000 hours

Sext Belts are recommended to be replaced every 3 years.

Extreme Duty Intervals only relate to select Extreme Duty Contracts

This marketing tool does not represent a contract or obligation of any kind between Caterpillar Financial Aftermarket Solutions Corporation or its affiliates, and the equipment owner. For details on any Cat® Customer Value Agreement (CVA), including a complete description of the terms, conditions, and/or exclusions, contact a participating Cat dealer.

All graphics and lists in this marketing tool are provided solely for general information purposes and are not intended to be a solicitation or an offer to purchase any product or service.

To the extent that the above publication(s), bulletin(s), and/or any designated contract(s) are ambiguous or inconsistent with the CVA contract language, the terms of the CVA contract shall govern.

© 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

