

<p>CAT Extend CVA Contracts include parts kits only and do not contain CAT fluids or dealer supplied labor.</p> <p>CAT Protect CVA Contracts include parts kits, CAT fluids, Component Protection Plan, and dealer supplied labor.</p> <p>Consult your CVA agreement for information on contract starting point and interval arrangement.</p>	<p>CAT Extend CVA Contracts include parts kits only and do not contain CAT fluids or dealer supplied labor.</p> <p>CAT Protect CVA Contracts include parts kits, CAT fluids, Component Protection Plan, and dealer supplied labor.</p> <p>Consult your CVA agreement for information on contract starting point and interval arrangement.</p>
	<p>EXCLUSIONS</p> <p>Ensure that all safety information, warnings, and instructions are read and understood before any operation or any maintenance procedures are performed. The user is responsible for the performance of the maintenance, including all adjustments, the use of proper lubricants, fluids, filters, and the replacement of components due to normal wear and aging. Failure to adhere to proper maintenance intervals and procedures may result in diminished performance of the product and/or accelerated wear of components. Use ratings, fuel consumption, service hours, or calendar time, WHICHEVER OCCURS FIRST, to determine the maintenance intervals. Skidsteer in the above table with 1,000 hour of drain intervals assumes the machine is operated in a Standard Service Application, utilizes Cat Recommended Fluids, and maintains timely SIOS sampling. Consult model and serial number specific OMM for alternate drain and maintenance options. The maintenance activities in the table above reflect commonly required activities. Machines may require more frequent maintenance and/or additional parts, depending on factors such as severe applications or extreme operating and environmental conditions. This chart is not intended to be a comprehensive list of all maintenance activities that may be recommended or required and may not contain fluids, maintenance variables or additional requirements associated with the above maintenance activities. Refer to your CVA contract for specific terms associated with the agreement.</p> <p>Some recommended maintenance activities excluded from CVA contracts are listed below:</p> <ul style="list-style-type: none"> - Valve gaskets excluded for valve lash checks. - Coolers to be replaced every 2 years, unless extended by utilizing Extended Life Coolant (ELC) additive. *** The maintenance manual recommends cleaning or replacing the DPF with a new or remanufactured DPF every 5000 hours **** Seal Belts are recommended to be replaced every 3 years. ***** A/C Dryers are recommended to be replaced every 2000 hour interval. ***** Radiator caps are recommended to be replaced every 2000 hour interval.



CAT[®]
Financial