



Cat[®] 651

Wheel Tractor-Scraper

The 651 has rejoined our wheel tractor-scraper lineup. Delivering high levels of productivity, the 651 single engine earthmoving system is a wise choice on numerous large-scale projects by providing fast cycle times when working in lower grades and rolling resistance applications. First introduced into the Cat[®] wheel tractor-scraper lineup in 1962, the 651 continues to uphold its legacy as one of our signature machines. Its single engine power provides the ability to work with a Cat D10 or D11 push dozer, delivering ultra-fast load times and the ability to work in abrasive or rocky conditions. With improvements in productivity combined with enhancements in operator comfort and new safety features – Powered Access System and effective wet disc brakes – this machine offers high returns on investment and time.

Be More Productive

- Move more material with Advanced Productivity Electronic Control System (APECS), which allows the machine to better utilize engine power and torque.
- Set the desired top speed with Ground Speed Control, and the machine will find the gear that works best for the engine and the transmission, providing a lower fuel burn in speed reduced areas.
- The Machine Speed Limit feature replaces Top Gear Selection.
- Auto-Stall assists in quickly bringing the transmission to an operating temperature at start-up when working in colder climates.
- Cat Payload Estimator for scrapers achieves on-the-go weighing to deliver optimal payload and jobsite efficiency.

Work in Comfort

- Steer with less effort with the newly designed high-pressure steering system.
- Reduce up to 14 individual operator commands per cycle with Sequence Assist (optional attachment).
- Enjoy interior improvements and a more ergonomic work environment.
- Intuitive, ergonomic controls with multifunction display keep operators focused on their work.
- Maintain desired cab temperature with automatic temperature control.

Designed for Safety

- Get in and out of the cab easier with the new powered access ladder system.
- Enhance the operator's awareness of site surroundings with the optional Work Area Vision System (WAVS).
- Ground-level access to fuel fill and several maintenance points for easier and safer service.
- Seat belt indicator provides visual and audible alerts when the seat belt is not in use.

Easy to Operate

- Cat Advanced Ride Management (ARM) seat suspension reduces end stroke movement of the load cylinder for a smoother ride.
- Engine overspeed protection will automatically engage with no operator input when the machine is in eighth gear. The machine will assist in slowing the machine speed by canceling the throttle command and engaging the engine compression brake.



Cat® 651 Wheel Tractor-Scraper

Integrated Cat Technologies

- Access information anytime, anywhere with Vision Link® – use it to make informed decisions that boost productivity, lower costs, simplify maintenance, and improve safety and security on your jobsite.
- Product Link™ collects machine data that can be viewed online through web and mobile applications (optional attachment).

Execute Efficiency

- The Cat C18 tractor engine meets U.S. EPA Tier 4 Final and EU Stage V emission standards, contributing to lower fuel consumption.
- The new tractor hydraulic demand fan and required belt guarding help lower fuel consumption.

Standard Equipment and Optional Attachments

Standard equipment and optional attachments may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
POWER TRAIN			OPERATOR ENVIRONMENT (CONTINUED)		
Cat® C18 engine (U.S. EPA Tier 4 Final and EU Stage V)	✓		Keypad switches: throttle lock; wipers/washers; hazard lights; work lights on, off; information mode; messenger display; safety tab rocker switches, parking brake	✓	
Cat engine brake	✓		Seat belt, static two-piece	✓	
Electric start, 24V	✓		Steering wheel, tilt, telescoping, padded	✓	
Fan, hydraulic	✓		Windows, right side emergency egress	✓	
Ground-level engine shutdown	✓		Windows, sliding	✓	
Guard, crankcase	✓		Messenger display	✓	
Starting aid, ether	✓		Powered access ladder		✓
Braking system: primary and secondary, wet disc, hydraulic; parking, hydraulic released, spring-applied	✓		Seat – Cat Advanced Ride Management (ARM), Cat Comfort Series III, rotates 30 degrees	✓	
Transmission: 8-speed planetary powershift, ECPC control, APECS software, programmable top gear selection, transmission hold, differential lock, guard – power train, ground speed control, machine speed limit	✓		FLUIDS		
ELECTRICAL			Extended life coolant to -37°C (-34°F)	✓	
Alternator, 115 amp	✓		OTHER STANDARD EQUIPMENT – TRACTOR		
Batteries (4), 12V, 1,000 CCA, maintenance free	✓		Accumulators (brake and cushion hitch) with Canadian Registration Number (CRN)	✓	
Electrical system, 24V	✓		Fast oil change	✓	
Lighting system: headlights – halogen, turn signals with hazard functions – LED, floodlights, (2) cutting edge and (1) bowl, side vision – halogen	✓		Vandalism locks	✓	
Starting/charging receptacle	✓		Steering locks	✓	
OPERATOR ENVIRONMENT			Heater, engine coolant 120V	✓	
HVAC system, heat, AC, defrost	✓		OTHER ATTACHMENTS		
Thermostat control of HVAC system	✓		Cab beacon		✓
Coat hook	✓		Air horn		✓
Lunch box platform with holding strap	✓		Wiring group		✓
Diagnostic connection (2)	✓		SERVICE INSTRUCTIONS		
12V power ports (2)	✓		Film arrangement – U.S. (ANSI)		✓
Differential lock (1)	✓		Film arrangement – International (ISO)		✓
Dome courtesy light	✓		INTEGRATED TECHNOLOGIES		
Horn, electric	✓		Cat Production Measurement		✓
T-Handle implement control	✓		Product Link™	✓	
Radio ready	✓		Sequence Assist with Payload Estimator		✓
ROPS/FOPS cab, pressurized	✓				

Cat® 651 Wheel Tractor-Scraper

Technical Specifications

General Data

Fuel Tank Refill Capacity	860 L	227 gal
Shipping (split configuration)		
Tractor Width	3.90 m	12.80 ft
Tractor Height	4.52 m	14.83 ft
Scraper Width	3.93 m	12.9 ft
Scraper Height	3.90 m	12.80 ft
Scraper Capacity		
Struck	24.5 m ³	32.0 yd ³
Heaped	33.6 m ³	44.0 yd ³
Rated Load	47 200 kg	104,000 lb
Rated Load	46.5 mt	52.0 ton
Width of Cut	3.8 m	12.5 ft
Maximum Depth of Cut	440 mm	17.32 in
Maximum Depth of Spread	660 mm	26.0 in
Top Speed (loaded)	56.1 km/h	34.85 mph
180° Curb-to-Curb Turning Width (right)	13.85 m	45.4 ft
180° Curb-to-Curb Turning Width (left)	14.7 m	48.4 ft
Tire Size	40.5/75 R39 ** E-3	
Operating Weight (full fuel, no operator, configured with all factory attachments)		
Unloaded	65 772 kg	145,000 lb
With Rated Load	112 945 kg	249,000 lb

Engine

	Tractor	
Engine Model	Cat C18	
Rated Engine RPM	2,000 rpm	
Power – Net (SAE J1349/ISO 9249)	436 kW	585 hp
Power – Gross (SAE J1995)	475 kW	637 hp
Power – Engine (ISO 14396)	469 kW	629 hp
Emissions	U.S. EPA Tier 4 Final/ EU Stage V	

- Advertised power is tested per the listed standard revision in effect at the time of manufacture.

Safety Criteria Compliance Standards

Rollover Protective Structure (ROPS)	ISO 3471:2008 for up to 26 600 kg (58,643 lb)	
Falling Object Protective Structure (FOPS)	ISO 3449:2005 Level II	
Brakes	ISO 3450:2011	
Steering System	ISO 5010:2007	
Seat Belt	SAE J386:FEB2006	
Forward Horn and Reverse Alarm	ISO 9533:2010	
Operator Sound	ISO 6396:2008	
Exterior Sound	ISO 6395:2008	

Service Refill Capacities

	Tractor	
Crankcase	52 L	13.7 gal
Transmission System	136 L	35.9 gal
Cooling System	88.6 L	23.4 gal
Fuel Tank	860 L	227.2 gal
Hydraulic System	195 L	51.5 gal
Diesel Exhaust Fluid	30.5 L	8 gal

Travel Speeds (Runout)

Transmission Gear			
Eighth	56.1 km/h	34.8 mph	
Reverse	10.8 km/h	6.7 mph	



For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com.

© 2021 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Product Link, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.

AEXQ3246-00 (07-2021)
Build Number: WSR
(Global except Japan and China)

