

2021 Cat Convenience - Used CVA Planned Maintenance Schedule - Mini Hydraulic Excavator See Contract for applicable intervals. Extreme Duty Intervals are only available on select contracts.																							
Sales Model		303E2CR	303.5E2CR	303.5E2CR	303.5-07CR	303-07CR	304-07CR	305E2CR	305.5E2CR	307E2	308E2CRSB	306.8-07	307.5-07	308-07	308-07SR	308-07CR	308-07CR	308.5-07	309-07CR	310-07			
Interval	Serial Number Prefix	HMM, SOE	RKY	JWY	REB, CES	MY3, NXY	AX4	HSM	CR5	KC9	FJX, WBS	EG4	GW3	GW7	GX8	GK8	GG8	GW6, GX8	GZ8	GG9	GWT		
PM 1 - every 250 & 750 Hours	CVA with SOS	Fluids SOS - Number of bottles and analysis	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
PM 2 - 500, 1,500, 2,500, 3,500, 4,500, etc. Hours	CVA with SOS	SOS Coolant Sample Level 1 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	CAT Convenience - Used CVA	Fluids SOS - Number of bottles and analysis	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
		Hydraulic Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Oil Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Cab Fresh Air Filter	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		Cab Air Recirculation Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
		A/C Heater Filter Element	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		Fuel In-Line Element	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
FWS Element		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested		
PM 3 - 1,000, 3,000, 5,000, 7,000, 9,000 Hours	CVA with SOS	SOS Coolant Sample Level 1 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	IT Convenience - Used CVA	Fluids SOS - Number of bottles and analysis	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
		Final Drive Oil (Cat GO SAE 80W-90)	X (x2 qty)	X (x2 qty)	X (x2 qty)	-	-	-	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	
		Hydraulic Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine V-Belt	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		A/C Compressor Belt	-	-	X	-	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Oil Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Cab Fresh Air Filter	-	-	-	-	-	-	-	-	-	X	X	X	X	X	X	X	X	X	X	X	
Cab Air Recirculation Filter		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
A/C Heater Filter Element	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Fuel In-Line Element	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
FWS Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested		
PM 4 - 2,000, 4,000, 6,000, 8,000, & 10,000 Hours	CVA with SOS	SOS Coolant Sample Level 2 bottle and analysis	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
	IT Convenience - Used CVA	Fluids SOS - Number of bottles and analysis	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
		Final Drive Oil (Cat GO SAE 80W-90)	X (x2 qty)	X (x2 qty)	X (x2 qty)	-	-	-	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	X (x2 qty)	
		Fuel Cap Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Hydraulic Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine V-Belt	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		A/C Compressor Belt	-	-	X	-	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Oil Filter Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Primary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
		Engine Air Secondary Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
Cab Fresh Air Filter		-	-	-	-	-	-	-	-	-	X	X	X	X	X	X	X	X	X	X	X		
Cab Air Recirculation Filter	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X			
A/C Heater Filter Element	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Fuel In-Line Element	-	-	-	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
FWS Element	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
Customer Provided T/A-1 Inspection (CAT app)	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested	Requested		

CAT with SOS includes the identified SOS fluid sampling costs.
Consult your CVA agreement to determine SOS is part of your contract

EXCLUSIONS

Ensure that all safety information, warnings, and instructions are read and understood before any operation or any maintenance procedures are performed.
The user is responsible for the performance of maintenance, including all adjustments, the use of proper lubricants, fluids, filters, and the replacement of components due to normal wear and aging. Failure to adhere to proper maintenance intervals and procedures may result in diminished performance of the product and/or accelerated wear of components. Use mileage, fuel consumption, service hours, or calendar time, WHICH EVER OCCURS FIRST, to determine the maintenance intervals.
Products that operate in severe operating conditions may require more frequent maintenance. This chart is not intended to be a comprehensive list of all maintenance activities that may be recommended or required and does not contain fluids schedules or requirements associated with the above maintenance activities.

- * Valve lash checks are recommended every 1,000 hours
- ** Coolant is recommended to be replaced every 2 years, unless Convenience - Used by utilizing Convenience - Used Life Coolant (ELC) additive.
- *** The maintenance manual recommends cleaning or replacing the DPF with a new or remanufactured DPF every 3000 hours
- **** Seat Belts are recommended to be replaced every 3 years.
- ***** Extreme Duty Intervals only relate to select Extreme Duty Contracts

This marketing tool does not represent a contract or obligation of any kind between Caterpillar Financial Aftermarket Solutions Corporation or its affiliates, and the equipment owner. For details on any Cat® Customer Value Agreement (CVA), including a complete description of the terms, conditions, and/or exclusions, contact a participating Cat dealer.

All graphics and lists in this marketing tool are provided solely for general information purposes and are not intended to be a solicitation or an offer to purchase any product or service.

To the extent that the above publication(s), bulletin(s), and/or any designated contract(s) are ambiguous or inconsistent with the CVA contract language, the terms of the CVA contract shall govern.

© 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

