



Cat[®] Hammers

H100-H210

Cat[®] hammers are designed for productive concrete and rock demolition. With improved hydraulics and quick access to maintenance areas, Cat hammers help increase overall productivity and reduce maintenance costs. Cat hammers are a versatile solution for many applications, including road construction, trenching, and demolition.

Not all attachments are available in all regions. Consult your Cat dealer for specific configurations available in your region.

Improved Productivity

- High impact power and fast impact frequency help provide high working efficiency and increased production.
- Achieve higher production and lower fuel consumption due to the major components optimized design.
- Cat hammers are fully tested and validated with matched machines, resulting in better performance and compatibility.

Dependable Reliability

- Power cells are made with high-quality alloy steel and two-stage heat treatment to help increase durability and lower service costs.
- Over 5 million cycles of pit testing and 2000+ hours of field tests with Cat machines help deliver high reliability and durability.
- Improved bolt tightening processes and reinforced connecting hardware help provide stronger, more durable joints.
- The Cat hammer lines kit with independent return oil routing helps prevent contamination of the main hydraulic system.

Easy to Maintain

- The slip-fit and 90-degree rotatable lower bushing allows for easier replacement in the field, helping reduce service time and extend service life.
- Easy and quick access to maintenance areas make hammer maintenance simple.
- The new tie rod nut on H200 and H210 models provides better tightening performance.

Technical Specifications

| Model | Mount | Recommended Carrier Weight | | | | Blows per Minute | | Operating Weight | | Rated Flow | | | | Operating Pressure | | | | Tool Diameter | |
|-------|-------|----------------------------|---------|---------|---------|------------------|------|------------------|--------|------------|-----|---------|-----|--------------------|-------|---------|-------|---------------|-----|
| | | Minimum | | Maximum | | Min. | Max. | Minimum | | Minimum | | Maximum | | Minimum | | Maximum | | mm | in |
| | | ton | lbs | ton | lbs | | | kg | lb | lpm | gpm | lpm | gpm | kPa | psi | kPa | psi | | |
| H100 | Side | 10 | 22,046 | 15 | 33,069 | 350 | 700 | 783 | 1,726 | 80 | 21 | 100 | 26 | 14 700 | 2,132 | 16 600 | 2,408 | 100 | 3.9 |
| H140 | Side | 18 | 39,683 | 26 | 57,320 | 350 | 500 | 1783 | 3,931 | 120 | 32 | 180 | 48 | 15 700 | 2,277 | 17 700 | 2,567 | 140 | 5.5 |
| H155 | Side | 28 | 61,729 | 35 | 77,161 | 300 | 450 | 2499 | 5,509 | 180 | 48 | 240 | 63 | 15 700 | 2,277 | 17 700 | 2,567 | 155 | 6.1 |
| H165 | Side | 30 | 66,138 | 40 | 88,184 | 250 | 380 | 3169 | 6,986 | 200 | 53 | 250 | 66 | 15 700 | 2,277 | 18 600 | 2,698 | 165 | 6.5 |
| H175 | Side | 35 | 77,161 | 40 | 88,184 | 200 | 350 | 3744 | 8,254 | 200 | 53 | 260 | 69 | 15 700 | 2,277 | 18 600 | 2,698 | 175 | 6.9 |
| H185 | Side | 40 | 88,184 | 55 | 121,253 | 200 | 250 | 4656 | 10,264 | 220 | 58 | 270 | 71 | 19 600 | 2,843 | 23 500 | 3,408 | 185 | 7.3 |
| H195 | Side | 45 | 99,207 | 60 | 132,276 | 100 | 200 | 5712 | 12,593 | 260 | 69 | 310 | 82 | 22 600 | 3,278 | 28 400 | 4,119 | 195 | 7.7 |
| H200 | Side | 50 | 110,230 | 60 | 132,276 | 100 | 200 | 6164 | 13,589 | 260 | 69 | 330 | 87 | 22 560 | 3,272 | 28 400 | 4,119 | 200 | 8.0 |
| H210 | Side | 55 | 121,253 | 80 | 176,368 | 120 | 160 | 6917 | 15,249 | 330 | 87 | 375 | 99 | 25 600 | 3,713 | 28 500 | 4,133 | 210 | 8.3 |

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com.

© 2022 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

GEHQ2320-02 (09-2022)
Replaces GEHQ2320-01
(China)

