



Cat[®] AP655

Asphalt Paver

The Cat[®] AP655 asphalt paver is a rubber track paver that delivers a high-return on investment. This high-production paver offers a fast-heating screed system, durable components, and easy to use technology, while consuming less fuel. A variety of screed choices provide versatility and high-quality results on interstates, highways, airports, and parking lots.

High Return on Investment

- Exclusive 70 kW integrated generator delivers fast, reliable screed heating and is designed for long life by the same team that developed the D7E electric drive dozer
- Fast heating screed leads to more daily production, heating time in as little as 15 minutes
- Mobil-trac[™] undercarriage design delivers excellent traction, good flotation, and fast travel that helps lead to increased production
- Exclusive air flow design improves operating conditions for the crew and keeps components cooler for lasting durability

Technology That Works For You

- Pavement Start Assistant saves set-up profiles for repeatable use on future job sites including: tow-point height, screed heat temperature, paving speed, paving width, paving depth, crown, extender slope and height, screed assist, and screed locking features
- A hopper level sensor (option) with temperature indication keeps the operator informed of material height and delivery temperatures, indicators are located in each tractor display
- Exclusive screed heating system monitors elements for failure conditions, eliminates unnecessary replacement
- Cat[®] Grade Control option is integrated into the tractor and screed displays for optimized operator efficiency
- Thermal mapping (option) utilizes an infra-red camera mounted on a fixed-position mast that captures the entire width of the asphalt surface behind the screed. An LCD display mounted near the screed console provides real-time visibility to the surface being paved

High Quality Results, Higher Earnings

- Versatile screed designs deliver excellent ride, density, and mat texture while providing superior adjustment; available with front-mount extenders, rear-mount extenders, or tamper-bar systems
- Tow-point utilizes exclusive linkage design for optimal screed flotation
- Exclusive 2-speed proportional control on the screed extenders
- Cat Grade Control is a factory-integrated guidance system that helps remove irregularities from the surface and control mat thickness for increased production, lower operating costs, and higher profitability

Low Owning and Operating Costs

- Exclusive Eco-mode and Automatic Engine Speed Control, reduce fuel consumption and lower sound levels for better comfort and communication
- 4-pump feeder system is designed for high production in Eco-mode, leads to lower fuel consumption
- Million cycle switches provide reliability
- Conveyor bed plates and chain guards designed to minimize labor requirements and provide lower cost replacement
- Heating elements slide-out for easy replacement
- Machined screed frames simplify screed plate replacement
- Enhanced hopper flashing with increased memory and temperature resiliency offers better performance during truck exchanges



Cat® AP655 Asphalt Paver

More Comfort

- Ventilation system draws fumes from the auger chamber and redirects them away from the operator for a more comfortable working environment
- Dual operating station provide back-up capability and complete control from either side of the machine, each station can swing-out beyond the frame for good all-around visibility
- Heated seat option, pneumatic suspension, multiple adjustments, and tilting consoles provide day-long comfort
- Eco-mode provides low sound levels that supports clear communication with the crew
- High visibility 76 mm (3") seat belt helps with crew safety compliance
- USB port simplifies software updates
- Cup holders offer convenience

Easy Viewing Displays, Simple Operation

- Touch-screen displays with adjustable brightness control enable operators to fine-tune performance in various lighting conditions
- Touch-screen access simplifies activation of the generator and auxiliary power, while also providing easy adjustments to screed plate heating temperatures, tamper and vibratory speeds, Cat Grade Control (option), and stored operator preferences
- Operating displays can be tailored to specific language requirements with multiple options available

Cat Electronics

- Cat Electronic Control Modules (ECM) and ET compatibility simplifies diagnostics and trouble-shooting procedures

Product Link™ Elite

- Make timely, fact-based decisions to maximize efficiency, improve productivity, and lower owning and operating costs
- Easily track location, machine hours, fuel usage, and idle time
- Diagnostic codes are made available through online web applications

Service and Repair Kits

- Paver and screed service and repair kits include the parts necessary to complete specific repairs
- Cat genuine parts are manufactured to precise specifications and designed for optimal performance and maximum uptime
- Repair kits are identified by a single part number to make ordering easy
- Select kits are available to be packaged as a kit by the dealer for over-the-counter purchases or through the dealer service shop

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional
OPERATING ENVIRONMENT		
Air-ride seat		✓
Canopy – hard top		✓
Deceleration pedal		✓
Dual operating stations	✓	
Friction steering		✓
Heated seats		✓
Side shields		✓
Steering guide	✓	
Tow-point indicator		✓
Umbrella – tractor/screed		✓
Ventilation system	✓	
Visor – LCD screen		✓
Windshield – requires hard top canopy		✓
TECHNOLOGY		
Cat Grade Control		✓
Hopper level and material temperature indication		✓
Pave Start Assistant		✓
Product Link™ Elite 631 (satellite)		✓
Product Link Elite 641 (cellular)	✓	
Thermal Mapping		✓
POWERTRAIN		
Automatic engine speed control	✓	
Ballast – front weights		✓
Cat C4.4 – four-cylinder	✓	
Cooling fan – variable speed	✓	
Eco-mode	✓	
Hydraulic oil – extended life	✓	
Mobil-trac™ belt – smooth belt		✓
Mobil-trac belt – tread bar belt		✓
ELECTRICAL SYSTEM		
1000 CCA batteries (2)	✓	
100 amp alternator	✓	
12-volt power receptacle	✓	
24-volt charging system	✓	
Automotive-type fuse system	✓	
Auxiliary power panel – 6.6 kW		✓
Cat Electronic Technician (Cat ET)	✓	
Generator – 70 kW	✓	
Machine security – wire ready	✓	
Remote jump-start receptacle	✓	

	Standard	Optional
MATERIAL DELIVERY		
Auger extensions		✓
Leveling devices		✓
Mainframe extensions – manual		✓
Mainframe extensions – power		✓
Material feed sensors – contact	✓	
Material feed sensors – sonic		✓
Power folding front hopper apron		✓
Push-roller – adjustable	✓	
Truck hitch		✓
Wash-down pump and reel		✓
Washdown Tank		✓
Wide-width paving packages		✓
SERVICE AND MAINTENANCE		
Extended-life coolant to -35° C (-37° F)	✓	
Engine coolant heater	✓	
Remote access drains and lubrication points	✓	
Service repair kits		✓
Sampling ports for Scheduled Oil Sampling (S.O.S SM)	✓	
Sight Gauges – engine coolant, hydraulic oil	✓	
Uptime kit		✓
SAFETY		
Alarm – back-up	✓	
Horn – warning (front & rear)	✓	
Lights – working	✓	
Lights – roading		✓
Mirror package	✓	
Vandal covers	✓	
Warning – LED safety beacons		✓

Cat® AP655 Asphalt Paver

Technical Specifications

PowerTrain

Engine model	Cat C4.4	
Rated power @ 2200 rpm	129 kW	173 hp
Global emissions: <i>US EPA Tier 4 Final</i>		
Speed – paving	64 mpm	210 fpm
Speed – travel	14.5 km/hr	9 mph

Machine Weight

Paver only (shipping)	15 292 kg	33,730 lb
w/SE47 FM screed (operating)	18 397 kg	40,560 lb
w/SE50 V screed (operating)	18 868 kg	41,597 lb
w/SE60 FM screed (operating)	19 119 kg	42,150 lb
w/SE60 V screed (operating)	19 001 kg	41,890 lb

Operating Weights are approximate and include coolant, lubricants, full fuel tank, and 75 kg (165 lb) operator.

Service Refill Capacities

Maximum throughput capacity	1300 Tonnes	1433 Tons
Cooling system	31 L	8 gal
Diesel exhaust fluid (DEF)	19.1 L	5 gal
Engine oil	13.5 L	3.6 gal
Fuel tank	278 L	73 gal
Hydraulic tank	219 L	58 gal
Washdown spray tank	30 L	7.9 gal


Paving Range With Extensions

SE47 FM screed	2.44 m - 6.25 m	8' - 20' 6"
SE50 V screed	2.55 m - 6.5 m	8' 4" - 21' 4"
SE60 FM screed	3.0 m - 7.8 m	10' - 25' 6"
SE60 V screed*	3.0 m - 7.65 m	9' 10" - 25'
Paving depth	305 mm	12"

** Paving range includes wide width endgate shoe*

Dimensions

1	Operating length w/SE47 FM	6608 mm	21' 9"
	Shipping length w/SE47 FM	6375 mm	20' 11"
	Shipping width w/SE47 FM	2982 mm	9' 10"
	Operating length w/SE50 V	6800 mm	22' 4"
	Shipping length w/SE50 V	6635 mm	21' 9"
	Shipping width w/end gates - SE50 V	2762 mm	9' 1"
	Shipping width w/folded end gates - SE50 V	2550 mm	8' 4"
	Operating length w/SE60 FM	6608 mm	21' 9"
	Shipping length w/SE60 FM	6635 mm	21' 9"
	Shipping width w/SE60 FM	3592 mm	11' 10"
	Operating length w/SE60 V	6800 mm	22' 4"
	Shipping length w/SE60 V	6635 mm	21' 9"
	Shipping width w/end gates - SE60 V	3211 mm	10' 6"
	Shipping width w/end gates folded - SE60 V	3000 mm	9' 10"
2	Operating width	3306 mm	10' 10"
3	Operating height	3777 mm	12' 4"
4	Shipping height	2930 mm	9' 7"
5	Operating platform height	1792 mm	5' 10"
6	Truck entry height	529 mm	21"
7	Truck entry width	3194 mm	10' 6"
8	Hopper length with push roller extended	2414 mm	7' 11"
	Auger diameter	406 mm	16"



For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2022 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

QEHO2943-01 (3-2022)
Build Number:07A
(North America)

