CAT® PRODUCT LINK™ NAMING CONVENTION
MAKING SENSE OF THE NUMBERS

CAT®

KIT EXAMPLE: PLE702 + PL083 = **PLE783**

PLATFORM	NETWORK MANAGER	CAPABILITY	PRIMARY COMMUNICATION	GENERATION	SUFFIX (OPTIONAL)
PL		**7**	**8**	**3**	
▶ **Indicates a Product Link Component**	Blank = Radio Only ▶ **E = Elite** G = Generation R = Router	0 = Bridge 1 = Locator 2 = Basic 3 = Legacy 4 = Legacy (E&T Pro) 5 = Legacy (Aftermarket Pro) 6 = Pro, Elite ▶ **7 = High End Elite**	0 = Wired 3 = Satellite 4 = Cellular 5 = Wifi 6 = Bluetooth 7 = V2X ▶ **8 = Cell & Sat**	0 = 1st Generation/ Off the shelf 1 = 2nd Generation 2 = 3rd Generation ▶ **3 = 4th Generation**	B = Battery P = Panel Mount i = Internal Antenna e = External Antenna

LOCATOR SERIES
- Location only
- Low cost for unpowered assets
- Battery powered, no external power needed
- No wiring required

BASIC SERIES
- Low cost solution for equipment with no data link
- Basic asset data (hours, location)
- Pigtail connection
- Remote disable
- Basic configurability
- Internal battery, limited message, location change

PRO SERIES
- Expanded coverage / roaming (4G/3G/2G)
- Cat Data Link / J1939
- High Band Width (Cell)
- Low Latency
- Full suite of health data
- Enhanced asset data
- Remote derate/disable

ELITE SERIES
- Cat Data Link / J1939
- 2 Way communication
- Multi-mode communication
- Remote Services
- Large analytics file transfer
- Industrial Protocols: RS485
- Remote disable/derate