



# CAT® 777 (05) WATER TRUCK

## THE CHALLENGE: DUST. THE ANSWER: CAT® WATER SOLUTIONS.

Cat® Water Solutions helps you efficiently reduce haul road dust to enhance safety and increase productivity at your job site, quarry, or mine site. An integrated truck, tank, and water delivery system – paired with scalable levels of connectivity – helps you solve overwatering and underwatering issues with a focus on sustainable operations.

The exclusive Auto Mode feature enables operators to deliver a more efficient watering technique with enhanced precision and control – helping solve watering issues common with traditional manual watering operation.

**This solution is sold and supported by the local Cat dealer you know and trust.**

### INTEGRATED DESIGN – DELIVERING PROVEN PERFORMANCE

- + Built on a proven Cat 777 truck platform.
- + Integrated design: truck, tank, and Cat Water Delivery System (WDS) connected with Cat MineStar™ technology.
- + Ergonomically designed in-cab controls for ease of use.

### GAIN EFFICIENCY WITH THE CAT WATER DELIVERY SYSTEM (WDS)

- + Auto Mode provides variable water flow based on truck speed and determines appropriate flow to conserve water.
- + Automatic start and stop helps eliminate overwatering at road intersections.
- + Maintenance-free and self-cleaning water spray heads reduce truck downtime.

### SCALABLE CONNECTIVITY WITH CAT MINESTAR™

- + Take control with near-real-time information hosted in the cloud.
- + Monitor water source and distribution, report status to remote management.
- + Service-based offering with scalable levels of connectivity to fit your needs: select between Basic or upgrade to Premium for a higher level of data-driven insights.

### REDUCE COSTS, SUSTAINABLY

- + Gain more control of your operations using less water.
- + Auto Mode can help conserve water and reduce fuel costs.
- + Advanced technology connected to our water delivery system increases efficiency to help optimize your water truck fleet size.

### ENHANCE SAFETY & PRODUCTIVITY AT YOUR QUARRY, MINE, OR JOB SITE

- + Lower dust levels, increase visibility, maintain haul road safety.
- + Know where and when to water using advanced technology.
- + With automated water delivery, the operator can remain focused on traffic and driving.

### CUSTOMIZATION WITH OPTIONS TO FIT YOUR OPERATIONS

- + We can help you choose a cannon nozzle, water tank, and spray head configuration based on your region and specific watering requirements.
  - » Choose number of spray heads mounted on rear spray bar, add optional side spray heads on the water tank for additional coverage, select cannon nozzle size, and more.
  - » Hoist cylinder mounting enhances serviceability by raising the water tank for easier maintenance.
- + Optional WDS Camera System: includes a camera to view spray bar on back of water tank and two cameras on top of tank for water fill positioning.

### SUPPORTED & BACKED BY THE ONE YOU TRUST

- + Full support of Cat dealer and parts network.
- + Cat dealer installation and retrofit kits available.
- + Eligible for Equipment Protection Plans (EPP) and Customer Value Agreements (CVAs).



# 777 (05) Water Solutions Truck Specifications

Configurations and features may vary by region. Please consult your Cat® dealer for availability in your area.

Specifications shown include the bare chassis and Cat Water Delivery System. Water tank specifications not included.

## Engine

Engine Model	Cat® C32B	
Rated Engine Speed	1,800 rpm	
Gross Power – SAE J1995	765 kW	1,026 hp
Net Power – SAE J1349/ISO 9249	711 kW	953 hp
Cylinders	12	
Bore	145 mm	5.7 in
Stroke	162 mm	6.4 in
Displacement	32.1 L	1,959 in <sup>3</sup>

- Net Power advertised is the power available at the flywheel when the engine is equipped with air intake system, exhaust system, and alternator.
- Power rating applies at 1,800 rpm when tested under the specified condition for the specified standard in effect at the time of manufacture.
- Ratings based on SAE J1349:2011 standard air conditions of 25°C (77°F) and 100 kPa (29.61 Hg) barometer. Power based on fuel having API gravity of 35 at 16°C (60°F) and an LHV of 42 780 kJ/kg (18,390 BTU/lb) when engine used at 30°C (86°F).
- No engine derating required up to 3048 m (10,000 ft) altitude.
- Meets China Nonroad Stage III emission standards, equivalent to U.S. EPA Tier 2..

## Weights – Approximate

Bare Chassis Weight	48 133 kg	106,115 lbs
Target Gross Machine Weight (GMW)	163 360 kg	360,147 lbs
• Machine weights vary based on configuration.		
• Target GMW not to exceed weight after water tank and attachments are installed.		
• For truck rimpull and retarding curves, please reference the 777 (05) Off-Highway technical specifications document.		

## Transmission

Forward 1	10.9 km/h	6.8 mph
Forward 2	14.8 km/h	9.2 mph
Forward 3	20.1 km/h	12.6 mph
Forward 4	27.1 km/h	16.9 mph
Forward 5	36.8 km/h	22.9 mph
Forward 6	49.4 km/h	30.7 mph
Forward 7	67.1 km/h	41.7 mph
Reverse	12.1 km/h	7.5 mph

- Maximum travel speeds with standard 27.00R49 (E4) tires.

## Final Drives

Differential Ratio	2.74:1
Planetary Ratio	7.0:1
Total Reduction Ratio	19.16:1

## Braking System

Brake Surface – Front Dry	2787 cm <sup>2</sup>	432 in <sup>2</sup>
Brake Surface – Rear	102 116 cm <sup>2</sup>	15,828 in <sup>2</sup>
Brake Surface – Front Wet (optional)	40 225 cm <sup>2</sup>	6,235 in <sup>2</sup>
Brake Standard		ISO 3450:2011

## Body Hoists

Body Raise Time – High Idle	15.0 seconds
Body Lower Time – Float	13.0 seconds
Body Power Down – High Idle	13.0 seconds

## Weight Distributions – Approximate

Front Axle – Empty	46 %
Front Axle – Loaded	30 %
Rear Axle – Empty	54 %
Rear Axle – Loaded	70 %

## Suspension

Effective Cylinder Stroke – Front	318 mm	12.5 in
Effective Cylinder Stroke – Rear	165 mm	6.5 in
Rear Axle Oscillation		±5.4°

## Steering

Steer Angle	30.5°
Turning Diameter – Front	25.3 m
Turning Circle Clearance Diameter	28.4 m
Steering Standards	ISO 5010:2019

# 777 (05) Water Solutions Truck Specifications

## Tires

Standard Tire 27.00R49 (E4)

- Productive capabilities of the 777 truck are such that, under certain job conditions, TKPH (T MPH) capabilities of standard or optional tires could be exceeded and, therefore, limit production.
- Caterpillar recommends the customer evaluate all job conditions and consult the tire manufacturer for proper tire selection.

## Service Refill Capacities

Fuel Tank	1140 L	300 gal
Cooling System	212 L	56 gal
Crankcase	115 L	30 gal
Differentials	222 L	59 gal
Final Drives (each)	42 L	11 gal
Steering System (includes tank)	60 L	16 gal
Brake/Hoist System	420 L	110 gal
Torque Converter/ Transmission System	125 L	33 gal
Front wheel (each)	7.5 L	2 gal

## Cab

Sound Standards	ISO 6396:2008	
ROPS Certification Rating	Tractor ROPS Rating	
777 WTR (Tractor)	55 000 kg	121,254 lb

- The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 2.0 kg (4.4 lbs) of refrigerant, which has a CO<sub>2</sub> equivalent of 2.86 metric tonnes (3.152 tons).
- The dynamic operator sound pressure level is 80 dB(A) as per ISO 6396:2008 for cab offered by Caterpillar. The cab was properly installed and maintained. The test was conducted with the cab doors and the cab windows closed.
- Rollover protective structure (ROPS) cab offered by Caterpillar meets ISO 3471:2008 for operator and ISO 13459:2012 for trainer.
- Falling objects protective structure (FOPS) meets ISO 3449:2005 Level II for operator and ISO 13459:2012 Level II FOPS for trainer.

## Cat® Water Delivery System (WDS)

Operator selectable coverage	0.2-0.8 L/m <sup>2</sup> (4 kph - 40 kph)	0.05-0.2 gal/ft <sup>2</sup> (3 mph - 25 mph)
Maximum water flow	6814 L/min	1,800 gal/min
Water per spray head (minimum)	132.5 L/min	35 gal/min
Water per spray head (maximum)	2271 L/min	600 gal/min
Spray head opening range (minimum)	1 mm	0.04 in
Spray head opening range (maximum)	19 mm	0.75 in
Maximum size debris flushed through spray head	19 mm	0.75 in
Spray width per head (dependent on flow)	4.5-9.1 m	15-30 ft
Spray system hydraulic tank capacity	27.5 L	7.25 gal
Maximum number of rear spray heads	5	
Minimum number of rear spray heads (3 recommended)	2	
Maximum number of front/side spray heads	2	
Minimum number of front/side spray heads	0	
Maximum water from cannon (idle)*	2271 L/min	600 gal/min
Maximum water from cannon (high idle)*	6246 L/min	1,650 gal/min
Maximum cannon spray distance*	61 m	200 ft
Wet water pump/hydraulic motor coupling		

\*Depends on nozzle orifice and pipe size.

- Coverage rates above 0.6 L/m<sup>2</sup> may not be available at higher speeds depending on head count and configuration.
- The Auto Mode setting controls water coverage and automatically adjusts to the number of spray heads being used — independent of ground speed. This is an exclusive feature designed into the Cat® WDS software to help water more efficiently.
- Alternatively, manual mode allows the operator to set a water flow rate that is constant regardless of ground speed. This mode is not recommended for daily operation and will reduce watering efficiency and may increase fuel usage.
- Spray head opening is automatically controlled by the system to achieve Auto Mode Coverage or manual mode flow rate.
- Spray heads on competitive water distribution systems require tools and maintenance to change flow and spray pattern. Caterpillar is the only company to have variable active spray heads to regulate water spray.
- Water flow is continually adjusted during operation to conserve water and achieve desired coverage and flow rate.
- Water tanks are offered by local 3rd party providers with customization based on water application and regional customer requirements. Please contact your local Cat dealer, regional OEM Solutions Account manager, or email OEM\_Solutions@cat.com for more information on water tank options and attachments.

# 777 (05) Water Solutions Truck Specifications

## In-Cab Water Controls



1

Keypad to select and control the number of spray heads with buttons for intermittent spray, head cleaning, pump on / off, water cannon on / off, tank fill percentage, and adjustments for water flow rate.

2

Joystick for cannon control with adjustable spray selection. Choose a stream or fan spray when watering the pile or mining face. The cannon may also be used for fire mitigation.

3

Integrated touchscreen with user interface for configuring the water delivery system with real-time indicator of water tank level, cannon, and spray head operation. Optional Cat WDS cameras may also be viewed in this screen.

# 777 (05) Water Solutions Truck Specifications

## Cat MineStar Connectivity Packages

MINESTAR CONNECTIVITY FEATURES*	LEVEL 1: BASIC** Equipment Tracking	LEVEL 2: PREMIUM Equipment Tracking + Production Recording
Near-real-time and historical reporting.	●	●
Truck location / utilization data: routes, starts, and stops.	●	●
Fuel and water level.	●	●
Whether or not the truck is spraying water.	●	●
Water Delivery System Utilization. (Auto Mode vs. manual mode)	●	●
Home Page View.	●	●
Home Page View with Cumulative and Hourly graphs.		●
Water Distribution Map.		●
Volume of water put down over time and area covered.		●
Water distribution rate, water delivery system setting by location, truck, and conditions.		●
Activity breakdown including time and distance: watering, not watering, stopped, etc.		●
Water dispensed by time/rate and mode, last 5 water activities, water dispensed by age.		●
View and export at least 8 weeks of historical water activity data.		●
Replay provides the ability to review and replay shifts by selecting a historical date and time. Review water level, pump on/off, heads on/off, cannon on/off, WDS Mode (Manual or Auto Mode), and coverage rates.		●
In-cab reporting to operator on water coverage and need: route, heat map, decay map. <sup>1</sup>		●
Future enhancements and new feature developments.		●

\*Based on equipment connectivity via WiFi or cellular data. \*\*Basic Connectivity Package comes standard on new truck purchase with a 6-month complimentary service-based offering for better data insights.<sup>1</sup> Feature included in future update.

# 777 (05) Water Solutions Truck Specifications

## Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional	
<b>POWERTRAIN</b>			<b>OPERATOR ENVIRONMENT</b>			
Cat C32B Engine	•		Advisor, touchscreen display	•		
Auto electric fuel priming pump	•		Ash tray	•		
Biodiesel compatibility, B40	•		Coat hook	•		
Brake release motor (towing)	•		Combined gear shift/hoist/park brake lever	•		
Braking system: Hydraulically actuated brakes with oil cooled multiple disc (rear) and caliper disc (front), hydraulically applied and spring released	•		Cup/bottle holder	•		
Cat transmission: 7F/1R speed planetary powershift, ECPC control, APECS software, programmable top gear/speed selection, body upshift inhibitor, directional shift management, neutral start switch, neutral coast inhibitor, reverse shift inhibitor, body-up reverse neutralizer, 2nd gear drive, torque shift management, and part throttle shifting	•		Diagnostic connection port	•		
Economy mode/adaptive economy mode	•		Horn electric	•		
Emergency/parking brake, spring applied and hydraulically released	•		HVAC	•		
Engine overspeed protection	•		Liquid crystal display (LCD), cluster gauge: brake oil temperature, transmission oil temperature, engine coolant temperature, hour meter, tachometer, fuel level gauge, speedometer	•		
Retarder control – manual	•		Left side power window	•		
Water/fuel separator	•		Mirrors, left and right	•		
Front oil cooled disc brake	•		Radio ready	•		
Traction control system	•		Right side access door	•		
Retarder control – automatic	•		ROPS/FOPS cabin	•		
<b>ELECTRICAL</b>			Seat, trainer with lap belt	•		
Alternator, 150 amp	•		Seat: operator – fully adjustable, air suspension, 4-point seat belt with reminder	•		
Auxiliary jump start receptacle	•		Storage compartment	•		
Backup alarm	•		Sun visor	•		
Backup light, LED	•		Switches: throttle lock, wipers/washers, hazard lights, headlights, secondary steering, back light adjust, AC on/off, spare, economy mode, egress lamp, Product Link™ disconnect	•		
Directional signal/hazard warning, LED lights	•		Tilt and telescopic steering wheel	•		
Electrical system, 10 amp, 24V to 12V converter	•		Blind spot mirror	•		
Four batteries, 12V, 190 amp-hour	•		Heated mirror	•		
Ground-level battery disconnect switch	•		<b>CAT TECHNOLOGY PRODUCTS</b>			
Ground-level engine shutdown switch	•		Cat Water Delivery System software	•		
Headlights with dimmer, LED	•		Cat Product Link™	•		
Operator courtesy lights, LED	•		Cat Detect system	•		
Stop/tailights, LED	•		Truck Vision Camera system	•		
Switch, engine lockout	•		Truck production management system (TPMS)	•		
Switch, machine lockout	•		Vital Information Management System (VIMS™)	•		
Two starter motors	•		<b>Cat MineStar™ hardware and connectivity packages:</b>			
Working lights, LED	•		<ul style="list-style-type: none"> <li>• Level 1 – Basic (Equipment Tracking)*</li> <li>• Level 2 – Premium (Equipment Tracking + Production Recording)</li> </ul>	•		
Audio visual backup alarm	•		*Basic connectivity package comes standard on all Cat Water Trucks with a 6-month complimentary service-based offering.			
Fog lamp	•					

# 777 (05) Water Solutions Truck Specifications

## Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional	Standard	Optional
<b>CAT WATER DELIVERY SYSTEM (WDS)</b>			<b>OTHER EQUIPMENT</b>	
<b>Controls:</b>			Body down indicator	•
• Factory installed	•		Body mounting group	•
• Integrated into cab	•		Body safety pin	•
<b>Water System Monitor:</b>			Driveline guard	•
• Integrated into cab	•		Engine crankcase guard	•
• Programmable spray configurations	•		Exhaust body heat system	•
• Automatic diagnostic messages	•		Extended life coolant to -35°C (-30°F)	•
<b>Variable Hydraulic Pump Drive:</b>			Ground-level grease fittings	•
• 1,800 gpm at speeds of 4 - 40 kph (3 - 25 mph)	•		Hydropneumatic suspension	•
• Auto shut-off	•		Load counter	•
• Soft startup	•		Rock ejectors	•
<b>Stainless Steel Spray Heads:</b>			Tie down eyes/tow down hooks	•
• Resists corrosion	•		Vandalism protection lock	•
• Maintenance free	•		Automatic lubrication system (27 kg/40 kg)	•
• Patented design	•		Cluster/grouped lubrication system	•
<b>Independent Hydraulic Cooling System:</b>			Cold weather package	•
• Minimizes overheating	•		Exhaust muffler	•
<b>Water Cannon:</b>			Fast fluid fill system	•
• Hydraulically controlled	•		Fast fuel fill system	•
• Optional nozzles		•	Fire extinguisher	•
• Integrated joystick with cab controls	•		Fuel tank 1325 L	•
<b>WDS Camera System:</b> includes three cameras, three camera washers and cable assemblies		•	Hoist quick disconnect	•
Parts and service available through global Cat dealer network			Oil change system – high speed	•
<b>WATER TANKS</b>			Spare rim	•
Water tanks are offered by local 3rd party providers with customization based on water application and regional customer requirements.		•	Wheel chocks	•
Options include: tie offs, ladders, splash guards, fill chute, rock ejectors, hose reels, working lights, and other options based on request.		•		
Spray bar for 3-5 Cat WDS spray heads		•		
Side spray mounting for Cat WDS spray heads		•		

Please contact your local Cat dealer, regional OEM Solutions Account manager, or email [OEM\\_Solutions@cat.com](mailto:OEM_Solutions@cat.com) for more information on water tank options and attachments.

For more information on Cat products, dealer services, and industry solutions, contact your local Cat dealer or Caterpillar OEM Solutions [oem\\_solutions@cat.com](mailto:oem_solutions@cat.com) | [www.cat.com/oemsolutions](http://www.cat.com/oemsolutions).

© 2026 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEXJ0143-03 (01-2026)  
(Build Number: 05)  
(South America, Africa, Middle  
East, Australia, New Zealand)

