

SCREW TO CONNECT QUICK DISCONNECT KITS FOR CAT® NEXT GENERATION MINI EXCAVATORS

Do you want to enhance your Cat® next generation mini excavator with improved comfort, safety or productivity features? Caterpillar offers a wide variety of field-installed aftermarket kits specially developed for Cat mini excavators.

For applications that require heavy-duty work tools, especially those that have high-pressure impulses like hammers and vibratory compactors, a Screw to Connect Quick Disconnect (QD) Kit eliminates the brinelling effect seen with standard ISO 160828 quick disconnects. They screw to connect and disconnect under pressure and have a locking sleeve which ensures the quick disconnects are fully connected preventing inadvertent disconnection — making job sites safer.

Available as field-installed kits for Cat 1.5-10 ton Mini Excavators, Screw to Connect QD Kits include:

- Male and female screw to connect set with protective caps (replaces the standard quick disconnects)
- · Screw to connect disconnects are the locking style that prevents the screw from backing off
- Two sets are required for machine and attachment connections or one set for the machine side only
- Adapters may be required to complete installation



SCREW TO CONNECT QUICK DISCONNECT KITS

Model	Serial Number Prefix	Kit Part Number
301.5	MNH	611-6995 ½" Locking Screw to Connect
301.6	MY6	
301.7 CR	JH7	
301.8	H8X	
302 CR	RHM	
302.7 CR	CZ6*, 3C3*	611-6997 34" Locking Screw to Connect
303 CR	NXY*, MY3*	
303.5 CR	RE9*, CE9*, R2E*	
304	AN4	
305 CR	5G5, 5X5	
306 CR	GW5, 6G6, 6W6	
307.5	GW7	
308 CR	GZ8, GW8, GG8	
309 CR	GW9, GG9	
310	GWT	

^{*}Some attachments may require both kit part numbers.

Please contact your Cat dealer for details for ordering and installation of Screw to Connect Disconnect Kits for 1.5-10 ton mini excavators.

Screw to Connect Quick Disconnect Kits





