



# Cat<sup>®</sup> Hammers

## H110 GC, H120 GC

***Cat<sup>®</sup> H110 GC and H120 GC Hammers are designed for durability in rock breaking and concrete demolition. With powerful hydraulics and quick access to maintenance areas, Cat H110 GC and H120 GC Hammers help increase overall productivity and reduce maintenance costs. Cat H110 GC and H120 GC Hammers are a versatile solution for many applications, including road construction, trenching, and demolition.***

***Not all attachments are available in all regions. Consult your Cat dealer for specific attachments available in your region.***

### High Performance

- The large hammer tool diameter has high impact power to help break tough rock and concrete applications on the job site.
- Cat H110 GC and H120 GC Hammers are designed with high impact power and fast impact frequency to help break through material quickly to increase efficiency and production.
- Cat H110 GC and H120 GC Hammers are fully tested and validated with matched machines, resulting in better performance and compatibility.

### Reliability and Durability

- Cat H120 GC Hammers can sustain high vibrations with the help of a standard high-vibration adaptor.
- Power cells are made with high-quality alloy steel and two-stage heat treatment to help increase durability and lower service costs.
- Hydraulic components are shielded from damage inside the housing, helping decrease downtime on the job site.
- The Cat hammer lines kit with independent return oil routing helps prevent contamination of the main hydraulic system.

### Easy to Maintain

- The slip-fit and 90-degree rotatable lower bushing allows for easy replacement in the field, helping reduce service time and extend service life.
- Quick and easy access to maintenance areas helps make hammer maintenance simple.
- Daily tool inspection and grease points are accessible from the ground with the hammer still mounted on the machine.
- Reinforced connecting hardware and easy bolt tightening processes help provide strong, durable joints and extend hammer life.



# Cat® Hammers

## Technical Specifications

			Recommended Carrier Weight				Blows per Minute		Operating Weight		Rated Flow				Operating Pressure				Tool Diameter	
			Minimum		Maximum		Min.	Max.	Minimum		Minimum		Maximum		Minimum		Maximum			
Model	Build	Mount	ton	lbs	ton	lbs			kg	lb	lpm	gpm	lpm	gpm	kPa	psi	kPa	psi	mm	in
H110 GC	-04	Side	10	22,046	18	39,680	350	700	801	1,766	80	21	100	26	14 700	2,132	16 600	2,408	100	3.9
H110 GC	-04	Top	10	22,046	18	39,680	350	700	917	2,022	80	21	100	26	14 700	2,132	16 600	2,408	100	3.9
H120 GC	-04	Side	18	39,683	30	66,140	350	550	1827	4,028	120	32	180	48	15 700	2,277	17 700	2,567	140	5.5
H120 GC	-04	Top	18	39,683	30	66,140	350	550	2004	4,418	120	32	180	48	15 700	2,277	17 700	2,567	140	5.5

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com).

© 2024 Caterpillar  
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

GEHQ9333-00 (02-2024)  
(Afr-ME, Eurasia, Japan,  
S Am, SE Asia)

