



953

Track Loader

Save money and transport time with one rugged machine that does it all – land clearing, digging, grading, truck loading, slope work and more. Crawler loaders give you lower ground pressure and better traction so you can start the job sooner, and work longer, in all kinds of underfoot conditions. Cat® Track Loaders give you all this, plus outstanding performance and fuel efficiency.

One Machine, Many Jobs

- Track loader power, traction and agility mean you can use one machine and one operator to do everything from clearing the site to installing utilities and finishing around buildings.
- 953 is sized for tight spaces and easy transport.
- Fusion™ Quick Coupler option lets you make fast attachment changes with a wide range of tools like forks, buckets, etc. from wheel loaders and other Fusion compatible machines.
- Bucket/tooth, undercarriage, track shoe and attachment choices help you equip your machine for optimal performance in your applications.
- Purpose-built Waste Handler, Low Ground Pressure (LGP), Ship Hold and Steel Mill configurations stand up to the toughest tasks.

Top Performer

- 953 uses up to 10% less fuel per hour than the previous model.
- Performance Series bucket option boosts productivity up to 20% compared to General Purpose bucket.
- Cat Payload* technology delivers precise bucket load information with on-the-go weighing. More accurate loading reduces cycle times to help save time, labor and fuel costs.
- Advansys™ bucket tips are built to give you maximum productivity and the lowest bucket lifecycle cost for your toughest applications.
- Smoother implement and steering response, and improved steering performance provide more controllability.
- Load sensing hydraulics and position sensing cylinders offer precise, responsive performance.

All comparisons to 953K track loader.

**Not legal for trade.*

Easy to Operate

- Comfortable cab and an intuitive 254 mm (10-inch) touchscreen dash display.
- Standard High Definition rearview camera shows prominently in the main display.
- Slope Indicate helps make operation easier by showing machine mainfall and cross slope right on the display.
- Enjoy operator comforts like suspension seat and adjustable armrests and controls.
- Choose either joystick or two-lever implement controls to match operator preference or application.
- Speed/steering control choices include either a joystick or a v-lever and foot pedals.
- Set implement response – fine, normal, coarse – to match operator preference or application.
- Emissions reduction technology (when equipped) is designed to work in the background, with no action required from the operator.

Focus on Safety

- Excellent visibility to the bucket and all around the machine enhances safety and helps operators work more confidently.
- Handles and steps help operators climb on and off the machine more easily, from the front or the back of the tracks.
- Standard rear vision camera enhances visibility behind the machine.
- Seat belt indicator gives an alarm and registers fault code through Product Link™ if the operator fails to buckle up, enhancing job site safety.
- Ergonomics, a quiet engine and low-effort controls help lessen fatigue, so operators are better able to remain fresh and focused.



953 Track Loader

Equipped for the Job

- Equip your loader from the factory to take on extra-challenging tasks like soft footing, waste handling, ship hold and steel mill work.
- For added flotation and traction, or work in more sensitive ground conditions, choose a Low Ground Pressure (LGP) loader with wider tracks.
- Waste Handler configuration is a versatile machine for loading, sorting, excavation and spreading cover, and well suited to the landfill or transfer station. Specialized guarding, striker bars and seals help protect the machine and components from impact and airborne debris. Enhanced Cleaning Package reduces cleaning time, adds machine protection and increases compaction.
- Traction, high reach and machine balance make track loaders ideal for working in ship holds and port handling duties. Specialized guarding and seals help protect the machine, while attachments like coal buckets and trim blades help you get the job done.
- Your track loader can be factory equipped with a heat-resistant cab, high-temperature guarding and other features to help protect the machine and operator in high-temperature steel mill work.

Save on Maintenance

- Designed to help you take care of routine maintenance and get back to work.
- Grouped service points located behind large access doors.
- Daily grease points in easy reach at ground level.
- Service mode in the operator display shows hydrostatic and implement pressure for easier troubleshooting and servicing.
- Demand fan provides efficient cooling plus easy fold-down service access.
- Handy bracket holds a shovel for quick undercarriage clean-out.
- Tilt cab and convenient service access points for easier maintenance and repair.
- Diesel Particulate Filter in the Clean Emissions Module (when equipped) designed to work for the life of the engine without needing to clean or replace the filter.

Connect to Greater Efficiency

- Product Link collects machine data that can be viewed online through web and mobile applications.
- Access information anytime, anywhere with VisionLink™ – and use it to make informed decisions that boost productivity, lower costs, simplify maintenance, and improve safety and security on your jobsite.
- Remote Troubleshoot saves time and money by allowing your Cat dealer to perform diagnostic testing remotely.
- Remote Flash updates on-board software without a technician being present, at a time that is convenient for you, potentially reducing update time by as much as 50%.

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional
POWER TRAIN		
Cat C7.1 Diesel Engine	✓	
Hydraulic demand fan	✓	
Hydrostatic transmission	✓	
Load sensing implement pump	✓	
Modular cooling system	✓	
Cat C7.1 diesel engine with engine-mounted aftertreatment to meet U.S. EPA Tier 4 Final, EU Stage V, Korea Stage V, China Nonroad Stage IV, Japan 2014 emission standards		✓
Cat C7.1 diesel engine to meet India Bharat Stage III, Eurasian Economic Union Stage IIIA, UN ECE R96 Stage IIIA emission standards, equivalent to Tier 3/Stage IIIA		✓
CAB		
12V power outlet and 5V USB port	✓	
Adjustable armrests	✓	
Full-color 254 mm (10 in) liquid crystal touchscreen display	✓	
Grab handle on dash	✓	
Heat/Air conditioning	✓	
Integrated rearview High Definition (HD) camera	✓	
Lights – 4 halogen	✓	
Pressurized, sound suppressed, Rollover Protective Structure (ROPS)/Falling Object Protective Structure (FOPS) Cab with tinted glass and sliding window	✓	
Radio ready	✓	
Storage areas throughout cab	✓	
Special application cab with dual pane/polycarbonate window		✓
Deluxe seat		✓
Premium seat		✓
Joystick or two-lever implement controls		✓
Joystick or V-lever-and-pedal steering controls		✓
Radio AM/FM Bluetooth®		✓
Radio AM/FM/DAB+ Bluetooth		✓
Radio AM/FM/Sirius XM Bluetooth		✓
Communication Radio Ready		✓
Lights – 2 LED front/bottom of cab, access light		✓
Lights – 8 LED		✓
LED flashing beacon		✓

	Standard	Optional
CAT TECHNOLOGY		
Slope Indicate	✓	
Product Link ready	✓	
Remote Flash/Remote Troubleshoot		✓
Product Link, Cellular		✓
Product Link – Dual Cellular/Satellite		✓
Cat Payload		✓
Grade control mast		✓
SERVICE AND MAINTENANCE		
4 x 2 Easy tie-down points on chassis	✓	
Ecology drains	✓	
Ground level service center	✓	
Hinged radiator guard and swing out fan	✓	
Shovel holder	✓	
Fast fuel fill		✓
High Speed oil change		✓
Hydraulic reversing fan		✓
Hydraulic tilt cab		✓
Refueling pump		✓
Underhood work light		✓
UNDERCARRIAGE		
Caterpillar Heavy Duty undercarriage	✓	
Oscillating track roller frames	✓	
Cat Abrasion undercarriage		✓
Waste or Low Ground Pressure (LGP) undercarriage		✓
SPECIAL ARRANGEMENTS		
Low Ground Pressure (LGP) Arrangement		✓
Waste Handler		✓
Ship Hold Arrangement		✓
Steel Mill Arrangement		✓
ATTACHMENTS		
Bumper		✓
Counterweights		✓
Multi-shank ripper		✓
Ripper hitch		✓
Ripper-ready rear hydraulics		✓
Striker bar box		✓
BUCKETS		
Fusion quick coupler		✓
General Purpose bucket		✓
Landfill bucket		✓
Multi-Purpose bucket		✓

953 Track Loader

Technical Specifications

Engine		
Flywheel Power	119 kW	160 hp
Engine Model	Cat C7.1	
Net Power – ISO 9249/SAE J1349	119 kW	160 hp
Net Power – ISO 9249 (DIN)	162 mhp	
Emissions	Meets U.S. EPA Tier 4 Final, EU Stage V, Korea Stage V, China Nonroad Stage IV, Japan 2014 emission standards or India Bharat Stage III, Eurasian Economic Union Stage IIIA, UN ECE R96 Stage IIIA emission standards, equivalent to U.S. EPA Tier 3/EU Stage IIIA.	
<ul style="list-style-type: none">• The Cat C7.1 is available in configurations that meet U.S. EPA Tier 4 Final, EU Stage V, Korea Stage V, China Nonroad Stage IV, Japan 2014 emission standards or Eurasian Economic Union Stage IIIA, UN ECE R96 Stage IIIA emission standards, equivalent to U.S. EPA Tier 3/EU Stage IIIA.• Cat U.S. EPA Tier 4 Final, EU Stage V, Korea Stage V, China Nonroad Stage IV, Japan 2014 engines are required to use ULSD (ultra-low sulfur diesel fuel with 15 ppm of sulfur or less) and are compatible* with ULSD blended with the following lower-carbon intensity fuels** up to:<ul style="list-style-type: none">✓ 20% biodiesel FAME (fatty acid methyl ester)***✓ 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels• Cat engines meeting Eurasian Economic Union Stage IIIA, UN ECE R96 Stage IIIA emission standards, equivalent to U.S. EPA Tier 3/EU Stage IIIA, are compatible with diesel fuel blended with the following lower-carbon intensity fuels up to:<ul style="list-style-type: none">✓ 100% biodiesel FAME (fatty acid methyl ester)****✓ 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels		
Refer to guidelines for successful application. Please consult your Cat dealer or “Caterpillar Machine Fluids Recommendations” (SEBU6250) for details.		
<i>*While Caterpillar engines are compatible with these alternative fuels, some regions may not allow their use.</i>		
<i>**Tailpipe greenhouse gas emissions from lower-carbon intensity fuels are essentially the same as traditional fuels.</i>		
<i>***Engines with no aftertreatment devices are compatible with higher blends, up to 100% biodiesel (for use of blends higher than 20% biodiesel, consult your Cat dealer).</i>		
<i>****For use of blends higher than 20% biodiesel, consult your Cat dealer.</i>		
<ul style="list-style-type: none">• Net power advertised is the power available at the engine flywheel when the engine is equipped with a fan, air cleaner, clean emissions Module (when equipped) and alternator. Advertised power is tested per the specified standard in effect at the time of manufacture.		
Weights		
Operating Weight	15 692 kg	34,594 lb
Service Refill Capacities		
Fuel Tank	265 L	70 gal
Diesel Exhaust Fluid (DEF) Tank	16 L	4.2 gal

Standard		
Operating Weight	15 958 kg	35,181 lb
Width of Standard Shoe	480 mm	20 in
Ground Contact Area	2.4 m²	3,720 in²
Ground Pressure	66 kPa	10 psi
Low Ground Pressure (LGP)		
Operating Weight	17 261 kg	38,055 lb
Width of Standard Shoe	800 mm	31.5 in
Ground Contact Area	3.9 mm²	6,045 in²
Ground Pressure	43 kPa	6 psi
Waste Handler		
Operating Weight	16 176 kg	35,662 lb
Width of Standard Shoe	480 mm	20 in
Ground Contact Area	2.4 m²	3,720 in²
Ground Pressure	67 kPa	10 psi
Dimensions		
Overall Machine Length*	6378 mm	251.1 in
Overall Machine Width without Bucket: With Standard Tracks – 550 mm (21.6 in) Shoes	2316 mm	91.2 in
Machine Height – Top of Cab	3156 mm	124.2 in
Reach at Full Lift Height and 45° Dump*	1053 mm	41.4 in
Clearance at Full Lift Height and 45° Dump*	2838 mm	111.7 in
Height – Bucket Hinge Pin	3608 mm	142.1 in
Ground Clearance	413 mm	16.3 in
Ramp Angle	29°	
*With General Purpose pin-on bucket		
Undercarriage		
Track Gauge	1836 mm	72.3 in
Track on Ground	2286 mm	90 in
Track Rollers/Shoes – Each Side	6/37	
Buckets		
Capacity – General Purpose	1.8 m³	2.4 yd³
Capacity – Multi-Purpose	1.6 m³	2.1 yd³
Capacity – Performance Series	2.1 m³	2.7 yd³
Width – General Purpose	2485 mm	97.8 in
Width – Multi-Purpose	2471 mm	97.3 in
Width – Performance Series	2536 mm	99.8 in
Air Conditioning System		

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2025 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, VisionLink, their respective logos, “Caterpillar Corporate Yellow,” the “Power Edge” and Cat “Modern Hex” trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEXQ3711-01 (07-2025)
Replaces AEXQ3711-00
Build Number: 12A
(Global excluding Brazil)

