

SAFETY DATA SHEET

1. Identification

Product identifier Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment

Other means of identification

Product code 1002881

Recommended use of the chemical and restrictions on use

Recommended use Antifreeze / Coolant.

Recommended restrictions Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Supplier Arteco Coolants India Pvt Ltd
#304A, Town Square,
Viman Nagar,
Pune – 411 014. Maharashtra
India

e-mail customerservice-india@arteco-coolants.com

Product information +91-(0)20-6728 6000

1.4. Emergency telephone number

Transportation emergency Europe: +44 20 35147487 (24hr) Access code: 335087
India: +001 803 015 203 9774 (24hr)

Health Emergency Europe: +44 20 35147487 (24hr) Access code: 335087
India: +001 803 015 203 9774 (24hr)

2. Hazards identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 5
Reproductive toxicity (the unborn child) Category 1B
Specific target organ toxicity following repeated exposure Category 2 (kidney)

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be harmful if swallowed. May damage the unborn child. May cause damage to organs (kidney) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapours. Wear protective gloves/protective clothing/eye protection/face protection.

Response IF SWALLOWED: Immediately call a POISON CENTRE/doctor. IF exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification None known.

Supplemental information None.

3. Composition/information on ingredients

Mixture

Chemical name	CAS number	%
Ethylene glycol	107-21-1	34 - < 80
Sodium 2-ethylhexanoate	19766-89-3	0.1 - < 3
Methyl-1H-benzotriazole	29385-43-1	0.1 - < 1

Composition comments All concentrations are in percent by weight.
This product contains a bittering agent.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Convulsions. Dizziness. Nausea, vomiting. Abdominal pain. Oedema. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapours. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m ³	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Neoprene, butyl rubber, nitrile or Viton gloves are recommended. Full contact: Use gloves classified protection index 6 with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

Other

Wash hands thoroughly after handling. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Clear liquid.

Colour

Red.

Odour

Mild.

Odour threshold

Not determined.

pH

8.25 - 8.60 (20°C)

Melting point/freezing point

Not determined. / -36 °C (-32.8 °F)

Initial boiling point and boiling range

109 °C (228.2 °F) (Estimated)

Flash point

Does not flash.

Evaporation rate

Not determined.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Not determined.

Explosive limit – upper (%)

Not determined.

Vapour pressure

Not determined.

Vapour density

Not determined.

Relative density

Not determined.

Solubility(ies)

Solubility (water)

Miscible.

Partition coefficient (n-octanol/water)

Not applicable, product is a mixture.

Auto-ignition temperature

398 °C (748.4 °F) (Ethylene glycol)

Decomposition temperature

Not determined.

Viscosity

Not determined.

Other information

Density	1.070 kg/l (20 °C) (Typical)
Kinematic viscosity	Not determined.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidising agents. Nitrates. Peroxides. Chlorates.
Hazardous decomposition products	At elevated temperatures: Ketones. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

Inhalation	In high concentrations, mists/vapours may irritate throat and respiratory system and cause coughing.
Skin contact	Prolonged or repeated contact may dry skin and cause irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May be harmful if swallowed. Ingestion of ethylene glycol may result in nausea, vomiting, abdominal cramps, blindness, liver damage, irritation, reproductive effects, nerve damage, convulsions, oedema of the lung, cardiopulmonary effects (metabolic acidosis), pneumonia and kidney failure which could result in death. The single lethal dose for humans is about 100 ml. Inhalation of high levels of vapour or mists for prolonged periods of time may also result in toxic effects.

Symptoms related to the physical, chemical and toxicological characteristics	Convulsions. Dizziness. Nausea, vomiting. Abdominal pain. Oedema. Prolonged exposure may cause chronic effects.
--	---

Information on toxicological effects

Acute toxicity	May be harmful if swallowed.
----------------	------------------------------

Product	Species	Test Results
Perkins ELC(Extended Life Coolant) Premix 50/50 with Embitterment (CAS -)		
Acute		
Oral		
ATEmix		3178 mg/kg bw
Components		
Ethylene glycol (CAS 107-21-1)		
Acute		
Dermal		
LD50	Mouse	> 3500 mg/kg
Inhalation		
<i>Aerosol</i>		
LC50	Rat	> 2.5 mg/l, 6 Hours
Oral		
LD50	Cat	1600 mg/kg
Methyl-1H-benzotriazole (CAS 29385-43-1)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	720 mg/kg
Sodium 2-ethylhexanoate (CAS 19766-89-3)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours

Components	Species	Test Results
Oral LD50	Rat	2043 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitisation		
Respiratory sensitisation	Not a respiratory sensitiser.	
Skin sensitisation	This product is not expected to cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
ACGIH Carcinogens		
Ethylene glycol (CAS 107-21-1)	A4 Not classifiable as a human carcinogen.	
Reproductive toxicity	May damage the unborn child.	
Reproductivity		
Methyl-1H-benzotriazole (CAS 29385-43-1)	30 mg/kg bw/day OECD 414 Result: LOAEL Species: Rat	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (kidney) through prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.	
Further information	No data available.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Ethylene glycol (CAS 107-21-1)		
Aquatic		
Crustacea	EC50	Daphnia magna > 100 mg/l, 48 Hours
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) 72860 mg/l, 96 hours
Methyl-1H-benzotriazole (CAS 29385-43-1)		
Aquatic		
<i>Acute</i>		
Algae	ECr50	Pseudokirchneriella subcapitata 75 mg/l, 72 hours
Crustacea	EC50	Daphnia galeata 8.58 mg/l, 48 hours
	LC50	Arcartia tonsa 55 mg/l, 48 hours
Fish	LC50	Danio rerio 180 mg/l, 72 hours
<i>Chronic</i>		
Crustacea	EC10	Daphnia galeata 0.4 mg/l, 21 days
Persistence and degradability	Ethylene glycol: >90% / 10 days (OECD 301A) Readily biodegradable.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
Ethylene glycol (CAS 107-21-1)	-1.36	
Mobility in soil	This product is miscible in water and may not disperse in soil.	
Other adverse effects	No data available.	

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

ADR

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

Controlled Narcotic & Psychotropic Precursors List

Not regulated

CWC (Chemical Weapons Convention Act 2000, Schedules 1-3)

Not regulated

Hazardous Chemicals, Schedule 2: Threshold Quantities at an Isolated Storage (Manufacture, Storage and Import of Hazardous Chemical Rules 1989, as amended).

Not regulated

Hazardous Chemicals, Schedule 3: Threshold Quantities in an Industrial Installation (Manufacture, Storage and Import of Hazardous Chemical Rules 1989, as amended).

Not regulated

List of Hazardous Chemicals (Manufacture, Storage and Import of Hazardous Chemical Rules, Schedule I (Part II)).

Ethylene glycol (CAS 107-21-1)

Ozone Depleting Substances (ODS) (Ozone Depleting Substances (Regulation and Control) Rules 2000, Schedule 1).

Not regulated

International regulations

All components comply with the following chemical inventory requirements: AIC (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States), TCSI (Taiwan), NZIoC (New Zealand).
For countries not listed above, further action by the importer is needed.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Montreal Protocol

Not applicable.

Kyoto Protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information, including date of preparation or last revision

Issue date	04-March-2024
Revision date	-
Version No.	01

List of abbreviations

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
EC50: Effective Concentration, 50%.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
LC50: Lethal Concentration, 50%.
LD50: Lethal Dose, 50%.
MARPOL: International Convention for the Prevention of Pollution from Ships.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TWA: Time Weighted Average.

References

ECHA CHEM

Disclaimer

ARTECO NV cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.