

# 313

## HYDRAULIC EXCAVATOR



---

Net Power – ISO 9249  
Operating Weight  
Maximum Digging Depth

70.6 kW (95 hp)  
15 800 kg (34,900 lb)  
5180 mm (17 ft)

**CAT**<sup>®</sup>

# 313

## HYDRAULIC EXCAVATOR

The Cat 313 low ground pressure hydraulic excavator brings premium power, performance, and control to your work. This low ground pressure machine has been designed to work in the most demanding agricultural and forestry applications. Unmatched versatility, excellent ground clearance, easy operation, and a comfortable, redesigned cab help make the 313 a leading performer.



### IMPROVED PERFORMANCE

Designed for excellent performance in forestry and agriculture applications. Lower your fuel bill without impacting your productivity.

### UP TO 20% LOWER OPERATING COSTS

Simplify maintenance and reduced maintenance costs up to 20%.

### PROVEN RELIABILITY & DURABILITY

Low ground pressure machine designed for tough forestry and agricultural applications.

# LATEST FEATURES



- Cab Monitor Improvements
  1. Continuously improved user interface allows for intuitive navigation, minimizing performance interruption with the easy-to-use touchscreen menu.
  2. Identify apps quickly with a grid list view, abbreviated app names, and categorized menu options.
  3. A new notification center keeps important information visible to the operator, and displays messages without shrinking the camera view.
  4. Color coded notifications set critical messages apart from the rest.
  5. Use the in-monitor QR code to learn about machine and technology features through a full suite of “how-to” videos.
- Operator Coaching is an in-cab system that recognizes specific opportunities for operators to be more productive and prevent unnecessary machine wear and tear.
- Optional Cat Detect – People Detection helps the operator avoid personnel on the jobsite with visual and auditory alerts.
- Standard integrated vehicle health management system alerts the operator with service guidance and parts needed to enhance uptime.

***Not all features are available in all regions. Please check with your local Cat dealer for specific offering availability in your area. Build Number: 05D.***

# RELIABLE & DURABLE PERFORMANCE



- The 313 low ground pressure machine has been designed for tough forestry and agricultural applications.
- The C3.6 engine and electro-hydraulic system work in sync, allowing you to move large volumes of material without burning too much fuel.
- The new main hydraulic pump is electronically controlled and provides higher fluid for improved control and productivity.
- Digging force has been increased and the swing drive has been redesigned to provide up to 10% more swing torque and smoothness for improved performance.
- A wide and high undercarriage and track provide design a balance of outstanding ground clearance, performance and stability.
- A full length deck bumper and heavy-duty bottom guard offer increased protection.
- Boom, stick and bucket linkages are reinforced for maximum durability.

# LOW OWNING & OPERATING COSTS

- The 313 is designed to simplify maintenance and reduce maintenance costs, which can reduce costs by up to 20%.
- Three working modes are provided, and the power can be selected according to the specific operation: Smart mode, which can automatically adjust the power according to the demand; Eco mode, which can reduce fuel consumption; Power mode, which can achieve the highest productivity.
- Hydraulic and air filter life has been extended, and pilot and case drain filters have been eliminated.
- A new electric priming pump system automatically prefills the fuel system on start-up, simplifying service and reducing the possibility of air cavitation.
- The swing drive is now integrated with the hydraulic system, eliminating the need to check or refill a separate oil system.
- Refill capacities of both hydraulic oil and engine oil have been reduced with no change in performance or service life.
- The Automatic Engine Control (AEC) system lowers engine rpm to idling if there is no operator input for 5 seconds, reducing your fuel costs.
- The Cat Product Link™ system comes standard so you can remotely monitor fuel consumption, machine health, location and hours via VisionLink® if desired.



# EASY TO USE



- The keyless engine push start is easy to operate.
- The all-new electro-hydraulic joysticks require less operator effort and reduce operator fatigue significantly, while at the same time allowing customization of the joystick response and gain settings for maximum controllability.
- Quickly navigate through simplified control menus on a high-resolution 203 mm (8 in) touchscreen monitor.
- Cat continues to improve user interface functionality for operators of all skill levels. The touchscreen monitor is an easy-to-use operating tool that presents the jobsite dashboard with an intuitive format. Productivity applications are displayed in grid-view to read on-the-go, and touchscreen navigation is programmed to make sure job performance continues without any hold ups.

# WORK COMFORTABLY

- The 313 features an adjustable, wider seat and suspension for improved operator comfort.
- Standard automatic temperature control ensures a comfortable temperature throughout the day.
- A large touch screen features simplified menus for adjusting operator preferences.
- Radio comes with Bluetooth® connectivity allowing operator to pair the device, enjoy music of choice and pick up calls handsfree.
- Convenient storage locations throughout the cab offer ample space for personal items.



# LOW EFFORT MAINTENANCE



- The radiator screen is easily removable for easy cleaning and eliminates small, hard-to-remove debris, such as grass clippings, from the radiator.
- The engine compartment is easily accessible from the service platform; the oil cap and level gauge are easily accessible, and an automatic tensioner ensures you never have to adjust the conveyor belt.
- Cat technology helps you monitor your machine, while the Caterpillar service network helps maximize uptime.



# SAFETY FEATURES

- The 313 features emergency engine and electrical cut-off devices.
- Emergency engine and electrical cut-off devices are accessible at ground level.
- Extra handrails aid in easy servicing; steps and platforms use anti-skid plates with countersunk bolts to prevent slips and trips.
- In an emergency, the operator can climb out of the machine through the rear window or steel sunroof.
- The updated cab is designed with larger windows and smaller cab posts to provide excellent visibility.
- Bright exterior LED lights ensure you're well aware of your surroundings on the jobsite.



# MORE THAN MACHINES

## BUILT AROUND YOUR SUCCESS

When you buy Cat equipment, you get so much more than the machine. You also get the support of a best-in-class dealer network, backed by a range of flexible solutions, technology, tools, and more.



### CUSTOMER VALUE AGREEMENTS

A Customer Value Agreement (CVA) from your Cat dealer helps you do more and worry less. A CVA simplifies machine ownership and maintenance, adds the security of expert dealer support, and gives you the peace of mind from effective equipment health management.

### GENUINE CAT PARTS

Genuine Cat parts deliver the highest level of reliability and productivity. Order direct from your Cat dealer or shop online at [parts.cat.com](http://parts.cat.com).

### REPAIR OPTIONS

A broad range of repair options gives you choices that work with your needs, budget, and timeline. Every repair is performed by expert Cat technicians. You'll receive smart repair advice, a timely, accurate quote, and service that gets your machine back into action quickly.

### FINANCIAL SERVICES

Count on Cat Financial to provide the best finance and extended protection solutions for your business. For more than 30 years, we have helped our customers succeed through financial service excellence.



DOZERS



SKID STEERS



MATERIAL HANDLERS



EXCAVATORS



WHEEL LOADERS



TRACK LOADERS

# INCREASE YOUR PRODUCTIVITY AND PROFIT WITH CAT ATTACHMENTS

You can easily expand the performance of your 313 GC by utilizing a variety of Cat attachments. Each Cat attachment is designed to fit the weight and horsepower of the Cat excavator for improved performance, safety, and stability.

## GENERAL DUTY BUCKETS



## VIBRATORY PLATES



## BETTER BUCKET, GREATER PAYDAYS

Get greater payloads and paydays with the Cat general duty excavation bucket.

## HYDRAULIC HAMMERS



## PREVENT HAMMER WEAR AND TEAR

Protect your hammer tool from overheating and rapid wear. Auto hammer stop warns you after 15 seconds of continuous firing and then automatically shuts it off after 30 seconds – all to extend the tool's service life.

# TECHNICAL SPECIFICATIONS

## Engine

Net Power – ISO 9249	70.6 kW	95 hp
Engine Model	Cat® C3.6	
Engine Power – ISO 14396	74.4 kW	100 hp
Engine Power – ISO 14396 – Metric	101 mhp	
Net Power – ISO 9249 – Metric	96 mhp	
Bore	98 mm	4 in
Stroke	120 mm	5 in
Displacement	3.6 L	220 in <sup>3</sup>
Biodiesel Capability	Up to B20 <sup>1</sup>	
Emissions	Meets Brazil MAR-1 emission standards equivalent to U.S. EPA Tier 3 and EU Stage IIIA.	

Net power advertised is the power available at the flywheel when the engine is equipped with fan, air intake system, exhaust system and alternator with engine speed at 2,200 rpm. Advertised power is tested per the specified standard in effect at the time of manufacture.

<sup>1</sup>Cat engines are compatible with diesel fuel blended with the following lower-carbon intensity fuels\*\* up to 100% biodiesel FAME (fatty acid methyl ester)\* or 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels.

\*For use of blends higher than 20% biodiesel, consult your Cat dealer.

\*\*Lower-carbon intensity fuels do not significantly reduce GHGs

## Hydraulic System

Main System – Maximum Flow – Total	247 L/min	65 gal/min
Maximum Pressure – Equipment	35 000 kPa	5,075 psi
Maximum Pressure – Swing	25 900 kPa	3,756 psi
Maximum Pressure – Travel	35 000 kPa	5,075 psi

## Swing Mechanism

Swing Speed	11.5 r/min	
Maximum Swing Torque	43 kN-m	31,640 ft-lbf

## Weights

Operating Weight	15 800 kg	34,900 lb
------------------	-----------	-----------

Low Ground Pressure undercarriage, HD Reach boom, HD R2.5 (8'2") stick, GD 0.65 m<sup>3</sup> (0.85 yd<sup>3</sup>) bucket, 960 mm (38") triple grouser track shoes and 1300 kg (2,870 lb) counterweight.

## Service Refill Capacities

Fuel Tank Capacity	237 L	62.6 gal
Cooling System	11 L	2.9 gal
Engine Oil	11 L	2.9 gal
Final Drive – Each	6 L	1.6 gal
Hydraulic System – Including Tank	145 L	38.3 gal
Hydraulic Tank	77 L	20.3 gal

## Dimensions

Boom	Reach Boom 4.65 m (15'3")	
Stick	Reach Stick R2.5 m (8'2")	
Bucket	General Duty	
Shipping Height – Top of Cab	3190 mm	10.42 ft
Shipping Height	3220 mm	10.58 ft
Shipping Length	7680 mm	25.17 ft
Transport Width	2890 mm	9.5 ft
Tail Swing Radius	2200 mm	7.25 ft
Counterweight Clearance	1260 mm	4.17 ft
Ground Clearance	650 mm	2.17 ft
Track Length	4000 mm	13.08 ft
Track Gauge	2080 mm	6.83 ft

## Working Ranges

Boom	Reach Boom 4.65 m (15'3")	
Stick	Reach Stick R2.5 m (8'2")	
Bucket	General Duty	
Maximum Digging Depth	5180 mm	17 ft
Maximum Reach at Ground Level	8100 mm	26.58 ft
Maximum Cutting Height	8860 mm	29.08 ft
Maximum Loading Height	6460 mm	21.17 ft
Minimum Loading Height	2380 mm	7.83 ft
Maximum Depth Cut for 2440 mm (8'0") Level Bottom	4970 mm	16.33 ft
Maximum Vertical Wall Digging Depth	4500 mm	14.75 ft
Bucket Digging Force (ISO)	98.5 kN	22,140 lbf
Stick Digging Force (ISO)	68.8 kN	15,470 lbf

# STANDARD & OPTIONAL EQUIPMENT

NOTE: Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional
<b>UNDERCARRIAGE AND STRUCTURES</b>		
HD travel motor guards	✓	
Center track guiding guard	✓	
Grease lubricated track link	✓	
Low Ground Pressure undercarriage	✓	
1300 kg (2,870 lb) counterweight	✓	
Bottom guard	✓	
Swivel guard		✓
790 mm (31") triple grouser track shoes		✓
960 mm (38") single grouser track shoes		✓
<b>CAT TECHNOLOGY</b>		
Cat Product Link	✓	
<b>CAB</b>		
Sound suppressed with viscous mounts	✓	
Keyless push-to-start engine control	✓	
Automatic bi-level air conditioner	✓	
Fixed left side console	✓	
51 mm (2") orange seat belt	✓	
Mechanically adjustable seat with headrest	✓	
Emergency exit	✓	
High-resolution 203 mm (8") LCD touchscreen monitor	✓	
Cup holder and storage compartments	✓	
24V DC outlet	✓	
Speaker	✓	
AM/FM radio with Bluetooth	✓	
Washable floor mat	✓	
Dome light	✓	
Openable steel hatch	✓	
Upper radial wiper with washer	✓	
70/30 tempered glass windshield	✓	
1-button joystick		✓
Roller front sunscreen		✓
1-slider joystick		✓
<b>ENGINE</b>		
-18° C (-0.4° F) cold start capability	✓	
Cat C3.6 single turbo diesel engine	✓	
<b>BOOMS, STICKS AND LINKAGES</b>		
2.5 m (8'2") HD Reach stick	✓	
4.65 m (15'3") HD Reach boom	✓	
Bucket linkage without lifting eye	✓	

	Standard	Optional
<b>ELECTRICAL SYSTEM</b>		
LED left-side boom and chassis lights	✓	
Centralized electrical disconnect switch	✓	
1,000 CCA maintenance-free batteries (x2)	✓	
LED right-side boom light		✓
LED cab light		✓
<b>SERVICE AND MAINTENANCE</b>		
Radiator screen	✓	
Scheduled Oil Sampling (S.O.S) ports	✓	
Grouped engine oil and fuel filters	✓	
<b>HYDRAULIC SYSTEM</b>		
Element type main hydraulic filter	✓	
Automatic two-speed travel	✓	
Electronic control pump	✓	
Electronic main control valve	✓	
Tool control (one way high pressure flow)		✓
Tool control (without high pressure flow)		✓
Tool control (two way high pressure flow)		✓
Main control valve without tool control		✓
<b>SAFETY AND SECURITY</b>		
Hydraulic lock out lever neutralizes all controls	✓	
Ground-level secondary engine shutoff switch	✓	
Signaling/warning horn	✓	





For more complete information on Cat products, dealer services and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com).

© 2024 Caterpillar. All Rights Reserved.

VisionLink is a trademark of Caterpillar Inc., registered in the United States and in other countries.

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, SmartBoom, S·O·S, Product Link, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.  
[www.cat.com](http://www.cat.com) [www.caterpillar.com](http://www.caterpillar.com)



AEXQ3743-00  
Build Number: 05D  
(Indonesia, SE Asia)

