



Perkins® Diesel Engine Oil (DEO)

The difference is in the detail

SAE 15W-40 API CI-4.

Diesel engine oil for Europe, Africa, Middle East, Americas and Asia Pacific.

Recommended use.

- Perkins' full range of Tier 3 and below, emissions compliant diesel engines
- Recommended for commercial, industrial, marine, on-highway and off-highway applications including construction, mining, quarrying and agriculture
- Suitable for engines with common rail electronic and mechanical fuel injection systems
- Heavy-duty diesel engines made by other manufacturers that recommend API CI-4 or CH-4 classification oil
- Mixed fleet applications including automotive gasoline engines that require API SJ/SL classification oils

Features and benefits.

Perkins® Diesel Engine Oil is tested and recommended by Perkins to meet the high standards of genuine Perkins parts.

High performance diesel engine oil that provides excellent lubrication:

- Increased engine life – resists oxidation and inhibits build up of deposits on pistons and rings
- Provides confidence in oil drain intervals - while delivering excellent engine protection
- Proven performance – extensively tested to provide excellent engine life and high performance
- Long-lasting protection – improved soot control and enhanced shear stability enable oil to maintain proper viscosity for longer operating periods in Perkins engines with electronic ignition and common rail fuel systems

Typical characteristics.*

SAE viscosity grade	15W-40
API service classification: <ul style="list-style-type: none">• Diesel• Gasoline	CI-4, CH-4 SL/SJ
ACEA classifications	E7-12
Meets the specifications below set by the following companies: <ul style="list-style-type: none">• Caterpillar• MB• MAN• Renault• Volvo• Cummins • Mack	ECF-2 228.3 3275-1 RLD-2 VDS-3 CES 20071/ 72/76/77 EON/ EO-M PLUS
Flash point, °C (ASTM D92)	230
Density, g/mL @ 15.6°C (ASTM D4052)	0.879
Pour point, °C (ASTM D97)	-30
Viscosity: <ul style="list-style-type: none">• Kinematic cSt @ 40°C (ASTM D445)• Kinematic cSt @ 100°C (ASTM D445)	106 14.5
Viscosity index (ASTM D2270)	135
Sulphated ash, % wt. (ASTM D874)	1.3
TBN (ASTM D2896)	11.3
Zinc, % wt. spectro or AA or ICP0	140

* The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice.

Why use Perkins genuine parts?

Perkins genuine parts are designed to work together to maximise component life and engine performance. Genuine parts restore optimum power and fuel efficiency and are supported by the Perkins warranty.

Perkins product support network.

We offer you the right parts and service solutions, when and where you need them.

Perkins distributors are highly trained experts helping to keep your entire fleet up and running to maximise your equipment investment.

Tested beyond industry standards.

Perkins DEO has undergone in-house multi-cylinder endurance tests, a variety of quality assurance tests and thousands of hours of field service. Ensuring your confidence to deliver reliable performance and long lasting protection of your engine.



For a copy of the MSDS please visit
www.perkins.com/msds

Perkins filters: complete protection for your machine.

Combine Perkins fluids with Perkins filters for a high level of contamination control and protection for your engine. We recommend Perkins filters for all Perkins engine applications.

Health and safety.

Under normal conditions of intended use, this product does not pose a risk to health.

Excessive exposure may result in eye, skin or respiratory irritation. Always observe good hygiene measures.

Read and understand the Material Safety Data Sheet (MSDS) before using this product.