



Cat[®] 395

Hydraulic Excavator

The Cat[®] 395 Excavator is a powerhouse that gets the job done every time. Built with the 540 horsepower Cat[®] C18 engine, this machine is a groundbreaking rockstar with fast cycle times and a powerful digging force that eases bucket penetration and digs down deep with maximum digging depths from 7.2 m (23.7 ft) up to 11.7 m (38.5 ft). Equipped with the latest Cat technology, the 395 helps you make informed and smart decisions to help improve jobsite efficiency, increase productivity, and return safely home every day. If you want to generate big-time results for your business, put the 395 next generation excavator to work. It is the top choice in its size class.

Latest Features

Machine Setup Simplification

- At the touch of fingertips and navigating user-friendly icons, the latest operator oriented User Interface (UI) maximizes uptime and gets crews to work without delay. From re-ordering work tool lists to creating new work tool combinations as needed, operators can quickly set up machines and easily access information.
- The interface allows operators to maintain accuracy and makes the most of every second of their shift. Adding the ability to input couplers and attachments into the system makes setting up work tool combinations highly efficient by significantly reducing calibration time. It also eliminates the need to measure up again when changing Cat[®] work tool attachments and makes it manageable for a single person to check and adjust for bucket wear.

Cat Grade 3D Ready

- The Cat Grade 3D Ready option includes all the hardware required for the Grade with 3D system, installed and tested from the factory. This option provides an easier upgrade path for customers who want to add Grade with 3D after their initial purchase. To activate, contact your Cat Dealer to purchase the required 3D software licenses. Licenses can be installed remotely or manually loaded onto the machine.

Cat Payload and Advanced Payload

- Cat Payload provides operators with on-the-go weighing to help them hit load targets and avoid overloading, underloading, or misloading materials. Advanced Payload is a system upgrade that offers expanded features and capabilities, including custom tags, daily totals, and electronic ticketing. Combine Payload with VisionLink[®] Productivity* to analyze jobsites and individual assets for remote management of production targets and key metrics.

**VisionLink[®] subscription required. Availability may vary by region, consult your Cat[®] Dealer for more details.
Build Number: 07H*

Performance Powerhouse

- Work up to 3000 m (9,840 ft) above sea level without de-rating.
- The exclusive hydrostatic swing circuit has a dedicated bi-directional swing pump, swing motors, charge pump, and charge accumulator. The swing pump supplies oil to the swing motor; the charge pump and charge accumulator prevent cavitation (air bubbles) and overheating. The circuit enables regenerating swing brake energy and independent management of cylinder oil flow, resulting in higher efficiency and smoother, more predictable performance when you multi-task with the excavator.
- Powerful swing torque easily handles changes in momentum, uneven terrain, and consistent high-impact connections, helping operators make their work swift and precise.
- Did you know baffle plates help increase an excavator's strength-to-weight ratio? That is why Caterpillar incorporates the plates in high-stress areas like the boom, stick, and frame. Reinforcing the machine without adding significantly more weight also helps provide years of reliable performance, even in the harshest environments.
- The cylinder rods are reinforced with additional wear rings to help reduce oil leaks. The car body has thick baffle plates for a long service life. The thick track link has large bolt joints to help maintain bolt retention. Track rollers have a large shaft diameter to help prevent bending and oil leaks while increasing the 395's loading capacity, which means more reliable production for you.
- Grease sealed between track pins and bushings reduces travel noise and prevents debris from entering to increase undercarriage life.
- The center track guiding guard helps align the excavator track when traveling and working on slopes.
- The sloped track frame prevents mud and debris accumulation, helping reduce the risk of track damage.
- Auxiliary (AUX) hydraulic options allow you to use a wide range of Cat[®] attachments.
- Advansys[™] bucket tips increase penetration and improve cycle times. Tip changes can be done quickly with a simple lug wrench instead of a hammer or special tool, improving safety and uptime.
- Match the excavator to the job with three operating modes: Power, Smart, and ECO.



Cat® 395 Hydraulic Excavator

Performance Powerhouse *(continued)*

- Smart mode automatically adjusts power for the highest fuel efficiency – less power for tasks such as swinging and more power for digging.
- Enhanced heavy lift mode increases system pressure to help you easily pick and place heavy material.
- Auto warm-up speeds up hydraulic oil warming in cold temperatures and helps prolong the life of components.
- Don't let the temperature stop you from working. This excavator has a high-ambient capability of 52° C (125° F) and a standard cold start capability of -18° C (-0.4° F).
- The engine meets U.S. EPA Tier 4 Final, EU Stage V, Korea Stage V and Japan 2014 emission standards with an aftertreatment system that requires no operator input or downtime.

Exceptional Efficiency Through Technology

- The latest operator oriented User Interface (UI) has been designed to maximize uptime by allowing operators to easily re-order work tool lists and quickly create new work tool combinations. It also eliminates the need to measure up again when changing Cat® work tool attachments and makes it manageable for a single person to check and adjust for bucket wear.
- Cat® Lift Assist helps avoid machine tipping. With visual and auditory alerts, operators will know if their load is within the excavator's safe working range limits.
- Cat® 2D E-Fence restricts the front linkage from moving beyond operator-defined preset boundaries for the ceiling, floor, wall, swing, and cab. It helps operators avoid jobsite hazards such as traffic, keeps personnel safe, and helps you save on costly repairs, equipment downtime, and potential jobsite fines.
- Cat® Detect – People Detection for excavators is an intelligent vision camera system that can alert an operator when someone enters a machine's hazard zone.*
- Cat® Grade with Assist helps operators stay on grade simply and effortlessly with semi-autonomous digging. It automates boom, stick, and bucket movements to deliver more accurate cuts with less effort.
- Cat® Grade with 2D for excavators is an indicate system that helps operators reach grade faster.* Select your target depth and slope and watch the Grade with 2D system use on-board processors and sensors to provide real-time guidance on the distance to grade.
- Cat® Grade with 3D for excavators helps operators grade more quickly, accurately, and efficiently, improving productivity.* It incorporates Global Navigation Satellite System (GNSS) technology and Real Time Kinematic (RTK) positioning guidance to streamline the grading process for complex designs commonly encountered on large infrastructure and commercial projects. This system allows operators to work confidently, eliminating guesswork while cutting and filling to precise specifications.
- The Cat® Grade 3D Ready option includes all the hardware required for the Grade with 3D system, installed and tested from the factory. Activation requires the purchase of additional 3D software licenses, contact your Cat Dealer for details.
- Upgrade to our dual antenna GNSS for maximum grading efficiency. The system lets you create and edit designs on the touchscreen monitor while you're on the job, or you can have the plan design sent to the excavator to make your work easier. Plus, you get added benefits of avoidance zones, cut and fill mapping, lane guidance, and augmented reality along with advanced positioning capability.
- All Cat Grade systems are compatible with radios and base stations from Trimble, Topcon, and Leica. Already invested in a grade infrastructure? You can install grade systems from Trimble, Topcon, and Leica onto the machine.

- Cat® Payload provides operators with on-the-go weighing to help them hit load targets and avoid overloading, underloading, or misloading materials. Advanced Payload is a system upgrade that offers expanded features and capabilities, including custom tags, daily totals, and electronic ticketing. Combine Payload with VisionLink® Productivity** to analyze jobsites and individual assets for remote management of production targets and key metrics. Cat® Operator Coaching allows operators of all experience levels to take their efficiency and productivity to the next level. With tips and data at their fingertips, operators can track and improve their productivity through everyday work on the jobsite. Gain data-based insights towards operators and operations when you pair Operator Coaching with VisionLink® Productivity.** There are two coaching tip categories –

1. Operational Efficiency Tips: Help operators stay at the top of their game by identifying areas to increase skill and efficiency, such as digging technique and idle times.
2. Machine Health Tips: Some actions are inefficient and cause unnecessary wear and tear on the machine and its components. Following Machine Health Tips can help extend the life of the machine, improve digging technique, and reduce fuel waste.

**The system may not detect personnel in certain circumstances, such as fast swing speeds, people lying down or crouching, or when cameras are impaired by low light conditions (dusk, dawn, overcast), inclement weather (snow, rain, fog), or other similar conditions. For limitations of use, refer to the operation and maintenance manual.*

***VisionLink® subscription required.*

NOTE: Cat® Payload for excavators is not legal for trade. Availability may vary by region, consult your Cat Dealer for more details.

Take the Guesswork Out of Managing Your Equipment

- VisionLink® provides actionable data insights for all assets – regardless of fleet size or equipment manufacturer.* Review equipment data from your desktop or mobile device to maximize uptime and optimize assets. Dashboards provide information such as hours, miles, location, idle time, and fuel utilization. Make informed decisions that lower costs, simplify maintenance, and improve safety and security on your jobsite.
- VisionLink® Productivity gathers and summarizes machine telematics and jobsite data from all your equipment – regardless of the manufacture.* View actionable information such as idle time, fuel burn, location, payload, load counts, total cycles, and more to improve machine efficiency, productivity, and utilization. Access data anywhere via a mobile, tablet, or desktop device – on or off the jobsite.
- Cat® Inspect is a mobile application that allows you to easily perform digital preventative maintenance (PM) checks, inspections, and daily walkarounds. Inspections can easily be integrated with other Cat data systems like VisionLink® so you can keep a close eye on your fleet.
- Cat® Remote Troubleshoot is a mobile application that allows your Cat dealer to perform diagnostic testing on your connected machine remotely to help ensure that issues are resolved quickly and with less downtime.
- Cat® Remote Flash is a mobile application that allows you to update onboard software without a technician being present, allowing you to initiate software updates when convenient, increasing your overall operating efficiency.
- The Cat® PL161 attachment locator allows you to track attachments across all worksites, reduce the number of lost attachments, and plan for attachment maintenance and replacement. The work tool recognition** feature automatically adjusts machine settings based on the selected tool.

Take the Guesswork Out of Managing Your Equipment (continued)

- Cat® Command remote control enables equipment operators to work safely outside the machine when working in hazardous environments. Command offers the choice of handheld Consoles* (line-of-sight) or long-distance virtual Stations (non-line-of-sight). Deep integration with machine systems enables efficiency and productivity by maintaining the use of in-cab technology*** features (Grade, Payload, Assist, etc.).

*Data field availability can vary by equipment manufacturer.

**Recognition feature available on select excavator models.

***Not all technology features are available on the Command Console and vary by model. Consult your Cat Dealer for details.

Easy and Economical Maintenance

- The 395's extended and synchronized service intervals and reduced hydraulic oil capacity help you save time and money.
- The excavator is auto-lube ready with built-in mounting points; an available auto-lube retrofit kit provides additional hardware to mount a grease pump and line guards – all to help do the job of lubing safer, cleaner, and trouble-free.
- Boost productivity with proactive service reminders. The Integrated Vehicle Health Management system alerts the operator with step-by-step service guidance and parts needed so you don't experience unnecessary downtime.
- Track your excavator's filter life and maintenance intervals via the in-cab monitor.
- Fuel and engine oil filters are accessible from the upper platform and synchronized to be changed at 1,000 hours.
- The latest hydraulic oil filter provides high-quality filtration performance and features anti-drain valves to keep oil clean when the filter is replaced, and the 3,000-hour extended replacement interval offers efficiency and convenience.
- Scheduled Oil Sampling (S-O-SSM) ports with extended sampling intervals are on ground level, simplifying maintenance and allowing for quick, easy extraction of samples for fluid analysis.
- Using Cat® genuine oil and filters and doing typical S-O-S monitoring will extend the current service interval, giving you more uptime.
- The high-efficiency hydraulic fan has a programmable automatic reverse function to keep cores free from debris, eliminating the need for any operator interaction.
- The advanced air intake filter with pre-cleaner has a high dust-holding capacity.
- The latest engine air cleaners with an integrated pre-cleaner surpass radial seal air cleaners' lifespan.

Ultimate Operator Comfort

- Sites where excavators work are typically rugged and challenging. That's why it's important that the 395 cab help protect the operator as much as possible from fatigue, stresses, sounds, and temperatures of the job.
- Comfort and efficiency of movement help keep operators productive and alert all shift long. The standard seat is wide and adjustable for operators of virtually any size.
- The tip-up left console makes getting in and out of the seat easy.
- Two cab options – Deluxe, and Premium – let you choose the level of comfort you need.

- The Deluxe cab package includes a heated air suspension seat; the Premium seat is heated and cooled.
- The cab is sound-suppressed and sealed.
- Advanced viscous mounts reduce cab vibration.
- Control the excavator comfortably with easy-to-reach controls located in front of you.
- The touchscreen monitor makes it easy to access critical information and settings. Shortcut keys make it easy, and two are for entertainment, heating, and air conditioning. There is also a shortcut key for apps and functions that you can set.
- Standard automatic climate control keeps you at the right temperature throughout your shift.
- Convenience features include Bluetooth® integrated radio, USB charging and phone connectivity ports, 12V DC outlets, and an AUX port.
- Cup and bottle holders are easy to reach, and storage spaces are located conveniently throughout the cab.
- Stow your gear with plenty of in-cab storage beneath and behind the seat, overhead, and in the consoles.

Not all features are available in all regions. Please check with your local Cat® dealer for specific offering availability in your area.

Safely Home Every Day

- Operator ID keeps your excavator secure. To enable the push-button starting feature, use your PIN code on the monitor or the optional Bluetooth key fob.
- Serrated steps, anti-skid plating, and handrails help you avoid slips and trips – a major contributor to workplace injuries.
- Standard Lift Assist quickly calculates the actual load you are lifting and compares it to the rated load the excavator is capable of handling. Visual and auditory alerts tell you if you are within safe working range or need to take immediate action to avoid tipping.
- See all around the machine with the premium 360 lighting package. The 1,800-lumen lights on the chassis, cab, boom, sides, and rear illuminate the jobsite for operators and ground personnel.
- Add optional inspection lighting to illuminate the engine, pump, battery, and cooling compartments, making service work more accessible.
- Whether you are using a bucket, hammer, grapple, or clamshell, standard 2D E-fence automatically stops excavator motion using boundaries you set in the monitor for the entire working envelope – above, below, sides, and front. E-fence protects equipment from damage and helps reduce fines related to zoning or underground utility damage. Automatic boundaries even help prevent operator fatigue by reducing overswinging and overdigging. A travel direction indicator helps operators know which way to activate the travel levers.
- Consider adding Cat® Command to your fleet. The remote-control system keeps you away from potential hazards. The non-line-of-site kit has a Wi-Fi radio, cameras, and a microphone to work anywhere.
- Small cab pillars, large windows, and a flat engine hood design help you enjoy great visibility into the trench, in each swing direction, and behind you.
- Add a swing alarm to alert people when rotating from the trench to the stockpile.
- Rear and right-hand-sideview cameras are standard. Upgrade to 360° visibility, and you'll easily visualize objects and personnel around the excavator in a single view.

Cat® 395 Hydraulic Excavator

Safely Home Every Day *(continued)*

- A ground-level shutoff switch stops all fuel to the engine when activated and shuts down the machine.
- The right-hand service platform design help provide easy, safe, and quick access to the upper service platform; the service platform steps use serrated steps and an anti-skid punch plate to prevent slipping. The handrails comply with ISO 2867 requirements.

Intuitive and Empowering to Operate

- The 395 uses a keyless push-button engine start. This adds security for the machine by using Operator ID codes to limit and track machine access. Codes can be entered manually via an optional Bluetooth key fob.
- Most machine settings can be controlled through the high-resolution touchscreen monitor. It offers several languages and is easy to reach from the seat – no twisting or turning.
- A second 254 mm (10 in) monitor is available for the Cat® Grade and Cat® Grade with 3D.
- Operating can be made easier with the touch of a joystick button. The joystick function can be customized through the monitor. The joystick pattern and response can be set to match operator preference. All preferences are saved with the Operator ID and restored at login.
- Make moving the excavator much easier with Cat® Stick Steer. Push a button and use one hand to travel and turn instead of both hands or feet on levers or pedals.
- You can also add an auxiliary relay to power on or turn off a CB radio, beacon light, or other attachment so you don't have to take your hands off the joysticks.
- Program up to four depth and slope offsets so you can easily get to grade without a grade checker – saving time and enhancing safety on the jobsite.
- Operator coaching is an in-cab system that recognizes specific opportunities for operators to be more productive and prevent unnecessary machine wear and tear.
- Not sure how a function works or how to maintain the excavator? Always have the operator's manual at your fingertips on the touchscreen monitor.
- Use the in-monitor QR code to learn about machine and technology features through a full suite of "how-to" videos.

Not all features are available in all regions. Please check with your local Cat® dealer for specific offering availability in your area.

Sustainability

- The Cat® C18 engine meets U.S. EPA Tier 4 Final, EU Stage V, Korea Stage V and Japan 2014 emission standards.
- Cat diesel engines are required to use ULSD (ultra-low sulfur diesel fuel with 15 ppm of sulfur or less) or ULSD blended with the following lower-carbon intensity fuels** up to: 20% biodiesel FAME (fatty acid methyl ester)* or 100% renewable diesel, HVO (hydrogenated vegetable oil) and GTL (gas-to-liquid) fuels. Refer to guidelines for successful application. Please consult your Cat dealer or "Caterpillar Machine Fluids Recommendations" (SEBU6250) for details.
- A well-trained operator is worth the investment. Skilled operators benefit your bottom line by maximizing productivity, avoiding costly downtime, and maintaining jobsite safety – which can help to improve fuel efficiency and reduce greenhouse gas emissions.

- Cat® Grade technologies combine advanced guidance with optional automated machine control, helping you reach grading targets while reducing fuel burn and greenhouse gas emissions by improving efficiency, jobsite productivity, and accuracy.
- Auto Engine Speed Control helps reduce unnecessary fuel burn and greenhouse gas emissions by allowing the engine to automatically go into idle mode when the machine is not working.
- Cat® Payload for excavators provides on-the-go material weighing, which helps reduce fuel burn by improving loading efficiency, jobsite productivity, and eliminating trips to the scale.
- Cat® 2D E-fence keeps the front linkage within a pre-defined work area to aid in avoiding hazards such as traffic – not only helping keep personnel safe but also helping you avoid repairs, downtime, and costly jobsite fines.
- Extended maintenance intervals help reduce downtime and decrease the amount of fluid and filters replaced over the machine's life.
- Cat® VisionLink displays the CO₂ emissions for monitored assets, calculated by fuel type for the Runtime Fuel Burned each day in a selected date range.
- Remote Flash helps minimize downtime and maintenance time while keeping your asset running at maximum efficiency. Alerts for machine updates are sent virtually from your Cat® dealer, and updates can be deployed without a dealer technician needing to be onsite.
- Remote Troubleshoot helps decrease maintenance time and keeps your machine running with maximum efficiency by allowing your Cat® dealer to virtually test the machine while working. Once a problem is identified, a technician can fix it the first time, saving time and money.

**Engines with no aftertreatment devices can use higher blends, up to 100% biodiesel (for use of blends higher than 20% biodiesel, consult your Cat dealer).*

***Tailpipe greenhouse gas emissions from lower-carbon intensity fuels are essentially the same as traditional fuels.*

395 Long Reach Excavator

- The Cat® 395 Long Reach Excavator (LRE) combines premium performance and simple-to-use technology.
- The 395 LRE has a maximum reach capability of 28 meters (91'10") and a dig depth of 21 700 mm (71'2").
- The long and extended undercarriage and 21.6 mt (47,600 lb) counterweight provide a stable platform for long-reach digging.
- This machine excels in ultimate long-distance dredging, ditch cleaning, settling pond clean-out, waterway and canal maintenance, and vegetation control.

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
UNDERCARRIAGE AND STRUCTURES			CAT TECHNOLOGY (continued)		
Long variable gauge undercarriage	✓		Cat Grade Connectivity		✓
Swivel guard	✓		Cat Grade 2D with Attachment Ready Option (ARO)		✓
Grease lubricated track	✓		Cat Grade with 3D (single or dual GNSS)		✓
Standard counterweight	✓		Cat Grade 3D Ready		✓
Heavy Duty (HD) bottom guard	✓		GNSS antennae		✓
HD travel motor guard	✓		Laser catcher		✓
Long variable gauge	✓		Cat Tilt Rotator (TRS) Integration		✓
Standard counterweight	✓		Operator Coaching		✓
Towing eye on base frame	✓		Advanced Payload (Daily totals, Custom lists, Smart weight target, E-ticket Integration)		✓
Towing eye on base frame	✓		1,800 lumen LED premium surround lights		✓
BOOMS AND STICKS			LED boom and cab lights		✓
7.25 m (23'9") Mass boom		✓	-32° C (-25° F) cold start capability		✓
5.5 m (18'1") HD Reach stick		✓	Cold start block heaters		✓
8.4 m (27'7") General Purpose (GP) boom		✓	Hydraulic efficiency monitoring		✓
10 m (32'10") Reach boom		✓	Advanced tool control		✓
2.92 m (9'7") Mass stick		✓	Medium-pressure auxiliary circuit		✓
2.92 m (9'7") GP stick		✓	Quick coupler circuit		✓
3.4 m (11'2") Mass stick		✓	Smart Boom		✓
3.4 m (11'2") GP stick		✓	Cat Command remote control		✓
3.7 m (12'2") GP stick		✓	Swing alarm		✓
4.4 m (14'5") HD Reach stick		✓	360° visibility		✓
Bucket linkage, HB2 type without lifting eye, Autolube ready		✓	Boom lowering check valve		✓
Bucket linkage, HB2 type without lifting eye, Autolube ready		✓	Stick lowering check valve		✓
Bucket linkage, JC type with lifting eye, Autolube ready		✓	Inspection lighting		✓
Bucket linkage, JC type without lifting eye, Autolube ready		✓	Cat Detect people detection		✓
CAT TECHNOLOGY			Swing alarm		✓
VisionLink®	✓		360° visibility		✓
Remote Flash	✓		Boom lowering check valve		✓
Remote Troubleshoot	✓		Stick lowering check valve		✓
Operator Coaching	✓		Inspection lighting		✓
Compatibility with radios and base stations from Trimble, Topcon, and Leica	✓		Tilt-up walkway		✓
Capability with 3D grade systems from Trimble, Topcon, and Leica	✓		Bluetooth key fob		✓
Cat Grade with 2D	✓		76 mm (3") retractable seat belt		✓
Cat Assist (Grade, Boom, Bucket, Swing, Lift)	✓		Electric refueling pump with auto shutoff		✓
Cat Payload (On-the-go weighing, Semiautomatic calibration, Payload/cycle information, USB Reporting Capability)	✓		Fast-fill fuel system		✓
Work tool recognition and tracking (Requires PL161 attachment locator on work tool and Bluetooth receiver on machine)	✓		QuickEvac maintenance ready		✓
VisionLink® Productivity		✓	Counterweight with removal device		✓
VisionLink® Productivity back office reporting		✓	650 mm (26") HD double grouser track shoes		✓
			750 mm (30") HD double grouser track shoes		✓
			900 mm (35") HD double grouser track shoes		✓
			Three-piece segmented track guiding guards		✓
			Two-piece segmented track guiding guards		✓

Cat® 395 Hydraulic Excavator

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
ENGINE			CAB		
Three selectable modes: Power, Smart, and Eco	✓		High-resolution 254 mm (10") LCD touch screen monitor	✓	
Auto engine speed control	✓		Heated seat with air-adjustable suspension (Deluxe only)	✓	
Up to 4500 m (14,760 ft) altitude capability	✓		Heated and cooled seat with auto adjustable suspension (Premium only)	✓	
52° C (126° F) high-ambient cooling capacity	✓		Sound suppressed cab with viscous mounts	✓	
-18° C (-0.4° F) cold start capability	✓		Automatic bi-level air conditioner	✓	
Hydraulic reverse fan	✓		Jog dial and shortcut keys for monitor control	✓	
Double element air filter with integrated pre-cleaner	✓		Keyless push-to-start engine control	✓	
3 vertical side-by-side cooling system	✓		Height-adjustable console, infinite with no tool	✓	
Remote disable	✓		Tilt-up left-side console	✓	
95 Amp alternator	✓		51 mm (2") orange seat belt	✓	
ELECTRICAL SYSTEM			Bluetooth integrated radio (including USB, AUX port and microphone)	✓	
Maintenance-free 1,400 CCA batteries (x2)	✓		2 x 12V DC outlets	✓	
Centralized electrical disconnect switch	✓		Cup and storage compartments	✓	
Chassis light	✓		Openable two-piece front window (Deluxe standard)	✓	
Exterior lights (integrated into storage box)	✓		Upper radial wiper with washer (Deluxe cab only)	✓	
SERVICE AND MAINTENANCE			Parallel wiper with washer (Premium only)	✓	
Integrated vehicle health management system	✓		Openable polycarbonate skylight hatch (Deluxe standard)	✓	
Auto lube ready	✓		LED dome light	✓	
Grouped location of engine oil and fuel filters	✓		Floor welcome light	✓	
Scheduled Oil Sampling (S-O-S SM) ports	✓		Roller front sunscreen	✓	
QuickEvac maintenance ready	✓		Roller rear sunscreen (Premium standard)	✓	
Reversing cooling fan	✓		Rear window emergency exit	✓	
HYDRAULIC SYSTEM			Washable floor mat	✓	
Boom and stick regeneration circuit	✓		Beacon Ready	✓	
Electronic main control valve	✓		Cat® Stick Steer		✓
Dedicated closed loop swing circuit	✓		Auxiliary relay		✓
Anti-reaction valve	✓		Additional high-resolution LCD touch screen monitor for Cat® Grade Advanced 2D and 3D		✓
Auto hydraulic oil warmup	✓		Roller rear sunscreen (Deluxe)		✓
Auto swing parking brake	✓		Radial lower wiper		✓
High performance hydraulic return filter	✓		Joystick with horizontal sliders		✓
Two speed travel	✓		Left Hand (LH)/RH electrical pedal for tool control		✓
Bio hydraulic oil capability	✓		Dual exit rear window kit		✓
SAFETY AND SECURITY			Front windshield laminated glass (P5A glass, EU demolition regulation)		✓
Caterpillar One Key security system	✓		Cab/Operator Protective Guards (OPG) (not compatible with cab light cover, rain protector)		✓
Lockable fuel drain compartment	✓		Mesh guard full front (not compatible with cab light, cover, rain protector)		✓
Lockable external tool/storage box	✓		Mesh guard lower half front		✓
Lockable door, fuel, and hydraulic tank locks	✓		Rain protector for front windshield plus cab light cover		✓
Lockable disconnect switch	✓				
Service platform with anti-skid plate and recessed bolts	✓				
Right hand (RH) handrail and hand hold (ISO 2867:2011 compliant)	✓				
Visibility mirror package	✓				
Signaling/warning horn	✓				
Ground-level secondary engine shutoff switch	✓				
Rearview and right-hand-sideview cameras	✓				
Walkway	✓				
Travel alarm	✓				
2D E-Fence (E-ceiling, E-floor, E-swing, E-wall, E-cab avoidance)	✓				

Technical Specifications

Engine

Net Power – ISO 9249	404 kW	542 hp
Net Power – ISO 9249 (DIN)	550 hp (metric)	
Engine Model	Cat C18	
Engine Power – ISO 14396	405 kW	543 hp
Engine Power – ISO 14396 (DIN)	551 hp (metric)	
Bore	145 mm	6 in
Stroke	183 mm	7 in
Displacement	18.1 L	1,105 in ³
Biodiesel Capability	B20 ¹	
Emissions	Meets U.S. EPA Tier 4 Final, EU Stage V, Korea Stage V, and Japan 2014 emission standards.	

Net power advertised is the power available at the flywheel when the engine is equipped with fan, air intake system, exhaust system and alternator with engine speed at 1,700 rpm. Advertised power is tested per the specified standard in effect at time of manufacture.

¹Cat diesel engines are required to use ULSD (ultra-low sulfur diesel fuel with 15 ppm of sulfur or less) or ULSD blended with the following lower-carbon intensity fuels** up to: 20% biodiesel FAME (fatty acid methyl ester)* or 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels. Refer to guidelines for successful application. Please consult your Cat dealer or “Caterpillar Machine Fluids Recommendation” (SEBU6250) for details.

*Engines with no aftertreatment devices can use higher blends, up to 100% biodiesel (for use of blends higher than 20% biodiesel, consult your Cat dealer).

**Tailpipe greenhouse gas emissions from lower-carbon intensity fuels are essentially the same as traditional fuels.

Hydraulic System

Main System – Maximum Flow – Implement	1064 L/min	281 gal/min
Maximum Pressure – Equipment	37 000 kPa	5,366 psi
Maximum Pressure – Travel	35 000 kPa	5,076 psi
Maximum Pressure – Swing	31 000 kPa	4,496 psi

Swing Mechanism

Maximum Swing Torque*	362 kN·m	267,333 lbf·ft
-----------------------	----------	----------------

*For CE-marked machine default value may be set lower.

Weights

Operating Weight	94 000 kg	207,400 lb
------------------	-----------	------------

Long Variable Gauge undercarriage, GP boom, R4.4HB2 (14'5") stick, Severe Duty (SD) 5.2 m³ (6.8 yd³) bucket, 900 mm (35") double grouser shoes and counterweight with removal device.

Service Refill Capacities

Fuel Tank Capacity	1220 L	322 gal
Cooling System	71 L	19 gal
Engine Oil	67 L	18 gal
Swing Drive	24 L	6 gal
Final Drive – Each	20 L	5 gal
Hydraulic System – Including Tank	740 L	196 gal
Hydraulic Tank	372 L	98 gal
Diesel Exhaust Fluid (DEF) Tank	80 L	21 gal

Dimensions

Boom	GP 8.4 m (25'7")	
Stick	R4.4 m (14'5")	
Bucket	Severe Duty (SD) 5.2 m ³ (6.8 yd ³)	
Shipping Height – Top of Cab	3670 mm	12 ft
Handrail Height	3750 mm	12.4 ft
Shipping Length	15 090 mm	49.6 ft
Tail Swing Radius	4840 mm	15.11 ft
Counterweight Clearance	1640 mm	5.5 ft
Ground Clearance	830 mm	2.9 ft
Track Length	6350 mm	20.1 ft
Track Length to Center of Rollers	5120 mm	16.1 ft
Track Gauge	3510 mm	11.6 ft
Transport Width	3880 mm	12.9 ft

Track gauge undercarriage extended with 900 mm (35") shoes; transport width undercarriage retracted with 900 mm (35") shoes and no steps.

Working Ranges and Forces

Boom	GP 8.4 m (25'7")	
Stick	R4.4 m (14'5")	
Bucket	SD 5.2 m ³ (6.8 yd ³)	
Maximum Digging Depth	9670 mm	31.9 ft
Maximum Reach at Ground Level	14 710 mm	48.3 ft
Maximum Cutting Height	13 540 mm	44.5 ft
Maximum Loading Height	9250 mm	30.4 ft
Minimum Loading Height	3030 mm	9.11 ft
Maximum Depth Cut for 2440 mm (8 ft) Level Bottom	9560 mm	31.4 ft
Maximum Vertical Wall Digging Depth	6770 mm	22.3 ft
Bucket Digging Force – ISO	383 kN	86,100 lbf·ft
Stick Digging Force – ISO	305 kN	68,540 lbf·ft

Sustainability

Recyclability	98%
---------------	-----

Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1.00 kg (2.2 lb) of refrigerant, which has a CO₂ equivalent of 1.430 metric tonnes (1.576 tons).

Cat® 395 Hydraulic Excavator



オフロード法2014年
基準適合

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2025 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Advansys, S-O-S, Product Link, SmartBoom, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Caterpillar Inc., registered in the United States and in other countries.

AEXQ4188-00
Build Number: 07H
(Japan)

