



323 GX

Hydraulic Excavator

Technical Specifications

Configurations and features may vary by region. Please consult your Cat® dealer for availability in your area.

Table of Contents

Specifications	2
Engine Options	2
Swing Mechanism	2
Weights	2
Track	2
Drive	3
Hydraulic System	3
Service Refill Capacities	3
Standards	3
Sound Performance	3
Air Conditioning System	3
Operating Weights and Ground Pressures	4
Major Component Weights	5
Dimensions	6
Working Ranges	8
Reach Boom Lift Capacities – Counterweight: 4250 kg (9,370 lb)	10
Heavy Duty (HD) Reach Boom Lift Capacities – Counterweight: 4700 kg (10,360 lb)	14
Super Long Reach (SLR) Lift Capacities – Counterweight: 4700 kg (10,360 lb)	18
Bucket Specifications and Compatibility	22
Attachments Offering Guide:	
Africa, Middle East	23
Eurasia	24
Sri Lanka	25
Standard and Optional Equipment	26
Dealer Installed Kits and Attachments	28
323 GX Environmental Declaration	29

323 GX Hydraulic Excavator Specifications

Engine Options

Engine Model	Cat® C4.4	
Net Power:		
ISO 9249	123.7 kW	166 hp
ISO 9249 (DIN)	168 hp (metric)	
Engine Power:		
ISO 14396	129.4 kW	174 hp
ISO 14396 (DIN)	176 hp (metric)	
Bore	105 mm	4 in
Stroke	127 mm	5 in
Displacement	4.4 L	269 in ³
Biodiesel Capability	Up to B20 ⁽¹⁾	

- Cat C4.4 engine emits equivalent to U.S. EPA Tier 3 and EU Stage IIIA.
- Recommended for use up to 4500 m (14,764 ft) altitude with engine power derate above 3000 m (9,842 ft).
- Advertised power is tested per the specified standard in effect at the time of manufacture.
- Net power advertised is the power available at the flywheel when the engine is equipped with fan, air intake system, exhaust system and alternator.
- Engine speed at 2,000 rpm.

Engine Model	Cat® C7.1	
Net Power:		
ISO 9249	111.3 kW	149 hp
ISO 9249 (DIN)	151 hp (metric)	
Engine Power:		
ISO 14396	118 kW	158 hp
ISO 14396 (DIN)	160 hp (metric)	
Bore	105 mm	4 in
Stroke	135 mm	5 in
Displacement	7.01 L	428 in ³
Biodiesel capability	Up to B20 ⁽¹⁾	

- Cat C7.1 engine emits equivalent to U.S. EPA Tier 3 and EU Stage IIIA.
- Recommended for use up to 4500 m (14,764 ft) altitude with engine power derate above 3000 m (9,842 ft).
- Advertised power is tested per the specified standard in effect at the time of manufacture.
- Net power advertised is the power available at the flywheel when the engine is equipped with fan, air intake system, exhaust system and alternator.
- Engine speed at 1,800 rpm.

⁽¹⁾Cat engines are compatible with diesel fuel blended with the following lower-carbon intensity fuels** up to:

- ✓ 100% biodiesel FAME (fatty acid methyl ester)*
- ✓ 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels

Refer to guidelines for successful application. Please consult your Cat dealer or "Caterpillar Machine Fluids Recommendations" (SEBU6250) for details.

*For use of blends higher than 20% biodiesel, consult your Cat dealer.

**Tailpipe greenhouse gas emissions from lower-carbon intensity fuels are essentially the same as traditional fuels.

Swing Mechanism

Swing Speed*	11.13 rpm	
Maximum Swing Torque	82 kN·m	60,633 lbf·ft

*For CE-marked machine default value may be set lower.

Weights

Operating Weight (Non-Rollover Protective Structure [Non-ROPS])	21 400 kg	47,200 lb
---	-----------	-----------

- Medium undercarriage, Reach boom, R2.9B1 (9'6") stick, General Duty (GD) 1.2 m³ (1.57 yd³) bucket, 600 mm (24") triple grouser shoes and 4250 kg (9,370 lb) counterweight.

Operating Weight (ROPS)	21 600 kg	47,600 lb
-------------------------	-----------	-----------

- Medium undercarriage, Reach boom, R2.9B1 (9'6") stick, GD 1.2 m³ (1.57 yd³) bucket, 600 mm (24") triple grouser shoes and 4250 kg (9,370 lb) counterweight.

Operating Weight (Non-ROPS)	22 600 kg	49,800 lb
-----------------------------	-----------	-----------

- Long undercarriage, Heavy Duty (HD) Reach boom, HD R2.9B1 (9'6") stick, GD 1.43 m³ (1.87 yd³) bucket, 600 mm (24") triple grouser shoes and 4700 kg (10,360 lb) counterweight.

Operating Weight (ROPS)	22 800 kg	50,300 lb
-------------------------	-----------	-----------

- Long undercarriage, Heavy Duty (HD) Reach boom, HD R2.9B1 (9'6") stick, GD 1.43 m³ (1.87 yd³) bucket, 600 mm (24") triple grouser shoes and 4700 kg (10,360 lb) counterweight.

Track

Track Shoes Width	600 mm	24 in
-------------------	--------	-------

Track Shoes Width	790 mm	31 in
-------------------	--------	-------

Medium Undercarriage:

Number of Shoes (each side)	47
-----------------------------	----

Number of Track Rollers (each side)	7
-------------------------------------	---

Number of Carrier Rollers (each side)	2
---------------------------------------	---

Long Undercarriage:

Number of Shoes (each side)	49
-----------------------------	----

Number of Track Rollers (each side)	8
-------------------------------------	---

Number of Carrier Rollers (each side)	2
---------------------------------------	---

323 GX Hydraulic Excavator Specifications

Drive

Gradeability	35°/70%	
Maximum Travel Speed	5.7 km/h	3.5 mph
Medium Undercarriage:		
Maximum Drawbar Pull	200 kN	44,917 lbf
Long Undercarriage:		
Maximum Drawbar Pull	200 kN	44,872 lbf

Hydraulic System

Main System – Maximum Flow – Implement	429 L/min (214.5 × 2 pumps)	113 gal/min (56.7 × 2 pumps)
Maximum Pressure – Equipment – Normal	35 000 kPa	5,075 psi
Maximum Pressure – Travel	35 000 kPa	5,075 psi
Maximum Pressure – Swing	27 500 kPa	3,988 psi
Boom Cylinder – Bore	120 mm	5 in
Boom Cylinder – Stroke	1260 mm	50 in
Stick Cylinder – Bore	140 mm	6 in
Stick Cylinder – Stroke	1504 mm	59 in
Bucket Cylinder – Bore	120 mm	5 in
Bucket Cylinder – Stroke	1104 mm	43 in

Service Refill Capacities

Fuel Tank Capacity	390 L	103 gal
Cooling System:		
C4.4 engine	24.5 L	6.5 gal
C7.1 engine	32.5 L	8.6 gal
Engine Oil:		
C4.4 engine	15 L	4 gal
C7.1 engine	25 L	6.6 gal
Swing Drive	5.5 L	1.5 gal
Final Drive (each)	4.5 L	1.2 gal
Hydraulic System (including tank)	218 L	57.6 gal
Hydraulic Tank	115 L	30.4 gal

Standards

Brakes	ISO 10265:2008
ROPS*	ISO 12117-2 2008
Cab/Operator Protective Guards (OPG) (optional)	ISO 10262:1998 Level II

*Mandatory in Kingdom of Saudi Arabia; Optional in other regions.

Sound Performance

ISO 6395:2008 (external)	103 dB(A)
ISO 6396:2008 (inside cab)	70 dB(A)

- Hearing protection may be needed when operating with an open operator station and cab (when not properly maintained or doors/windows open) for extended periods or in a noisy environment.

Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a or R1234yf. See the label or instruction manual for identification of the gas.

If equipped with R134a (Global Warming Potential = 1430), the system contains 0.85 kg (1.9 lb) of refrigerant which has a CO₂ equivalent of 1.216 metric tonnes (1.34 tons).

323 GX Hydraulic Excavator Specifications

Operating Weights and Ground Pressures

Base Machine Configurations	600 mm (24 in) Triple Grouser Shoes		790 mm (31 in) Triple Grouser Shoes	
	Weight	Ground Pressure	Weight	Ground Pressure
Base Frame with Track Rollers and Carrier Rollers	kg (lb)	kPa (psi)	kg (lb)	kPa (psi)
4250 kg (9,370 lb) Counterweight and Medium Undercarriage Base Machine (non-ROPS)				
Reach Boom + R2.5B1 (8'2") Stick + 1.3 m ³ (1.7 yd ³) GD Bucket	21 400 (47,200)	46.9 (6.8)	21 900 (48,300)	36.5 (5.3)
Reach Boom + R2.9B1 (8'6") Stick + 1.2 m ³ (1.57 yd ³) GD Bucket	21 400 (47,200)	46.9 (6.8)	21 900 (48,300)	36.5 (5.3)
4250 kg (9,370 lb) Counterweight and Medium Undercarriage Base Machine (ROPS)				
Reach Boom + R2.5B1 (8'2") Stick + 1.3 m ³ (1.7 yd ³) GD Bucket	21 500 (47,400)	47.1 (6.8)	22 000 (48,500)	36.6 (5.3)
Reach Boom + R2.9B1 (8'6") Stick + 1.2 m ³ (1.57 yd ³) GD Bucket	21 600 (47,600)	47.4 (6.9)	22 100 (48,700)	36.8 (5.3)
4700 kg (10,360 lb) Counterweight and Long Undercarriage Base Machine (non-ROPS)				
HD Reach Boom + R2.5B1 (8'2") Stick + 1.3 m ³ (1.7 yd ³) GD Bucket	22 400 (49,400)	46.6 (6.8)	22 900 (50,500)	36.2 (5.3)
HD Reach Boom + HD R2.9B1 (9'6") Stick + 1.43 m ³ (1.87 yd ³) GD Bucket	22 700 (50,000)	47.3 (6.9)	23 200 (51,100)	36.7 (5.3)
Super Long Reach (SLR) Boom + SLR 6.28A (20'7") Stick + 0.57 m ³ (0.74 yd ³) Ditch Cleaning (DC) Bucket	22 600 (49,800)	47.0 (6.8)	23 100 (50,900)	36.5 (5.3)
4700 kg (10,360 lb) Counterweight and Long Undercarriage Base Machine (ROPS)				
HD Reach Boom + R2.5B1 (8'2") Stick + 1.3 m ³ (1.7 yd ³) GD Bucket	22 600 (49,800)	47.0 (6.8)	23 100 (50,900)	36.5 (5.3)
HD Reach Boom + HD R2.9B1 (9'6") Stick + 1.43 m ³ (1.87 yd ³) GD Bucket	22 800 (50,300)	47.5 (6.9)	23 300 (51,400)	36.8 (5.3)
Super Long Reach Boom + SLR 6.28A (20'7") Stick + 0.57 m ³ (0.74 yd ³) DC Bucket	22 700 (50,000)	47.3 (6.9)	23 300 (51,400)	36.8 (5.3)

All operating weights include a 90% fuel tank with 75 kg (165 lb) operator.

323 GX Hydraulic Excavator Specifications


Major Component Weights

	kg	lb
Base Machine without ROPS (with 4250 kg [9,370 lb] counterweight, upper frame, Medium undercarriage with rollers and two boom cylinders – does not include boom, stick, bucket, stick cylinder, bucket cylinder, tracks, 90% fuel tank and 75 kg [165 lb] operator).	14 700	32,410
Base Machine with ROPS (with 4250 kg [9,370 lb] counterweight, upper frame, Medium undercarriage with rollers and two boom cylinders – does not include boom, stick, bucket, stick cylinder, bucket cylinder, tracks, 90% fuel tank and 75 kg [165 lb] operator).	14 850	32,700
Base Machine without ROPS (with 4700 kg [10,360 lb] counterweight, upper frame, Long undercarriage with rollers and two boom cylinders – does not include boom, stick, bucket, stick cylinder, bucket cylinder, tracks, 90% fuel tank and 75 kg [165 lb] operator).	15 400	33,950
Base Machine with ROPS (with 4700 kg [10,360 lb] counterweight, upper frame, Long undercarriage with rollers and two boom cylinders – does not include boom, stick, bucket, stick cylinder, bucket cylinder, tracks, 90% fuel tank and 75 kg [165 lb] operator).	15 550	34,280
Track Shoes for Medium Undercarriage:		
600 mm (24") Width, 10 mm (0.39") Thick Triple Grouser Track Shoes	2700	5,960
790 mm (31") Width, 10 mm (0.39") Thick Triple Grouser Track Shoes with Step Extension	3210	7,080
Track Shoes for Long Undercarriage:		
600 mm (24") Width, 10 mm (0.39") Thick Triple Grouser Track Shoes	2820	6,210
790 mm (31") Width, 10 mm (0.39") Thick Triple Grouser Track Shoes with Step Extension	3350	7,390
Two Boom Cylinders	360	800
Weight of 90% Fuel Tank and 75 kg (165 lb) Operator	380	840
Counterweights:		
4250 kg (9,370 lb) Counterweight	4250	9,370
4250 kg (9,370 lb) Counterweight	4700	10,360
Booms (including lines, pins, stick cylinder):		
5.7 m (18'8") Reach Boom	1690	3,720
5.7 m (18'8") HD Reach Boom	1910	4,210
8.85 m (29") Super Long Reach Boom	2280	5,030
High Pressure (HP) Tool Control Lines	80	180
Sticks (including lines, pins, bucket cylinder, bucket linkage):		
R2.5B1 (8'2") Reach Stick	1010	2,230
R2.9B1 (9'6") Reach Stick	1060	2,340
R2.9B1 (9'6") HD Reach Stick	1180	2,600
6.28A (20'7") Super Long Reach Stick	1300	2,870
HP Tool Control Lines	50	110
Buckets (without linkage, with tips and side cutters):		
1.19 m³ (1.56 yd³) GD with Advansys Tips	890	1,970
1.2 m³ (1.57 yd³) GD with J-Tips	870	1,930
1.3 m³ (1.70 yd³) GD with J-Tips	890	2,000
1.3 m³ (1.70 yd³) HD with J-Tips	980	2,160
1.3 m³ (1.70 yd³) HD with J-Tips	1070	2,360
1.43 m³ (1.87 yd³) GD with J-Tips	960	2,110
0.53 m³ (0.69 yd³) GD with J-Tips	410	910
0.57 m³ (0.74 yd³) DC with J-Tips	390	850

323 GX Hydraulic Excavator Specifications

Dimensions

All dimensions are approximate and may vary depending on bucket selection.




Boom Option		Reach Boom 5.7 m (18'8")			
Stick Options		Reach Stick			
		R2.5B1 (8'2")		R2.9B1 (9'6")	
Undercarriage Type		Medium		Medium	
1 Machine Height:					
Top of Cab Height		2980 mm	9'9"	2980 mm	9'9"
Top of OPG Height (non-ROPS)		3100 mm	10'2"	3100 mm	10'2"
Top of OPG Height (ROPS)		3120 mm	10'3"	3120 mm	10'3"
Handrail Height		3030 mm	9'11"	3030 mm	9'11"
With Boom/Stick/Bucket Installed		3130 mm	10'3"	3130 mm	10'3"
With Boom/Stick Installed		3060 mm	10'0"	3060 mm	10'0"
With Boom Installed		3030 mm	9'11"	3030 mm	9'11"
2 Machine Length:					
With Boom/Stick/Bucket Installed		9590 mm	31'6"	9520 mm	31'3"
With Boom/Stick Installed		9560 mm	31'4"	9510 mm	31'2"
With Boom Installed		8500 mm	27'11"	8500 mm	27'11"
3 Upperframe Width		2740 mm	9'0"	2740 mm	9'0"
4 Tail Swing Radius		2830 mm	9'3"	2830 mm	9'3"
5 Counterweight Clearance		1060 mm	3'6"	1050 mm	3'5"
6 Ground Clearance		460 mm	1'6"	470 mm	1'6"
7 Track Length – Length to Center of Rollers		3450 mm	11'4"	3450 mm	11'4"
8 Track Length – Crawler Overall Length		4250 mm	13'11"	4250 mm	13'11"
9 Track Gauge		2380 mm	7'10"	2380 mm	7'10"
10 Undercarriage Width:					
600 mm (24") Shoes		2980 mm	9'9"	2980 mm	9'9"
790 mm (31") Shoes		3170 mm	10'5"	3170 mm	10'5"
Bucket Type		GD		GD	
Bucket Capacity		1.30 m³	1.70 yd³	1.20 m³	1.57 yd³
Bucket Tip Radius		1522 mm	5'0"	1572 mm	5'2"

(continued on next page)

323 GX Hydraulic Excavator Specifications

Dimensions (continued)

All dimensions are approximate and may vary depending on bucket selection.




Boom Option	HD Reach Boom 5.7 m (18'8")				Super Long Reach Boom 8.85 m (29'0")	
Stick Options	Reach Stick R2.5B1 (8'2")		HD Reach Stick R2.9B1 (9'6")		Super Long Reach Stick 6.28A (20'7")	
Undercarriage Type	Long		Long		Long	
1 Machine Height:						
Top of Cab Height	2980 mm	9'9"	2980 mm	9'9"	2980 mm	9'9"
Top of OPG Height (non-ROPS)	3100 mm	10'2"	3100 mm	10'2"	3100 mm	10'2"
Top of OPG Height (ROPS)	3120 mm	10'3"	3120 mm	10'3"	3120 mm	10'3"
Handrail Height	3030 mm	9'11"	3030 mm	9'11"	3030 mm	9'11"
With Boom/Stick/Bucket Installed	3130 mm	10'3"	3130 mm	10'3"	3180 mm	10'5"
With Boom/Stick Installed	3060 mm	10'0"	3060 mm	10'0"	3100 mm	10'2"
With Boom Installed	3030 mm	9'11"	3030 mm	9'11"	2670 mm	8'9"
2 Machine Length:						
With Boom/Stick/Bucket Installed	9590 mm	31'6"	9520 mm	31'3"	12 790 mm	42'0"
With Boom/Stick Installed	9560 mm	31'4"	9510 mm	31'2"	12 810 mm	42'0"
With Boom Installed	8500 mm	27'11"	8500 mm	27'11"	11 750 mm	38'7"
3 Upperframe Width	2740 mm	9'0"	2740 mm	9'0"	2740 mm	9'0"
4 Tail Swing Radius	2830 mm	9'3"	2830 mm	9'3"	2830 mm	9'3"
5 Counterweight Clearance	1060 mm	3'6"	1060 mm	3'6"	1060 mm	3'6"
6 Ground Clearance	460 mm	1'6"	460 mm	1'6"	460 mm	1'6"
7 Track Length – Length to Center of Rollers	3650 mm	12'0"	3650 mm	12'0"	3650 mm	12'0"
8 Track Length – Crawler Overall Length	4450 mm	14'7"	4450 mm	14'7"	4450 mm	14'7"
9 Track Gauge	2380 mm	7'10"	2380 mm	7'10"	2380 mm	7'10"
10 Undercarriage Width:						
600 mm (24") Shoes	2980 mm	9'9"	2980 mm	9'9"	2980 mm	9'9"
790 mm (31") Shoes	3170 mm	10'5"	3170 mm	10'5"	3170 mm	10'5"
Bucket Type	GD		GD		DC	
Bucket Capacity	1.30 m³	1.70 yd³	1.43 m³	1.87 yd³	0.57 m³	0.75 yd³
Bucket Tip Radius	1522 mm	5'0"	1568 mm	5'2"	1068 mm	3'6"

323 GX Hydraulic Excavator Specifications

Working Ranges

All dimensions are approximate and may vary depending on bucket selection.





Boom Option		Reach Boom 5.7 m (18'8")			
Stick Option		Reach Stick			
		R2.5B1 (8'2")		R2.9B1 (9'6")	
Undercarriage Type		Medium		Medium	
1 Maximum Digging Depth		6290 mm	20'8"	6710 mm	22'0"
2 Maximum Reach at Ground Line		9460 mm	31'0"	9860 mm	32'4"
3 Maximum Cutting Height		9270 mm	30'5"	9470 mm	31'1"
4 Maximum Loading Height		6300 mm	20'8"	6500 mm	21'4"
5 Minimum Loading Height		2600 mm	8'6"	2180 mm	7'2"
6 Maximum Depth Cut for 2440 mm (8'0") Level Bottom		6100 mm	20'0"	6020 mm	19'9"
7 Maximum Vertical Wall Digging Depth		5840 mm	19'2"	5740 mm	18'10"
Minimum Working Equipment Radius		3700 mm	12'2"	3650 mm	12'0"
Bucket Digging Force (ISO)		142 kN	31,923 lbf	140 kN	31,428 lbf
Stick Digging Force (ISO)		119 kN	26,752 lbf	107 kN	23,942 lbf
Bucket Type		GD		GD	
Bucket Capacity		1.30 m ³	1.70 yd ³	1.20 m ³	1.57 yd ³
Bucket Tip Radius		1522 mm	5'0"	1572 mm	5'2"

323 GX Hydraulic Excavator Specifications

Working Ranges

All dimensions are approximate and may vary depending on bucket selection.





Boom Option	HD Reach Boom 5.7 m (18'8")				Super Long Reach Boom 8.85 m (29'0")	
Stick Option	Reach Stick R2.5B1 (8'2")		HD Reach Stick R2.9B1 (9'6")		Super Long Reach Stick 6.28A (20'7")	
Undercarriage Type	Long		Long		Long	
1 Maximum Digging Depth	6290 mm	20'8"	6710 mm	22'0"	11 530 mm	37'10"
2 Maximum Reach at Ground Line	9460 mm	31'0"	9860 mm	32'4"	15 720 mm	51'6"
3 Maximum Cutting Height	9270 mm	30'5"	9460 mm	31'0"	13 550 mm	44'5"
4 Maximum Loading Height	6300 mm	20'8"	6500 mm	21'4"	11 450 mm	37'7"
5 Minimum Loading Height	2600 mm	8'6"	2180 mm	7'2"	2250 mm	7'5"
6 Maximum Depth Cut for 2440 mm (8'0") Level Bottom	6100 mm	20'0"	6020 mm	19'9"	4850 mm	15'11"
7 Maximum Vertical Wall Digging Depth	5840 mm	19'2"	5710 mm	18'9"	11 040 mm	36'3"
Minimum Working Equipment Radius	3700 mm	12'2"	3650 mm	12'0"	5070 mm	16'8"
Bucket Digging Force (ISO)	142 kN	31,923 lbf	141 kN	31,698 lbf	62 kN	13,848 lbf
Stick Digging Force (ISO)	119 kN	26,752 lbf	107 kN	24,055 lbf	49 kN	10,971 lbf
Bucket Type	GD		GD		DC	
Bucket Capacity	1.30 m ³	1.70 yd ³	1.43 m ³	1.87 yd ³	0.57 m ³	0.75 yd ³
Bucket Tip Radius	1522 mm	5'0"	1568 mm	5'2"	1068 mm	3'6"

323 GX Hydraulic Excavator Specifications

Reach Boom Lift Capacities – Counterweight: 4250 kg (9,370 lb) – without Bucket

Medium Undercarriage



		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				mm ft/in
7500 mm 25'0"	kg lb									*4700 *10,500	*4700 *10,500	5610 17'97"
6000 mm 20'0"	kg lb					*5350 *11,750	5350 11,450			*4350 *9,550	4300 *9,550	6830 22'22"
4500 mm 15'0"	kg lb			*6750 *14,550	*6750 *14,550	*5800 *12,600	5200 11,150	*4800 3650		*4250 *9,300	3600 8,000	7570 24'75"
3000 mm 10'0"	kg lb			*8500 *18,250	7500 16,200	*6550 *14,200	4950 10,700	5150 11,050	3600 7,700	*4350 *9,550	3300 7,200	7960 26'09"
1500 mm 5'0"	kg lb			*10 000 *21,600	7050 15,200	7000 15,050	4750 10,250	5050 10,850	3500 7,500	4550 10,000	3150 6,950	8050 26'41"
0 mm 0'0"	kg lb			10 650 22,850	6850 14,750	6850 14,700	4600 9,950	5000 10,700	3450 7,350	4650 10,250	3250 7,100	7850 25'76"
-1500 mm -5'0"	kg lb	*11 350 *25,850	*11 350 *25,850	*10 550 22,750	6800 14,650	6800 14,600	4550 9,850			5100 11,300	3500 7,750	7350 24'06"
-3000 mm -10'0"	kg lb	*13 200 *28,600	*13 200 *28,600	*9600 *20,650	6900 14,900	6850 14,800	4650 10,000			6200 13,800	4250 9,400	6450 21'05"
-4500 mm -15'0"	kg lb			*7100 *14,900	*7100 *14,900					*6200 *13,550	6200 13,550	4960 15'97"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.

Lift capacity stays with $\pm 5\%$ for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

Reach Boom Lift Capacities – Counterweight: 4250 kg (9,370 lb) – without Bucket

Medium Undercarriage

2.5 m (9'2") 5.7 m (18'8")

R2.5B1

790 mm (31") Triple Grouser Shoes

2380 mm (7'10")

3450 mm (11'4")

4250 mm (13'11")

		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				mm ft/in
												
7500 mm 25'0"	kg lb									*4700 *10,500	*4700 *10,500	5610 17'97"
6000 mm 20'0"	kg lb					*5350 *11,750	*5350 11,650			*4350 *9,550	*4350 *9,550	6830 22'22"
4500 mm 15'0"	kg lb			*6750 *14,550	*6750 *14,550	*5800 *12,600	5300 11,400	*4800	3750	*4250 *9,300	3700 8,150	7570 24'75"
3000 mm 10'0"	kg lb			*8500 *18,250	7650 16,500	*6550 *14,200	5100 10,950	5250 11,350	3650 7,900	*4350 *9,550	3350 7,400	7960 26'09"
1500 mm 5'0"	kg lb			*10 000 *21,600	7200 15,550	7150 15,400	4850 10,450	5150 11,100	3600 7,700	*4650 *10,200	3250 7,100	8050 26'41"
0 mm 0'0"	kg lb			*10 700 *23,100	7000 15,100	7000 15,050	4750 10,150	5100 10,950	3500 7,550	4800 10,550	3300 7,250	7850 25'76"
-1500 mm -5'0"	kg lb	*11 350 *25,850	*11 350 *25,850	*10 550 *22,800	7000 15,000	6950 14,950	4700 10,050			5250 11,550	3600 7,950	7350 24'06"
-3000 mm -10'0"	kg lb	*13 200 *28,600	*13 200 *28,600	*9600 *20,650	7050 15,200	7050 *15,100	4750 10,250			*6350 *13,950	4350 9,600	6450 21'05"
-4500 mm -15'0"	kg lb			*7100 *14,900	*7100 *14,900					*6200 *13,550	*6200 *13,550	4960 15'97"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.



Lift capacity stays with ±5% for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

Reach Boom Lift Capacities – Counterweight: 4250 kg (9,370 lb) – without Bucket

Medium Undercarriage



		1500 mm/5'0"		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				
														mm ft/in
7500 mm 25'0"	kg lb							*4550	*4550			*3900 *8,650	*3900 *8,650	6160 19'9"
6000 mm 20'0"	kg lb							*4950 *10,800	*4950 *10,800			*3600 *7,950	*3600 *7,950	7290 23'9"
4500 mm 15'0"	kg lb							*5450 *11,800	5250 11,250	*5100 *11,150	3700 7,900	*3550 *7,750	3350 7,350	7990 26'1"
3000 mm 10'0"	kg lb					*7950 *17,100	7600 16,400	*6250 *13,500	5000 10,750	5150 11,100	3600 7,750	*3600 *7,950	3050 6,700	8350 27'5"
1500 mm 5'0"	kg lb					*9600 *20,700	7150 15,350	7000 15,100	4750 10,250	5050 10,850	3500 7500	*3850 *8,450	2950 6,450	8440 27'8"
0 mm 0'0"	kg lb			*6250 *14,300	*6250 *14,300	*10 500 *22,750	6850 14,750	6850 14,700	4600 9,900	4950 10,650	3400 7300	*4250 *9,350	3000 6,550	8250 27'1"
-1500 mm -5'0"	kg lb	*6650 *14,900	*6650 *14,900	*10 800 *24,450	*10 800 *24,450	10 550 22,650	6800 14,550	6750 14,500	4550 9,750	4950 10,600	3400 7,250	4700 10,350	3250 7,100	7770 25'6"
-3000 mm -10'0"	kg lb	*11 450 *25,650	*11 450 *25,650	*14 050 *30,450	13 200 28,300	*9950 *21,450	6850 14,700	6800 14,600	4550 9,850			5550 12,300	3800 8,400	6940 22'8"
-4500 mm -15'0"	kg lb			*11 200 *23,950	*11 200 *23,950	*8050 *17,100	7050 15,150					*6100 *13,350	5250 11,750	5580 18'0"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.

Lift capacity stays with $\pm 5\%$ for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

Reach Boom Lift Capacities – Counterweight: 4250 kg (9,370 lb) – without Bucket

Medium Undercarriage

2.9 m (9'6") 5.7 m (18'8")

R2.9B1

790 mm (31") Triple Grouser Shoes

2380 mm (7'10")

3450 mm (11'4")

4250 mm (13'11")

		1500 mm/5'0"		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				mm ft/in
														
7500 mm 25'0"	kg lb							*4550	*4550			*3900 *8,650	*3900 *8,650	6160 19'9"
6000 mm 20'0"	kg lb							*4950 *10,800	*4950 *10,800			*3600 *7,950	*3600 *7,950	7290 23'9"
4500 mm 15'0"	kg lb							5400 *11,800	5350 11,500	*5100 *11,500	3800 8,100	*3550 *7,750	3400 7,500	7990 26'1"
3000 mm 10'0"	kg lb					*7950 *17,100	7750 16,750	*6250 *13,500	5100 11,000	5300 11,350	3700 7,900	*3600 *7,950	3100 6,850	8350 27'5"
1500 mm 5'0"	kg lb					*9600 *20,700	7300 15,700	*7050 *15,300	4900 10,500	5150 11,100	3550 7,650	*3850 *8,450	3000 6,600	8440 27'8"
0 mm 0'0"	kg lb			*6250 *14,300	*6250 *14,300	*10 500 *22,750	7000 15,100	7000 15,050	4700 10,150	5100 10,900	3500 7,500	*4250 *9,350	3050 6,700	8250 27'1"
-1500 mm -5'0"	kg lb	*6650 *14,900	*6650 *14,900	*10 800 *24,450	*10 800 *24,450	*10 600 *23,000	6950 14,900	6900 14,850	4650 10,000	5050 10,850	3450 7,450	4800 10,600	3300 7,300	7770 25'6"
-3000 mm -10'0"	kg lb	*11 450 *25,650	*11 450 *25,650	*14 050 *30,450	13 500 28,900	*9950 *21,450	7000 15,050	6950 14,950	4650 10,050			5700 12,600	3900 8,600	6940 22'8"
-4500 mm -15'0"	kg lb			*11 200 *23,950	*11 200 *23,950	*8050 *17,100	7200 15,500					*6100 *13,350	5350 12,050	5580 18'0"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with ±5% for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

HD Reach Boom Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				mm ft/in
												
7500 mm 25'0"	kg lb									*4700 *10,500	*4700 *10,500	5610 17'97"
6000 mm 20'0"	kg lb					*5300 *11,650	*5300 *11,650			*4350 *9,550	*4350 *9,550	6830 22'22"
4500 mm 15'0"	kg lb			*6700 *14,450	*6700 *14,450	*5750 *12,500	5600 12,000	*4800 3950		*4250 *9,300	3900 8,600	7570 24'75"
3000 mm 10'0"	kg lb			*8400 *18,100	8050 17,400	*6500 *14,050	5350 11,500	*5650 *12,250	3850 8,300	*4350 *9,550	3550 7,750	7960 26'09"
1500 mm 5'0"	kg lb			*9900 *21,350	7600 16,350	*7250 *15,700	5100 11,000	5800 12,500	3750 8,100	*4650 *10,200	3400 7,500	8050 26'41"
0 mm 0'0"	kg lb			*10 550 *22,850	7350 15,850	*7700 *16,700	4950 10,700	5750 12,300	3700 7,950	*5200 *11,400	3450 7,650	7850 25'76"
-1500 mm -5'0"	kg lb	*11 350 *25,850	*11 350 *25,850	*10 400 *22,550	7350 15,750	*7750 *16,700	4900 10,600			5900 13,000	3800 8,350	7350 24'06"
-3000 mm -10'0"	kg lb	*13 000 *28,200	*13 000 *28,200	*9450 *20,400	7400 15,950	*7000 *14,950	5000 10,750			*6250 *13,750	4550 10,100	6450 21'05"
-4500 mm -15'0"	kg lb			*7000 *14,700	*7000 *14,700					*6100 *13,350	*6100 *13,350	4960 15'97"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with $\pm 5\%$ for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

HD Reach Boom Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				mm ft/in
												
7500 mm 25'0"	kg lb									*4700 *10,500	*4700 *10,500	5610 17'97"
6000 mm 20'0"	kg lb					*5300 *11,650	*5300 *11,650			*4350 *9,550	*4350 *9,550	6830 22'22"
4500 mm 15'0"	kg lb			*6700 *14,450	*6700 *14,450	*5750 *12,500	5700 12,250	*4800 4050		*4250 *9,300	3950 8,750	7570 24'75"
3000 mm 10'0"	kg lb			*8400 *18,100	8200 17,750	*6500 *14,050	5450 11,750	*5650 *12,250	3950 8,500	*4350 *9,550	3600 7,950	7960 26'09"
1500 mm 5'0"	kg lb			*9900 *21,350	7750 16,700	*7250 *15,700	5200 11,250	5950 12,750	3850 8,250	*4650 *10,200	3500 7,650	8050 26'41"
0 mm 0'0"	kg lb			10550 *22,850	7500 16,200	*7700 *16,700	5050 10,900	5850 12,600	3750 8,100	*5200 *11,400	3550 7,800	7850 25'76"
-1500 mm -5'0"	kg lb	*11 350 *25,850	*11 350 *25,850	*10 400 *22,550	7500 16,100	*7750 *16,700	5000 10,800			6050 13,300	3850 8,500	7350 24'06"
-3000 mm -10'0"	kg lb	*13 000 *28,200	*13 000 *28,200	*9450 *20,400	7600 16,300	*7000 *14,950	5100 11,000			*6250 *13,750	4650 10,300	6450 21'05"
-4500 mm -15'0"	kg lb			*7000 *14,700	*7000 *14,700					*6100 *13,350	*6100 *13,350	4960 15'97"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with ±5% for all available track shoes.


Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

HD Reach Boom Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		1500 mm/5'0"		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				
														mm ft/in
7500 mm 25'0"	kg lb							*4500 *4500				*3850 *8,550	*3850 *8,550	6160 19'82"
6000 mm 20'0"	kg lb							*4850 *10,600	*4850 *10,600			*3550 *7,850	*3550 *7,850	7290 23'73"
4500 mm 15'0"	kg lb							*5300 *11,550	*5300 *11,550	*4950 *10,900	3900 8,400	*3500 *7,700	*3500 *7,700	7990 26'12"
3000 mm 10'0"	kg lb					*7800 *16,750	*7800 *16,750	*6100 *13,200	5300 11,450	*5300 *11,550	3800 8,200	*3600 *7,850	3200 7,100	8350 27'39"
1500 mm 5'0"	kg lb					*9400 *20,250	7550 16,300	*6900 *14,950	5050 10,900	*5700 12,350	3700 7,900	*3800 *8,350	3100 6,800	8440 27'7"
0 mm 0'0"	kg lb			*6200 *14,250	*6200 *14,250	*10 300 *22,250	7250 15,600	*7500 *16,200	4850 10,500	5650 12,100	3600 7,750	*4200 *9,250	3150 6,950	8250 27'1"
-1500 mm -5'0"	kg lb	*6650 *14,800	*6650 *14,800	*10 750 *24,400	*10 750 *24,400	*10 400 *22,450	7150 15,400	*7650 *16,550	4800 10,300	5600 12,050	3550 7,650	*4950 *10,950	3400 7,500	7770 25'47"
-3000 mm -10'0"	kg lb	*11 400 *25,550	*11 400 *25,550	*13 750 *29,750	13 750 29,750	*9700 *20,950	7250 15,550	*7200 *15,450	4850 10,400			*5850 *12,900	4000 8,850	6940 22'64"
-4500 mm -15'0"	kg lb			*10 900 *23,300	*10 900 *23,300	*7850 *16,650	7450 16,050					*5900 *13,000	5550 12,450	5580 18'0"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with $\pm 5\%$ for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

HD Reach Boom Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		1500 mm/5'0"		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				mm ft/in
														
7500 mm 25'0"	kg lb							*4500	*4500			*3850 *8,550	*3850 *8,550	6160 19'82"
6000 mm 20'0"	kg lb							*4850 *10,600	*4850 *10,600			*3550 *7,850	*3550 *7,850	7290 23'73"
4500 mm 15'0"	kg lb							*5300 *11,550	*5300 *11,550	*4950 *10,900	4000 8,600	*3500 *7,700	*3500 *7,700	7990 26'12"
3000 mm 10'0"	kg lb					*7800 *16,750	*7800 *16,750	*6100 *13,200	5400 11,650	*5300 *11,550	3900 8,350	*3600 *7,850	3300 7,250	8350 27'39"
1500 mm 5'0"	kg lb					*9400 *20,250	7700 16,650	*6900 *14,950	5150 11,100	*5700 *12,350	3750 8,100	*3800 *8,350	3150 6,950	8440 27'7"
0 mm 0'0"	kg lb			*6200 *14,250	*6200 *14,250	*10 300 *22,250	7400 15,950	*7500 *16,200	5000 10,700	5750 12,400	3700 7,900	*4200 *9,250	3250 7,100	8250 27'1"
-1500 mm -5'0"	kg lb	*6650 *14,800	*6650 *14,800	*10 750 *24,400	*10 750 *24,400	*10 400 *22,450	7350 15,750	*7650 *16,550	4900 10,550	5750 12,350	3650 7850	*4950 *10,950	3500 7,650	7770 25'47"
-3000 mm -10'0"	kg lb	*11 400 *25,550	*11 400 *25,550	*13 750 *29,750	13 750 29,750	*9700 *20,950	7400 15,900	*7200 *15,450	4950 10,650			*5850 *12,900	4100 9,050	6940 22'64"
-4500 mm -15'0"	kg lb			*10 900 *23,300	*10 900 *23,300	*7850 *16,650	7600 16,400					*5900 *13,000	5650 12,750	5580 18'0"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with $\pm 5\%$ for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

SLR Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		1500 mm/5'0"		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				
														mm ft/in
12 000 mm 40'0"	kg lb											*1450 *3,200	*1450 *3,200	10 360 33'35"
10 500 mm 35'0"	kg lb											*1350 *2,950	*1350 *2,950	11 670 37'86"
9000 mm 30'0"	kg lb											*1300 *2,850	*1300 *2,850	12 660 41'27"
7500 mm 25'0"	kg lb											*1250 *2,800	*1250 *2,800	13 420 43'84"
6000 mm 20'0"	kg lb											*1250 *2,750	*1250 *2,750	13 970 45'73"
4500 mm 15'0"	kg lb											*1300 *2,800	1250 2,700	14 340 47'0"
3000 mm 10'0"	kg lb			*4600 *11,600	*4600 *11,600	*6050 *12,950	6050 *12,950	*4450 *9,600	*4450 *9,600	*3600 *7,800	*3600 *7,800	*1300 *2,900	1150 2,500	14 550 47'71"
1500 mm 5'0"	kg lb					*6700 *15850	6450 13950	*5250 *11,300	4450 9,600	*4100 *8,850	3300 7,100	*1400 *3,000	1100 2,400	14 600 47'89"
0 mm 0'0"	kg lb			*2000 *4,550	*2000 *4,550	*4650 *10650	*4650 *10,650	*5900 *12,700	4000 8,650	*4550 *9,800	3000 6,450	*1450 *3,200	1100 2,400	14 490 47'53"
-1500 mm -5'0"	kg lb	*2100 *4,600	*2100 *4,600	*2700 *6,100	*2700 *6,100	*4650 *10,500	*4650 *10,500	*6250 *13,550	3750 8,050	4800 10,350	2800 6,000	*1550 *3,450	1100 2,400	14 220 46'64"
-3000 mm -10'0"	kg lb	*2850 *6,350	*2850 *6,350	*3550 *7,900	*3550 *7,900	*5200 *11,750	*5200 11,750	*6400 13,800	3600 7,750	4650 10,050	2700 5,750	*1750 *3,800	1150 2,500	13 790 45'18"
-4500 mm -15'0"	kg lb	*3700 *8,200	*3700 *8,200	*4400 *9,900	*4400 *9,900	*6050 *13,700	5400 11,650	*6400 13,700	3550 7,650	4600 9,900	2650 5,650	*1950 *4,300	1250 2,700	13 170 43'1"
-6000 mm -20'0"	kg lb	*4550 *10,150	*4550 *10,150	*5400 *12,150	*5400 *12,150	*7200 *16,350	5550 11,900	*6150 *13,200	3600 7,750	4650 9,950	2650 5,650	*2300 *5,100	1400 3,050	12 330 40'25"
-7500 mm -25'0"	kg lb	*5500 *12,300	*5500 *12,300	*6600 *14,800	*6600 *14,800	*7250 *15,650	5700 12,300	*5650 *12,150	3700 8,000	*4550 *9,750	2700 5,850	*2700 *5,950	1600 3,600	11 230 36'51"
-9000 mm -30'0"	kg lb			*7950 *17,450	*7950 *17,450	*6150 *13,050	6000 12,950	*4850 *10,300	3900 8,450	*3900 *8,250	2850 6,200	*2700 *5,900	2050 4,600	9780 31'55"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with ±5% for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

SLR Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		9000 mm/30'0"		10 500 mm/35'0"		12 000 mm/40'0"		13 500 mm/45'0"				
												mm ft/in
12 000 mm 40'0"	kg lb									*1450 *3,200	*1450 *3,200	10 360 33'35"
10 500 mm 35'0"	kg lb			*2200 *4,850	*2200 *4,850					*1350 *2,950	*1350 *2,950	11 670 37'86"
9000 mm 30'0"	kg lb			*2200 *4,800	*2200 *4,800	*2200 *4,200	1950 4,100			*1300 *2,850	*1300 *2,850	12 660 41'27"
7500 mm 25'0"	kg lb			*2250 *4,900	*2250 *4,900	*2200 *4,850	1950 4,100			*1250 *2,800	*1250 *2,800	13 420 43'84"
6000 mm 20'0"	kg lb			*2400 *5,200	*2400 5,200	*2300 *5,000	1900 4,000	*2100 *3,750	1450 3,050	*1250 *2,750	*1250 *2,750	13 970 45'73"
4500 mm 15'0"	kg lb	*2800 *6,050	*2800 *6,050	*2550 *5,550	2300 4,900	*2400 *5,250	1800 3,800	*2300 4,950	1400 3,000	*1300 *2,800	1250 2,700	14 340 47'0"
3000 mm 10'0"	kg lb	*3100 *6,750	2750 5,950	*2800 *6,000	2150 4,600	*2550 *5,500	1700 3,650	2250 4,800	1350 2,850	*1300 *2,900	1150 2,500	14 550 47'71"
1500 mm 5'0"	kg lb	*3450 *7,400	2550 5,450	*3000 *6,500	2000 4,300	2650 5,700	1600 3,400	2200 4,700	1300 2,750	*1400 *3,000	1100 2,400	14 600 47'89"
0 mm 0'0"	kg lb	*3700 *8,050	2350 5,050	3150 6,700	1900 4,000	2550 5,500	1500 3,250	2150 4,600	1250 2,650	*1450 *3,200	1100 2,400	14 490 47'53"
-1500 mm -5'0"	kg lb	3750 8,050	2200 4,700	3000 6,450	1750 3,800	2500 5,350	1450 3,100	2100 4,500	1200 2,550	*1550 *3,450	1100 2,400	14 220 46'64"
-3000 mm -10'0"	kg lb	3650 7,800	2100 4,500	2950 6,300	1700 3,650	2450 5,250	1400 3,000	2100 4,200	1200 2,500	*1750 *3,800	1150 2,500	13 790 45'18"
-4500 mm -15'0"	kg lb	3600 7,700	2050 4,400	2900 6,250	1650 3,550	2450 5,200	1400 2,950			*1950 *4,300	1250 2,700	13 170 43'1"
-6000 mm -20'0"	kg lb	3600 7,700	2050 4,400	2900 6,250	1700 3,600	2450 5,300	1400 3,050			*2300 *5,100	1400 3,050	12 330 40'25"
-7500 mm -25'0"	kg lb	3650 7,850	2100 4,550	3000 *6,400	1750 3,750					*2700 *5,950	1600 3,600	11 230 36'51"
-9000 mm -30'0"	kg lb	*3100 *6,500	2250 4900							*2700 *5,900	2050 4,600	9780 31'55"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with ±5% for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

SLR Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		1500 mm/5'0"		3000 mm/10'0"		4500 mm/15'0"		6000 mm/20'0"		7500 mm/25'0"				
														mm ft/in
12 000 mm 40'0"	kg lb											*1450 *3,200	*1450 *3,200	10 360 33'35"
10 500 mm 35'0"	kg lb											*1350 *2,950	*1350 *2,950	11 670 37'86"
9000 mm 30'0"	kg lb											*1300 *2,850	*1300 *2,850	12 660 41'27"
7500 mm 25'0"	kg lb											*1250 2800	*1250 *2,800	13 420 43'84"
6000 mm 20'0"	kg lb											*1250 *2,750	*1250 *2,750	13 970 45'73"
4500 mm 15'0"	kg lb											*1300 *2,800	1250 2,750	14 340 47'0"
3000 mm 10'0"	kg lb			*4600 *11,600	*4600 *11,600	*6050 *12,950	*6050 *12,950	*4450 *9,600	*4450 *9,600	*3600 *7,800	*3600 *7,800	*1300 *2,900	1200 2,600	14 550 47'71"
1500 mm 5'0"	kg lb					*6700 *15,850	6600 14,300	*5250 *11,300	4550 9,850	*4100 *8,850	3400 7,300	*1400 *3,000	1150 2,500	14 600 47'89"
0 mm 0'0"	kg lb			*2000 *4,550	*2000 *4,550	*4650 *10,650	*4650 *10,650	*5900 *12,700	4100 8,850	*4550 *9,800	3100 6,650	*1450 *3,200	1150 2,450	14 490 47'53"
-1500 mm -5'0"	kg lb	*2100 *4,600	*2100 *4,600	*2700 *6,100	*2700 *6,100	*4650 *10,500	*4650 *10,500	*6250 *13,550	3850 8,250	*4850 *10,450	2900 6,200	*1550 *3,450	1150 2,500	14 220 46'64"
-3000 mm -10'0"	kg lb	*2850 *6,350	*2850 *6,350	*3550 *7,900	*3550 *7,900	*5200 *11,750	*5200 11,750	*6400 *13,900	3700 7,950	4800 10,300	2750 5,950	*1750 *3,800	1200 2,600	13 790 45'18"
-4500 mm -15'0"	kg lb	*3700 *8,200	*3700 *8,200	*4400 *9,900	*4400 *9,900	*6050 *13,700	5550 12,000	*6400 *13,800	3650 7,900	4750 10,200	2700 5,800	*1950 *4,300	1300 2,800	13 170 43'1"
-6000 mm -20'0"	kg lb	*4550 *10,150	*4550 *10,150	*5400 *12,150	*5400 *12,150	*7200 *16,350	5700 12,250	*6150 *13,200	3700 8,000	4750 10,250	2700 5,850	*2300 *5,100	1400 3,150	12 330 40'25"
-7500 mm -25'0"	kg lb	*5500 *12,300	*5500 *12,300	*6600 *14,800	*6600 *14,800	*7250 *15,650	5900 12,650	*5650 *12,150	3850 8,250	*4550 *9,750	2800 6,000	*2700 *5,950	1650 3,700	11 230 36'51"
-9000 mm -30'0"	kg lb			*7950 *17,450	*7950 *17,450	*6150 *13,050	*6150 *13,050	*4850 *10,300	4000 8,650	*3900 *8,250	2950 6,350	*2700 *5,900	2100 4,750	9780 31'55"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.




Lift capacity stays with ±5% for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

SLR Lift Capacities – Counterweight: 4700 kg (10,360 lb) – without Bucket

Long Undercarriage



		9000 mm/30'0"		10 500 mm/35'0"		12 000 mm/40'0"		13 500 mm/45'0"				mm ft/in
												
12 000 mm 40'0"	kg lb									*1450 *3,200	*1450 *3,200	10 360 33'35"
10 500 mm 35'0"	kg lb			*2200 *4,850	*2200 *4,850					*1350 *2,950	*1350 *2,950	11 670 37'86"
9000 mm 30'0"	kg lb			*2200 *4,800	*2200 *4,800	*2200 *4,200	2000 *4,200			*1300 *2,850	*1300 *2,850	12 660 41'27"
7500 mm 25'0"	kg lb			*2250 *4,900	*2250 *4,900	*2200 *4,850	2000 4,200			*1250 2800	*1250 *2,800	13 420 43'84"
6000 mm 20'0"	kg lb			*2400 *5,200	*2400 *5,200	*2300 *5,000	1900 4,100	*2100 *3,750	1500 3,150	*1250 *2,750	*1250 *2,750	13 970 45'73"
4500 mm 15'0"	kg lb	*2800 *6,050	*2800 *6,050	*2550 *5,550	2350 5,050	*2400 *5,250	1850 3,950	*2300 *5,000	1450 3,050	*1300 *2,800	1250 2,750	14 340 47'0"
3000 mm 10'0"	kg lb	*3100 *6,750	2850 6,050	*2800 *6,000	2200 4,700	*2550 *5,500	1750 3,750	2300 4,950	1400 2,950	*1300 *2,900	1200 2,600	14 550 47'71"
1500 mm 5'0"	kg lb	*3450 *7,400	2600 5,600	*3000 *6,500	2050 4,400	*2700 *5,800	1650 3,550	2250 4,850	1350 2,850	*1400 *3,000	1150 2,500	14 600 47'89"
0 mm 0'0"	kg lb	*3700 *8,050	2400 5,200	*3200 6,900	1950 4,150	2650 5,650	1550 3,350	2200 4,700	1300 2,750	*1450 *3,200	1150 2,450	14 490 47'53"
-1500 mm -5'0"	kg lb	3850 8,250	2250 4,850	3100 6,650	1850 3,900	2550 5,500	1500 3,200	2150 4,650	1250 2,650	*1550 *3,450	1150 2,500	14 220 46'64"
-3000 mm -10'0"	kg lb	3750 8,000	2150 4,650	3000 6,500	1750 3,750	2500 5,400	1450 3,100	2150 *4,200	1200 2,600	*1750 *3,800	1200 2,600	13 790 45'18"
-4500 mm -15'0"	kg lb	3700 7,900	2100 4,550	3000 6,400	1700 3,700	2500 5,350	1450 3,050			*1950 *4,300	1300 2,800	13 170 43'1"
-6000 mm -20'0"	kg lb	3700 7,950	2150 4,550	3000 6,450	1750 3,700	2550 5,450	1450 3,150			*2300 *5,100	1400 3,150	12 330 40'25"
-7500 mm -25'0"	kg lb	*3750 *7,950	2200 4,700	*3050 *6,400	1800 3,900					*2700 *5,950	1650 3,700	11 230 36'51"
-9000 mm -30'0"	kg lb	*3100 *6,500	2300 5,050							*2700 *5,900	2100 4,750	9780 31'55"



ISO 10567:2007



*Indicates that the load is limited by hydraulic lifting capacity rather than tipping load. The above loads are in compliance with hydraulic excavator lift capacity standard ISO 10567:2007. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Weight of all lifting accessories must be deducted from the above lifting capacities. Lifting capacities are based on the machine standing on a firm, uniform supporting surface. The use of a work tool attachment point to handle/lift objects, could affect the machine lift performance.

Lift capacity stays with ±5% for all available track shoes.

Always refer to the appropriate Operation and Maintenance Manual for specific product information.

323 GX Hydraulic Excavator Specifications

Bucket Specifications and Compatibility

Undercarriage									Medium		Long		
Counterweight									4250 kg (9,370 lb)		4700 kg (10,360 lb)		
	Linkage	Width		Capacity		Weight		Fill	Reach Boom		HD Reach Boom		SLR Boom
		mm	in	m³	yd³	kg	lb	%	R2.5 m (8'2")	R2.9 m (9'6")	R2.5 m (8'2")	HD R2.9 m (9'6")	SLR 6.28 (20'7")
Pin-On (No Quick Coupler)													
General Duty	B	1250	49	1.20	1.57	879	1,938	100	●	⊙	●	⊙	
	B	1200	48	1.19	1.56	890	1,962	100	●	⊙	●	⊙	
	B	1300	51	1.30	1.70	809	1,784	100	⊙		●	⊙	
Heavy Duty	B	1300	51	1.30	1.70	979	2,158	100	⊙		●	⊙	
	B	1300	51	1.30	1.70	1070	2,359	100	⊙		⊙	⊖	
General Duty	B	1400	55	1.43	1.87	844	1,861	100	⊙		⊙	⊖	
	A	900	36	0.53	0.69	411	906	100					◇
Ditch Cleaning	A, 312	1200	48	0.57	0.74	386	851	100					◇
Maximum load with pin-on (payload + bucket)								kg	3341	3085	3611	3216	886
								lb	7,366	6,801	7,961	7,090	1,953

The above loads are in compliance with hydraulic excavator standard EN474-5:2006 + A3:2013, they do not exceed 87% of hydraulic lifting capacity or 75% of tipping capacity with front linkage fully extended at ground line with bucket curled.

Capacity based on ISO 7451:2007.

Bucket weight with General Duty tips.

Maximum Material Density:

- 2100 kg/m³ (3,500 lb/yd³)
- ⊙ 1800 kg/m³ (3,000 lb/yd³)
- ⊖ 1500 kg/m³ (2,500 lb/yd³)
- ◇ 900 kg/m³ (1,500 lb/yd³)

Caterpillar recommends using appropriate work tools to maximize the value customers receive from our products. Use of work tools, including buckets, which are outside of Caterpillar recommendations or specifications for weight, dimensions, flows, pressures, etc. may result in less-than-optimal performance, including but not limited to reductions in production, stability, reliability, and component durability. Improper use of a work tool resulting in sweeping, prying, twisting and/or catching of heavy loads will reduce the life of the boom and stick.

323 GX Hydraulic Excavator Specifications

Attachments Offering Guide – Africa, Middle East

Not all Attachments are available in all regions. Consult your Cat dealer for configurations available in your region.

☒ Match ☐ No Match

PIN-ON ATTACHMENTS

Undercarriage		Medium		Long	
Counterweight		4250 kg (9,370 lb)		4700 kg (10,360 lb)	
Boom Type		Reach		HD Reach	
Stick Length		R2.5 m (8'2")	R2.9 m (9'6")	R2.5 m (8'2")	HD R2.9 m (9'6")
Hydraulic Hammers	H120 GC	✓	✓	✓	✓
	H120 GC S	✓	✓	✓	✓
	H120 S	✓	✓	✓	✓
	H130 GC	✓	✓	✓	✓
	H130 GC S	✓	✓	✓	✓
	H130 S	✓	✓	✓	✓
Compactors (Vibratory Plate)	CVP110	✓	✓	✓	✓

CW-40s DEDICATED COUPLER ATTACHMENTS

Undercarriage		Medium		Long	
Counterweight		4250 kg (9,370 lb)		4700 kg (10,360 lb)	
Boom Type		Reach		HD Reach	
Stick Length		R2.5 m (8'2")	R2.9 m (9'6")	R2.5 m (8'2")	HD R2.9 m (9'6")
Hydraulic Hammers	H120 GC S	✓	✓	✓	✓
	H120 S	✓	✓	✓	✓
	H130 S	✓	✓	✓	✓
Compactors (Vibratory Plate)	CVP110	✓	✓	✓	✓

CW-40 DEDICATED COUPLER ATTACHMENTS

Undercarriage		Medium		Long	
Counterweight		4250 kg (9,370 lb)		4700 kg (10,360 lb)	
Boom Type		Reach		HD Reach	
Stick Length		R2.5 m (8'2")	R2.9 m (9'6")	R2.5 m (8'2")	HD R2.9 m (9'6")
Hydraulic Hammers	H120 GC	✓	✓	✓	✓
	H120 GC S	✓	✓	✓	✓
	H120 S	✓	✓	✓	✓
	H130 GC	✓	✓	✓	✓
	H130 GC S	✓	✓	✓	✓
	H130 S	✓	✓	✓	✓
Compactors (Vibratory Plate)	CVP110	✓	✓	✓	✓

323 GX Hydraulic Excavator Specifications

Attachments Offering Guide – Eurasia

Not all Attachments are available in all regions. Consult your Cat dealer for configurations available in your region.

☒ Match

PIN-ON ATTACHMENTS

Undercarriage		Medium
Counterweight		4250 kg (9,370 lb)
Boom Type		Reach
Stick Length		R2.9 m (9'6")
Hydraulic Hammers	H120 GC	✓
	H120 GC S	✓
	H120 S	✓
	H130 GC	✓
	H130 GC S	✓
	H130 S	✓
Compactors (Vibratory Plate)	CVP110	✓

CW-40s DEDICATED COUPLER ATTACHMENTS

Undercarriage		Medium
Counterweight		4250 kg (9,370 lb)
Boom Type		Reach
Stick Length		R2.9 m (9'6")
Hydraulic Hammers	H120 GC S	✓
	H120 S	✓
	H130 S	✓
Compactors (Vibratory Plate)	CVP110	✓

CW-40 DEDICATED COUPLER ATTACHMENTS

Undercarriage		Medium
Counterweight		4250 kg (9,370 lb)
Boom Type		Reach
Stick Length		R2.9 m (9'6")
Hydraulic Hammers	H120 GC	✓
	H120 GC S	✓
	H120 S	✓
	H130 GC	✓
	H130 GC S	✓
	H130 S	✓
Compactors (Vibratory Plate)	CVP110	✓

323 GX Hydraulic Excavator Specifications

Attachments Offering Guide – Sri Lanka

Not all Attachments are available in all regions. Consult your Cat dealer for configurations available in your region.



Match



No Match

PIN-ON ATTACHMENTS

Undercarriage		Medium	Long
Counterweight		4250 kg (9,370 lb)	4700 kg (10,360 lb)
Boom Type		Reach	HD Reach
Stick Length		R2.9 m (9'6")	HD R2.9 m (9'6")
Hydraulic Hammers	H120 GC	✓	✓
	H120 GC S	✓	✓
	H120 S	✓	✓
	H130 GC	✓	✓
	H130 GC S	✓	✓
	H130 S	✓	✓
Compactors (Vibratory Plate)	CVP110	✓	✓

323 GX Standard and Optional Equipment

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
BOOMS, STICKS AND LINKAGES			CAT TECHNOLOGY		
5.7 m (18'8") Reach boom		✓	VisionLink®	✓ ⁶	
5.7 m (18'8") HD Reach boom		✓ ¹	ELECTRICAL SYSTEM		
8.85 m (29") Super Long Reach boom		✓ ¹	Two 950 CCA maintenance-free batteries	✓	
2.5 m (8'2") Reach stick		✓	Electrical disconnect switch	✓	
2.9 m (9'6") Reach stick		✓	LED chassis and cab lights	✓	
2.9 m (9'6") HD Reach stick		✓ ¹	LED right-side boom light		✓
6.28 m (20'7") Super Long Reach stick		✓ ¹	LED left-side boom light	✓	
Bucket linkage with lifting eye, B1 type		✓ ²	ENGINE		
Bucket linkage without lifting eye, B1 type		✓ ³	Cat® C4.4 twin turbo diesel engine	✓ ⁷	
Bucket linkage with lifting eye, A type		✓ ⁴	Cat C7.1 single turbo diesel engine	✓ ⁸	
CAB			Two selectable modes: Power, Smart	✓	
OPG		✓	Up to 4500 m (14,764 ft) altitude capability with derate from 3000 m (9,842 ft)	✓	
ROPS		✓ ⁵	52° C (125° F) high-ambient cooling capability	✓	
Sound suppressed cab with viscous mounts	✓		-25° C (-13° F) cold start capability	✓	
High-resolution 203 mm (8") LCD touchscreen monitor	✓		Electric fuel priming pump	✓	
Mechanical-suspension seat with head rest and arm rest	✓		Direct drive fan	✓	
51 mm (2") orange seat belt	✓		Two-stage fuel filtration system with water separator and indicator	✓	
Auto bi-level air conditioner	✓		Sealed double-element air filter with pre-cleaner	✓	
Keyless push-to-start engine control	✓		HYDRAULIC SYSTEM		
Fixed left-side console	✓		Electronic main control valve, hammer ready	✓	
1-button joysticks	✓		Tandem type electronic main pump	✓	
3-button joysticks		✓	Boom and stick regeneration circuits	✓	
AM/FM Bluetooth® radio with USB/Auxiliary ports	✓		Automatic hydraulic oil warm up	✓	
Speakers (mounted on roof)	✓		Automatic two-speed travel	✓	
24V DC outlet	✓		Hammer lines		✓
Storage compartments	✓		Hammer return filter		✓
Cup holder	✓		High performance hydraulic return filter	✓	
70/30 tempered glass windshield	✓				
Rear window emergency exit	✓				
Openable steel hatch	✓				
LED dome light	✓				
Washable floor mat	✓				

(continued on next page)

¹Middle East only

²All regions except Kingdom of Saudi Arabia

³Kingdom of Saudi Arabia only

⁴Middle East only

⁵Mandatory in Kingdom of Saudi Arabia; Not available in Sri Lanka; Optional in other regions.

⁶Provides core telematics data to manage health, maintenance insights, and condition monitoring. Other plans available for more comprehensive data reporting. Consult your Cat dealer for details.

⁷Africa, Sri Lanka, Eurasia only

⁸Middle East only

323 GX Standard and Optional Equipment

Standard and Optional Equipment *(continued)*

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional		Standard	Optional
SAFETY AND SECURITY			UNDERCARRIAGE AND STRUCTURES		
Anti-skid plating with countersunk bolts	✓		Medium undercarriage		✓ ¹¹
Handrail and hand hold	✓		Long undercarriage		✓ ¹²
Lockable external tool/storage box	✓		600 mm (24") triple grouser track shoes		✓
Lockable disconnect switch	✓		790 mm (31") triple grouser track shoes		✓
Ground-level secondary engine shutoff switch	✓		Grease lubricated track links	✓	
Signaling/warning horn	✓		Center track guiding guard	✓	
Hydraulic lockout lever	✓		Bottom guards	✓	
Rear and right-side-view cameras		✓ ⁹	Travel motor guards	✓	
Right-side-view mirror	✓		OPG guard		✓
Right-hand edge mirror on cab		✓ ¹⁰	4250 kg (9,370 lb) counterweight		✓
Rearview camera		✓	4700 kg (10,360 lb) counterweight		✓ ¹
Swing alarm		✓	Tie-down points	✓	
Travel alarm		✓			
SERVICE AND MAINTENANCE					
Grouped engine oil and fuel filters	✓				
Scheduled Oil Sampling (S·O·S SM) sampling ports	✓				
Radiator screen		✓			

¹Middle East only

⁹Mandatory for Kingdom of Saudi Arabia; Not available in other regions.

¹⁰Mandatory in Kingdom of Saudi Arabia; Optional in other regions.

¹¹All regions except Middle East

¹²Standard Middle East; Optional Sri Lanka, Indonesia, Southeast Asia only

323 GX Attachments

Dealer Installed Kits and Attachments

Attachments may vary. Consult your Cat dealer for details.

GUARDS

- 6 mm (0.24") swivel guard
- Mesh guard full front (not compatible with cab light cover, rain protector)
- Mesh guard lower half front
- Operator Protective Guards

SERVICE PART

- Hammer floor pedal kit
- Grease gun holder

The following information applies to the machine at the time of final manufacture as configured for sale in the regions covered in this document. The content of this declaration is valid as of the date issued; however, content related to machine features and specifications are subject to change without notice. For additional information, please see the machine's Operation and Maintenance Manual.

For more information on sustainability in action and our progress, please visit <https://www.caterpillar.com/en/company/sustainability>.

Engine

- The Cat C4.4 and Cat C7.1 engines emit equivalent to U.S. EPA Tier 3 and EU Stage IIIA.
 - Cat engines are compatible with diesel fuel blended with the following lower-carbon intensity fuels** up to:
 - ✓ 100% biodiesel FAME (fatty acid methyl ester)*
 - ✓ 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels
- Refer to guidelines for successful application. Please consult your Cat dealer or "Caterpillar Machine Fluids Recommendations" (SEBU6250) for details.
- *For use of blends higher than 20% biodiesel, consult your Cat dealer.*
- **Tailpipe greenhouse gas emissions from lower-carbon intensity fuels are essentially the same as traditional fuels.*

Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a or R1234yf. See the label or instruction manual for identification of the gas.

If equipped with R134a (Global Warming Potential = 1430), the system contains 0.85 kg (1.9 lb) of refrigerant which has a CO₂ equivalent of 1.216 metric tonnes (1.34 tons).

Paint

- Based on best available knowledge, the maximum allowable concentration, measured in parts per million (PPM), of the following heavy metals in paint are:
 - Barium < 0.01%
 - Cadmium < 0.01%
 - Chromium < 0.01%
 - Lead < 0.01%

Sound Performance

ISO 6395:2008 (external)	103 dB(A)
ISO 6396:2008 (inside cab)	70 dB(A)

- Hearing protection may be needed when operating with an open operator station and cab (when not properly maintained or doors/windows open) for extended periods or in a noisy environment.

Oils and Fluids

- Caterpillar factory fills with ethylene glycol coolants. Cat Diesel Engine Antifreeze/Coolant (DEAC) and Cat Extended Life Coolant (ELC) can be recycled. Consult your Cat dealer for more information.
- Cat Bio HYDO™ Advanced is an EU Ecolabel approved biodegradable hydraulic oil.
- Additional fluids are likely to be present, please consult the Operations and Maintenance Manual or the Application and Installation guide for complete fluid recommendations and maintenance intervals.

Features and Technology

- The following features and technology may contribute to fuel savings and/or carbon reduction. Features may vary. Consult your Cat dealer for details.
 - Smart mode matches machine power to digging requirements automatically
 - Automatic Engine Control reduces engine speed when the machine is not under load to minimize fuel consumption
 - Enhanced filters and extended service intervals help decrease maintenance costs
 - The latest hydraulic oil filter provides longer life with a 3,000-hour replacement interval

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2025 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, VisionLink, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEXQ4201-01 (05-2025)
Replaces AEXQ4201-00
Build Number: 05F
(Afr-ME, Eurasia, Sri Lanka)

