



Cat[®] C2.2B

MARINE GENERATOR

Cat[®] C2.2B Marine Generator is designed for advanced functionality. This low-noise, intelligent, and future-ready genset can be sold independently or as part of Cat Marine product solutions. The flexible design ensures seamless installation and single-side servicing for easy maintenance. The Cat C2.2B allows for the integration of multiple power sources, from shore power to batteries, ensuring an uninterrupted power supply. It meets U.S. EPA Tier 3 emissions standards at an engine speed of 1800 rpm, delivering up to 26 KWe of power. The enclosure is 20% smaller compared to the C2.2, offering a more compact footprint without compromising performance.

FEATURES:

- Yachting focused sound enclosure for quiet operation
- Compact size to increase installation options
- Digital system controller for easy operation and interface
- Single side servicing for easy maintenance
- Designed for easy integration, the optional handed connection panel simplifies engine room plumbing and cuts install time.
- Smart communication ensures seamless connectivity with digital vessel control systems for efficient operations.

BENEFITS:

- Cat C2.2B flexible installation options give boatbuilders the freedom to optimize engine room layouts and enhance design efficiency.
- Seamlessly integrates multiple power sources, ensuring continuous power when switching between shore power, generators, and batteries, meaning fewer disruptions and more time on the water.
- Low operating and maintenance costs with excellent fuel economy.

Engine Specifications

Configuration	Inline 4, 4-Stroke Cycle Diesel
Emissions	U.S. EPA Tier 3
Rated Engine Speed	1500 rpm / 1800 rpm
Displacement	2.2 L (135 in ³)
Aspiration	Naturally Aspirated/Turbocharged
Governor	Electronic Isochronous
Flywheel Housing	SAE No. 04
Bore × Stroke	84 mm × 100 mm / 3.31 in × 3.94 in
Refill Capacity	Lube Oil System with Oil Filter Change: 10.6 L (2.8 gal)
Oil Change Interval	500 hours
Rotation (from flywheel end)	Counterclockwise
Cooling	Heat Exchanger Cooled

Cat C2.2B Marine Generator

Ratings and Fuel Consumption

Generator Sets

ekW@.8pf	PC eKW*	kVA	Hz	RPM	U.S. gal/h	g/bkW-h	IMO	U.S. EPA	EU	China
14.5	16.0	18.75	50	1500	1.37	248.8	NST	NC	NST	NC
19.1	21.0	25.0	50	1500	1.88	242.8	NST	NC	NST	NC
17.3	19.0	22.5	60	1800	1.63	242.9	NST	T3C	NST	NC
23.6	26.0	31.25	60	1800	2.24	241.0	NST	T3C	NST	NC

*PC rating based on ISO 8528-1 prime power inclusive of +10% capacity. Operating unlimited annual hours with a load factor <60%. No Overload is permitted.

Rating Definition Generator Sets and Auxiliary Engines:

All Cat Marine auxiliary engines and generator sets are rated for prime power for continuous electric service according to ISO 8528-1.


Hours per year: unlimited

Load Factor: < 70%

Overload Capacity: +10% (Maximum of 1 hour in 12, maximum of 25 hours per year.

Engine Dimensions and Weight

All dimensions are approximate.



A Length	1100 mm	43.3 in	C Width	628 mm	24.7 in
B Height	740 mm	29.1 in	Dry Weight	480 kg	1036 lb

Standard and Optional Equipment

Standard Equipment

- Sound Attenuation Enclosure
- Digital control panel
- Self-priming fuel lift pump
- 12 or 24 volt system
- Single sided service points
- Water-cooled exhaust manifold
- Wet exhaust
- Single or brushless generator
- Anti-vibration mounts

OPTIONAL EQUIPMENT

- Double wall fuel injection lines
- Vessel connection Panel
- Siphon break
- AC circuit breaker
- Load share control panel
- Load share junction box

Cat C2.2B Marine Generator

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2025 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, VisionLink™, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

LEHM22772-01 (08-2025)
Replaces LEHM22772-00
(Regions)

