

SAE J517 100 R7

Hose dimensions according to **ISO 3949 R7**

Liner

Thermoplastic elastomer

Reinforcement

Reinforcement
One braid of synthetic fiber

Cover

Orange polyurethane nonconductive cover

Application

Medium pressure hydraulic lines

Temperature

Hydraulics Oils: from -40°C to 100°C (from -40°F to 212°F)

Water Glycol Hydraulic Fluids: up to 70°C (up to 158°F)

Water: from 0°C to 70°C (from 32°F to 158°F)

Air: up to 70°C (up to 158°F)

Sottostrato

Elastomero termoplastico

Rinforzo

Una treccia in fibra sintetica

Copertura

Copertura in poliuretano non-conduttiva arancio

Applicazioni

Linee idrauliche a media pressione

Temperatura

Olii idraulici: da -40°C a 100°C (da -40°F a 212°F)

Acqua, fluidi idraulici acqua e glicole: fino a 70°C (fino a 158°F)

Acqua: da 0°C a 70°C (da 32°F a 158°F)

Aria: fino a 70°C (fino a 158°F)

[illegible]

This hose fits with SERIES T couplings

ANCHOR NON CONDUCTIVE ISO 3949 R7 / SAE 100 R7 - */*" WP ** MPa (*** bar)**