

SAE J517 100 R19



Oil resistant synthetic rubber

One or more braids of high tensile steel wire

Oil and weather resistant black synthetic rubber MSHA approved










High pressure hydraulic lines

Hydraulics Oils: from -40°C to 100°C (from -40°F to 212°F)

Water Glycol Hydraulic Fluids: from 0°C to 66°C (from 32°F to 151°F)

Water: from 0°C to 66°C (from 32°F to 151°F)

Air:

														
	DN	dash size	inch	mm	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft
3663407	6	-4	1/4	6,4	#REF!	0,559	280	4060	1120	16240	50	2		
 SAE 100 R19 6 Plus	1/4" WP 280 bar (4060 psi) MSHA IC-XX/XXX													
3663408	10	-6	3/8	9,5	#REF!	0,708	280	4060	1120	16240	65	2,5		
 SAE 100 R19 10 Plus	3/8" WP 280 bar (4060 psi) MSHA IC-XX/XXX													
3663409	12	-8	1/2	12,7	#REF!	0,846	280	4060	1120	16240	90	3,5	5,5	0,367
 SAE 100 R19 12 Plus	1/2" WP 280 bar (4060 psi) MSHA IC-XX/XXX													

This hose fits with MN couplings