

R17 SAE 100 R17 PLUS

Applicable Standard

SAE J517 100 R17

Liner

Oil resistant synthetic rubber

Reinforcement

One or more braids of high tensile steel wire

Cover

Oil and weather resistant black synthetic rubber MSHA approved

Application

High pressure hydraulic lines

Temperature

Hydraulics Oils: from -40°C to 100°C (from -40°F to 212°F)
Water Glycol Hydraulic Fluids: from 0°C to 66°C (from 32°F to 151°F)
Water: from 0°C to 66°C (from 32°F to 151°F)
Air:



														
	DN	dash size	inch	mm	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft
3339881	6	-4	1/4	6,4	#REF!	0,496	210	3000	840	12000	50	2		
 ANCHOR	SAE 100 R17 6 Plus 1/4" WP 210 bar (3000 psi) MSHA IC-XX/XXX													
3339882	10	-6	3/8	9,5	#REF!	0,641	210	3000	840	12000	65	2,5		
 ANCHOR	SAE 100 R17 10 Plus 3/8" WP 210 bar (3000 psi) MSHA IC-XX/XXX													
3339883	12	-8	1/2	12,7	#REF!	0,830	210	3000	840	12000	90	3,5		
 ANCHOR	SAE 100 R17 12 Plus 1/2" WP 210 bar (3000 psi) MSHA IC-XX/XXX													
3339885	16	-10	5/8	15,9	#REF!	1,019	210	3000	840	12000	100	4		
 ANCHOR	SAE 100 R17 16 Plus 5/8" WP 210 bar (3000 psi) MSHA IC-XX/XXX													
3339886	19	-12	3/4	19,1	#REF!	1,192	210	3000	840	12000	120	5		
 ANCHOR	SAE 100 R17 19 Plus 3/4" WP 210 bar (3000 psi) MSHA IC-XX/XXX													
3339887	25	-16	1	25,4	#REF!	1,519	210	3000	840	12000	150	6		
 ANCHOR	SAE 100 R17 25 Plus 1" WP 210 bar (3000 psi) MSHA IC-XX/XXX													

This hose fits with MN couplings