

Pilot and Control Line

Applicable Standard

Pilot and Control Line

Liner

Oil resistant synthetic rubber

Reinforcement

One braid of high tensile steel wire

Cover

Oil and weather resistant black synthetic rubber MSHA approved

Application

High pressure hydraulic lines

Temperature

Hydraulics Oils: from -40°C to 121°C (from -40°F to 250°F)
Water Glycol Hydraulic Fluids: from 0°C to 70°C (from 32°F to 158°F)
Water: from 0°C to 70°C (from 32°F to 158°F)
Air:



														
	DN	dash size	inch	mm	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft
3663403	6	-4	1/4	6,4	12	0,472	103	1500	412	6000	30	1,2		
<div><div></div><div>WCL 6 1/4" Pilot and Control Line WP 103 bar (1500 psi) MSHA IC-XX/XXX</div></div>														
3668438	10	-6	3/8	9,5	15,3	0,602	103	1500	412	6000	50	2		
<div><div></div><div>WCL 10 3/8" Pilot and Control Line WP 103 bar (1500 psi) MSHA IC-XX/XXX</div></div>														
3668439	12	-8	1/2	12,7	18,5	0,728	103	1500	412	6000	60	2,4		
<div><div></div><div>WCL 12 1/2" Pilot and Control Line WP 103 bar (1500 psi) MSHA IC-XX/XXX</div></div>														