

SAE J517 100 R7

Thermoplastic elastomer

One braid of synthetic fiber

Black polyurethane cover

Medium pressure hydraulic lines







Hydraulics Oils: from -40°C to 93,5°C (from -40°F to 200°F)

Water Glycol Hydraulic Fluids: from 0°C to 66°C (from 32°F to 151°F)

Water: from 0°C to 66°C (from 32°F to 151°F)

Air:



														
	DN	dash size	inch	mm	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft
AC_924278003	5	-3	3/16	4,8	11,4	0,448	210	3000	840	12000	45	1,75		
ANCHOR 3TMA 3/16" I.D. (4.8mm) 3000 PSI WP (210 BAR) SAE 100R7 DATE SUP ID #														
AC_924278004	6	-4	1/4	6,4	13,7	0,539	192	2750	768	11000	50	2		
ANCHOR 4TMA 1/4" I.D. (6.4mm) 2750 PSI WP (192 BAR) SAE 100R7 DATE SUP ID #														
AC_924278006	10	-6	3/8	9,5	17,2	0,677	157	2250	628	9000	63	2,5		
ANCHOR 6TMA 3/8" I.D. (9.5mm) 2250 PSI WP (157 BAR) SAE 100R7 DATE SUP ID #														
AC_924278008	12	-8	1/2	12,7	21,5	0,846	140	2000	560	8000	90	3,5		
ANCHOR 8TMA 1/2" I.D. (12.7mm) 2000 PSI WP (140 BAR) SAE 100R7 DATE SUP ID #														

This hose fits with JN couplings