# **WATERBLAST 600**

## **Applicable Standard**

Hose applications according to  $\textbf{EN 1829-2}\$  manufacturer design

#### Liner

Water resistant synthetic rubber

#### Reinforcement

Four spirals of high tensile steel wire

#### Cover

Oil and weather resistant black synthetic rubber

## **Application**

High pressure water jet machines

### **Temperature**

Hydraulics Oils:

Water Glycol Hydraulic Fluids: from -40°C to 70°C (from -40°F to 158°F)

Water: from -10°C to 70°C (from 14°F to 158°F)

Air: up to 70°C (up to 158°F)



		<b>⊕</b> ©			<b>‡</b> ©					<b><u></u> <u>E</u> <u> </u></b>		A		ě	
	**	DN	dash size	inch	mm	mm	inch	MPa	psi	MP	a psi	mm	inch	g/m	lb/ft
WB600-16		25	-16	1"	25,4	39,1	1,539	60	8700	150	0 21750	330	12,99	2156	1,449
			crimping Ø +/-		crimping style -		-/- int. skive +,		+/-	/- ext. skive +/-		ins. depth +/-		le code	
					0,008	Ciliip	9 50,10	.,		0,02		)			

				crimpi	ng Ø +/-	crimping style +/-			int. skive +/-		ext. skive +/-		ins. depth +/-		ferrule code
				0,2	0,008				0,5	0,02	0,5	0,02	0,5	0,02	
	DN	dash s	inch	mm	inch		mm	inch	mm	inch	mm	inch	mm	inch	
WB600-16	25	-16	1"	42	1,654	FLAT			18	0,709	65	2,559	69	2,717	8I0W4S16

This hose fits with SERIES 3 couplings



