# **SUPERCLEAN 40 BLUE COVER**

## **Applicable Standard**

Hose dimensions according to  ${\bf ISO~11237}$ Hose applications according to EN 1829-2

#### Liner

Water resistant synthetic rubber

## Reinforcement

Two braids of high tensile steel wire

#### Cover

Oil and weather resistant blue synthetic rubber

High-pressure cleaning machines for cold and hot water. Not to be used in steam or high-temperature hydraulic applications

Temperature Cold and hot water up to 150°C (302°F), with usual cleaning ingredients

Hydraulics Oils:

Water Glycol Hydraulic Fluids:

Water: Air:



			<b>₹</b> ◎			<b>‡</b> ©				<b>ξ</b>		A		ě	
	**	DN	dash size	inch	mm	mm	inch	MPa	psi	MPa	psi	mm	inch	g/m	lb/ft
S40BU-5		8	-5	5/16"	7,9	16	0,63	40	5800	100	14500	85	3,35	326	0,219
S40BU-6		10	-6	3/8"	9,5	18,3	0,72	40	5800	100	14500	90	3,54	414	0,278
S40BU-8		12	-8	1/2"	12,7	21,5	0,846	40	5800	100	14500	130	5,12	532	0,357

					ng Ø +/-	crimping style +/-			int. skive +/-		ext. skive +/-		ıns. deptn +/-		ferrule code
				0,2	0,008				0,5	0,02	0,5	0,02	0,5	0,02	
	DN	dash s	inch	mm	inch		mm	inch	mm	inch	mm	inch	mm	inch	
S40BU-5	8	-5	5/16"	19,3	0,76	FLAT	0	0	0	0	0	0	25	0,984	
S40BU-6	10	-6	3/8"	22,0	0,866	FLAT	0	0	0	0	0	0	25	0,984	
S40BU-8	12	-8	1/2"	25,2	0,992	FLAT	0	0	0	0	0	0	27	1,063	

This hose fits with SERIES 1 couplings



SuperClean 40 \*\* \*/\*" +150°C WP \*\* MPa ( \*\*\* bar )

