

# PG115 Specifications

## RATINGS

Rated Input Power	130hp / 95kW
Rated Input Torque	600 lb ft / 800 Nm
Rated Input Speed	2,400 rpm
Maximum Input Speed	2,600 rpm
Minimum Input Speed	600 rpm

All Ratings Subject to Duty Cycle and Application Approval

## POWER TAKE OFF (PUMP Auxiliary drive)

Mounting	SAE "C" 2 Bolt Drive on Rear of transmission
Rated Power	80 hp / 60 kW

## CLUTCHES

Clutches	Electro-hydraulic Oil-Cooled Multidisc
Clutch Modulation Control	Hydro-mechanical modulated valve direction control

## GEARS

Gearing Type	Helical	
Standard Gear Ratios		
1F	4.842	
2F	3.000	
3F	2.276	
4F	1.410	
5F	1.000	
6F	0.620	
4 Wheel Drive Ratio	0.973	1.000
(Rotation Opposite to Engine)		
1R	4.842	
2R	2.276	
3R	1.000	

## OPTIONAL FEATURES

- Torque converter to match co-ax pump drive machine application
- Various ratios available to match the application
- 20 km/h option for TUV regulations
- Fully modulated control valves for directional changes
- Sequential shift electronic controller
- Temperature sender (max 120°C) available
- Available without pump drive
- Optional electrical connectors Deutsch or DIN
- 4 wheel drive options:
  - Full multi-plate clutch pack "engage on the move"
  - Permanent 4 wheel drive
- Remote mount transmission option available

