

Cat® 160

Motor Grader

Conquer the toughest roads with confidence. Powered to grade any terrain, the Cat® 160 motor grader transforms rugged landscapes into smooth, controlled paths – no matter how steep, soft, or stubborn the ground. When productivity matters and every pass counts, this is the performance that puts you ahead.

Powerful Performance

- Cut through the toughest road conditions with consistent power to the ground.
- Achieve stronger power to the ground with an engine built for consistent, reliable, and constant net power – no matter the conditions.
- Optional 16-foot moldboard clears a larger area per pass, accelerating job completion.

Optimized for the Operator

- Fully redesigned cab with improved automatic climate control and seat adjustment options.
- Enjoy superior sightlines with enhanced visibility from the operator station, giving operators a clearer view around the entire cab.
- Optional integrated rear vision, front vision, and 360° cameras show in large main display for increased machine surroundings awareness.

Maximized Productivity

- Cat Grade technologies help hit grade faster.
- Joystick control provides ergonomic and precise steering.
- Expanded versatility to easily upgrade attachments.

Choices

- Equipment Management technologies work together to put equipment information at your fingertips. Get real-time access to information on every machine in your fleet on any jobsite – no matter the size of the operation or the brands of equipment you run.
- Reduce material usage with the full range of Cat Grade technologies for your motor grader, and reach target grade faster with dependable accuracy.
- Choose standard or all-wheel drive (AWD) powertrain.

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat® dealer for details.

	Standard	Optional
OPERATOR ENVIRONMENT		
Cab storage	✓	
CB radio mount bracket with converter		✓
Cellphone holder	✓	
Cup holder	✓	
Automatic climate control	✓	
Lights, dome interior	✓	
Radio ready	✓	
AM/FM, Bluetooth®, Weatherband		✓
Satellite radio		✓
Rollover protective structure (ROPS) / falling objects protective structure (FOPS)	✓	
Seat belt	✓	
Seat belt w/indicator		✓
Seat, air suspension	✓	
Seat, premium heated and ventilated		✓
Wipers, front, door	✓	
Wipers, side windows, rear		✓
SAFETY		
Back-up alarm	✓	
Cameras		✓
Grab rails and tandem walkways	✓	
Hydraulic brakes	✓	
Lockout, hydraulic	✓	
Mirror, rearview	✓	
Mirrors, B-post		✓
Mirrors, side view		✓
Signaling/warning horn	✓	

	Standard	Optional
ATTACHMENTS		
Angling plow		✓
Brooms		✓
Counterweight		✓
Front blade, narrow		✓
Front blade, standard		✓
Lift groups		✓
Mid-machine scarifier (MMS)		✓
One-way plow		✓
Push block		✓
Rear ripper/scarifier		✓
Snow wing		✓
Straight plow		✓
Tow hitch		✓
Trip edge plow		✓
U-V plow		✓
V-Plow		✓
POWERTRAIN		
Cat® C9.3B engine	✓	
All-wheel drive (AWD)		✓
Cold weather package		✓
Cold weather package plus		✓
Eco mode	✓	
Ecology drain	✓	
Engine idle shutdown	✓	
High-speed engine oil drain		✓
Reversing fan		✓
Transmission with auto shift		✓
Transmission, 9-speed	✓	
DRAWBAR CIRCLE MOLDBOARD		
Blade lift accumulators		✓
Circle drive slip clutch	✓	
Circle, top adjust	✓	
Circle saver		✓
High Performance Circle with circle saver		✓
Moldboard cutting edges		✓
Moldboard end bits		✓
Moldboard grader bits		✓
Moldboard, 14 foot	✓	
Moldboard, 16 foot		✓

(Continued on next page)

Standard and Optional Equipment *(continued)*

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional
SERVICE AND MAINTENANCE		
Engine service light	✓	
Extended life coolant	✓	
Ground-level diesel exhaust fluid (DEF) and fuel fill	✓	
Grouped location for engine oil and fuel filters	✓	
Next generation fluid filters	✓	
Service doors, barrel-hinged	✓	
Service doors, lower panel toolless removal	✓	

	Standard	Optional
TECHNOLOGY		
Application Segmentation and Efficiency Coach		✓
Cat Grade 3D Mastless		✓
Cat Grade 3D Ready Plus		✓
Cross Slope Assist: E-Fence, Autoarticulation, Stable Blade, (2D)	✓	
Front Vision		✓
Rear Vision		✓
RTK corrections radios for Cat Grade w/3D Mastless		✓
Security System		✓
Stable Blade		✓
Surround Vision (360°)		✓
Surround Vision (360°) w/People Detection		✓
Tire Pressure Monitoring System (TPMS)		✓
VisionLink™		✓

Cat® 160 Motor Grader

Technical Specifications

Powertrain		
Engine Model	Cat® C9.3	
Emissions	Meets U.S. EPA Tier 4 Final and EU Stage V emission standards	
Net Engine Power Range	107-197 kW	143-264 hp
Net Engine Power Range (AWD)	112-209 kW	150-280hp
Displacement	9.3 L	567.5 in^3
Bore	115 mm	4.5 in
Stroke	149 mm	5.9 in
Torque Rise	42%	
Torque Rise (AWD)	38%	
Maximum Torque	1390 N•m	1,025 lbf-ft
Maximum Torque (AWD On)	1466 N•m	1,081 lbf-ft
Speed @ Rated Power	2,000 rpm	
Number of Cylinders	6	
Derating Altitude	4500 m	14,764 ft
Derating Altitude (AWD)	3000 m	9,843 ft

- Advertised power is tested per the specified standard in effect at the time of manufacture.
- Net power advertised is the power available at the flywheel when the engine is equipped with fan at minimum speed, air intake system, exhaust system, and alternator.

Weights		
Base Weight – Non-AWD	17804 kg	39,251 lb
Base Weight – AWD	19 853 kg	43,767 lb
Typically Equipped Weight* – Non-AWD	19 197 kg	42,322 lb
Typically Equipped Weight* – AWD	20 792 kg	45,838 lb

*Typically equipped operating weight is calculated with push block, transmission guard, rear ripper/scarifier, 14.0R24 tires with multi-piece (MP) rims, and other equipment.

Moldboard		
Height (Cutting Edges + Moldboard)	556 mm	21.9 in
Width (Cutting Edges + Moldboard)	3658 mm	144.0 in
Thickness	22 mm	0.9 in
Arc Radius	413 mm	16.3 in
Throat Clearance, Non-HPC	119 mm	4.7 in

Service Refill Capacities		
Standard Circle Drive	7 L	1.8 gal
High Performance Circle Drive	9.5 L	2.5 gal
Cooling System	50 L	13.2 gal
Diesel Exhaust Fluid (DEF)	40 L	10.6 gal
Engine Crankcase	26 L	6.9 gal
Fuel Tank	371 L	98.0gal
Hydraulic System	123 L	32.5 gal
Tandem Housing (each)	80 L	21.1 gal
Transmisson and Differential	60 L	15.9 gal

Air Conditioning System

- The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a or R1234yf. See the label or instruction manual for identification of the gas.
  – If equipped with R134a (Global Warming Potential = 1430), the system contains 1.6 kg (3.5 lb) of refrigerant which has a CO_2 equivalent of 2.288 metric tonnes (2.521 tons).

AEXQ4701-02 (05-2026)
Replaces: AEXQ4701-00
Build Number 16A
(Aus-NZ, Chile, Colombia, Europe, N Am, Türkiye)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at **www.cat.com**

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

© 2026 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, VisionLink, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.