



Cat[®] 160

Motor Grader

Conquer the toughest roads with confidence. Powered to grade any terrain, the Cat[®] 160 motor grader transforms rugged landscapes into smooth, controlled paths – no matter how steep, soft, or stubborn the ground. When productivity matters and every pass counts, this is the performance that puts you ahead.

Powerful Performance

- Cut through the toughest road conditions with consistent power to the ground.
- Achieve stronger power to the ground with an engine built for consistent, reliable, and constant net power – no matter the conditions.
- Optional 16-foot moldboard clears a larger area per pass, accelerating job completion.

Optimized for the Operator

- Fully redesigned cab with improved automatic climate control and seat adjustment options.
- Enjoy superior sightlines with enhanced visibility from the operator station, giving operators a clearer view around the entire cab.
- Optional integrated rear vision, front vision, and 360° cameras show in large main display for increased machine surroundings awareness.

Maximized Productivity

- Cat Grade technologies help hit grade faster.
- Joystick control provides ergonomic and precise steering.
- Expanded versatility to easily upgrade attachments.

Choices

- Equipment Management technologies work together to put equipment information at your fingertips. Get real-time access to information on every machine in your fleet on any jobsite – no matter the size of the operation or the brands of equipment you run.
- Reduce material usage with the full range of Cat Grade technologies for your motor grader, and reach target grade faster with dependable accuracy.
- Choose standard or all-wheel drive (AWD) powertrain.



Cat® 160 Motor Grader

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat® dealer for details.

	Standard	Optional		Standard	Optional
OPERATOR ENVIRONMENT			ATTACHMENTS		
Cab storage	✓		Angling plow		✓
CB radio mount bracket with converter		✓	Brooms		✓
Cellphone holder	✓		Counterweight		✓
Cup holder	✓		Front blade, narrow		✓
Automatic climate control	✓		Front blade, standard		✓
Lights, dome interior	✓		Lift groups		✓
Radio ready	✓		Mid-machine scarifier (MMS)		✓
AM/FM, Bluetooth®, Weatherband		✓	One-way plow		✓
Satellite radio		✓	Push block		✓
Rollover protective structure (ROPS) / falling objects protective structure (FOPS)	✓		Rear ripper/scarifier		✓
Seat belt	✓		Snow wing		✓
Seat belt w/indicator		✓	Straight plow		✓
Seat, air suspension	✓		Tow hitch		✓
Seat, premium heated and ventilated		✓	Trip edge plow		✓
Wipers, front, door	✓		U-V plow		✓
Wipers, side windows, rear		✓	V-Plow		✓
SAFETY			POWERTRAIN		
Back-up alarm	✓		Cat® C9.3B engine	✓	
Cameras		✓	All-wheel drive (AWD)		✓
Grab rails and tandem walkways	✓		Cold weather package		✓
Hydraulic brakes	✓		Cold weather package plus		✓
Lockout, hydraulic	✓		Eco mode	✓	
Mirror, rearview	✓		Ecology drain	✓	
Mirrors, B-post		✓	Engine idle shutdown	✓	
Mirrors, side view		✓	High-speed engine oil drain		✓
Signaling/warning horn	✓		Reversing fan	✓	
			Transmission with auto shift		✓
			Transmission, 9-speed	✓	
			DRAWBAR CIRCLE MOLDBOARD		
			Blade lift accumulators		✓
			Circle drive slip clutch	✓	
			Circle, top adjust	✓	
			Circle saver		✓
			High Performance Circle with circle saver		✓
			Moldboard cutting edges		✓
			Moldboard end bits		✓
			Moldboard grader bits		✓
			Moldboard, 14 foot	✓	
			Moldboard, 16 foot		✓

Standard and Optional Equipment

Standard and optional equipment may vary. Consult your Cat® dealer for details.

	Standard	Optional		Standard	Optional
SERVICE AND MAINTENANCE			TECHNOLOGY		
Engine service light	✓		Application Segmentation and Efficiency Coach		✓
Extended life coolant	✓		Cat Grade 3D Mastless		✓
Ground-level diesel exhaust fluid (DEF) and fuel fill	✓		Cat Grade 3D Ready Plus		✓
Grouped location for engine oil and fuel filters	✓		Cross Slope Assist: E-Fence, Autoarticulation, Stable Blade, Cross Slope (2D)	✓	
Next generation fluid filters	✓		Front Vision		✓
Service doors, barrel-hinged	✓		Rear Vision		✓
Service doors, lower panel toolless removal	✓		RTK corrections radios for Cat Grade w/3D Mastless		✓
			Security System		✓
			Stable Blade		✓
			Surround Vision (360°)		✓
			Surround Vision (360°) w/People Detect		✓
			Tire Pressure Monitoring System (TPMS)		✓
			VisionLink™		✓

Cat® 160 Motor Grader

Technical Specifications

Powertrain

Engine Model	Cat® C9.3	
Emissions	Meets U.S. EPA Tier 4 Final and EU Stage V emission standards.	
Net Engine Power Range	112-206 kW	150-276 hp
Net Engine Power Range (AWD)	111-179 kW	149-240 hp
Displacement	9.3 L	567.5 in ³
Bore	115 mm	4.5 in
Stroke	149 mm	5.9 in
Torque Rise	39%	
Torque Rise (AWD)	38%	
Maximum Torque	1453 N·m	1,071.7 lbf·ft
Maximum Torque (AWD On)	1466 N·m	1,081.3 lbf·ft
Speed @ Rated Power	2,000 rpm	
Number of Cylinders	6	
Derating Altitude	4500 m	14,764 ft
Derating Altitude (AWD)	3000 m	9,843 ft

- Advertised power is tested per the specified standard in effect at the time of manufacture.
- Net power advertised is the power available at the flywheel when the engine is equipped with fan at minimum speed, air intake system, exhaust system, and alternator.

Weights

Weight (Non-AWD)	19 853 kg	43,768 lb
Weight (AWD)	20 792 kg	45,838 lb

*Typically equipped operating weight is calculated with push block, transmission guard, rear ripper/scarifier, 14.0R24 tires with multi-piece (MP) rims, and other equipment.

Moldboard

Width	4267 mm	14.0 ft
Height	609.5 mm	24.0 in
End Bit	152.4 mm	6.0 in
Cutting Edge	203.2 mm	8.0 in
Arc Radius	413 mm	16.3 in
Throat Clearance	117 mm	4.6 in

Service Refill Capacities

Standard Circle Drive	7 L	1.8 gal
High Performance Circle Drive	9.5 L	2.5 gal
Cooling System	68 L	18.0 gal
Diesel Exhaust Fluid Tank	40 L	10.6 gal
Engine Crankcase	28 L	7.4 gal
Fuel Tank	371 L	98.0 gal
Hydraulic System	600 L	158.5 gal
Tandem Housing (each)	80 L	21.1 gal
Transmission and Differential	60 L	15.9 gal

Air Conditioning System

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a or R1234yf. See the label or instruction manual for identification of the gas.

– If equipped with R134a (Global Warming Potential = 1430), the system contains 1.6 kg (3.5 lb) of refrigerant which has a CO₂ equivalent of 2.288 metric tonnes (2.521 tons).

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

© 2026 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, VisionLink, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEXQ4701-00 (02-2026)
Build Number 16A
(N Am, Europe, Aus-NZ, Chile,
Colombia, Turkiye)

