



Arrangement shown
with optional trailer

XQ300 SOUND ATTENUATED

50/60 Hz

FEATURES



EMISSIONS

- EPA Tier 3 and CARB Emissions Certified for non-road mobile applications at all 50 Hz and 60 Hz ratings



CAT C9 ATAAC DIESEL ENGINE

- Utilizes ACERT® Technology
- Reliable, rugged, durable design
- Field-proven in multiple applications worldwide
- Four-stroke-cycle diesel engine combines durability with minimum weight while providing dependability and economy
- 50/60 Hz convertibility



CAT SR4B GENERATOR

- Designed to match performance and output characteristics of Caterpillar diesel engines
- Permanent magnet excitation
- Segregated AC/DC, low voltage accessory box provides single point access to accessory connections



ENCLOSURE

- Made with 12-gauge steel
- Single point lifting eye
- Sound attenuated
- Convenient hand holds and steps for safe operation
- Two coat polyester powder-coated finish

ENVIRONMENTALLY FRIENDLY DESIGN

- Sound attenuated for low noise operation
- OSHA compliant safe design
- 110% spill containment for coolant and oil
- UL 142 certified dual wall fuel tank

MULTI-VOLTAGE DISTRIBUTION PANEL

- Dual voltage, manual changeover board
- Load door safety switch
- Rust-free hinges on rear opening door
- Adequate space for line and plug connection without interference
- Remote start and stop contacts

SINGLE-SOURCE SUPPLIER

- Complete systems designed at Caterpillar ISO 9001:2000 certified facilities
- **Certified Prototype Tested** with torsional analysis

WORLDWIDE PRODUCT SUPPORT

- Worldwide parts availability through the Caterpillar dealer network
- With over 1,875 dealer outlets operating in 200 countries, you're never far from the Caterpillar part you need.
- 99.7% of parts orders filled within 48 hours. The best product support record in the industry.
- Caterpillar dealer service technicians are trained to service every aspect of your electric power generation system.

FACTORY INSTALLED STANDARD AND OPTIONAL EQUIPMENT

STANDARD FEATURES	
Air Inlet System	Air cleaner, dual element Turbocharger
Charging System	Battery charger Heavy duty charging alternator
Control Panel	Generator controls and monitoring Fuel tank monitoring Engine controls and monitoring Digital displays
Cooling System	Fan and belt guards Base mounted radiator Air to air aftercooling
Distribution Panel	Lockable doors Load door safety switch (trips breaker upon door opening) Individual bus bar connections Circuit breaker with 24 VDC shunt trip Remote start/stop contacts Shore power connections
Enclosure	Sound attenuated 12-gauge steel Lockable doors Separate vented battery compartment Single point lifting Exterior oil and water drains with interior valves Hidden exterior fuel drain Hand holds and steps Powder-coated finish
Fuel System	Primary fuel filter/water separator UL142 dual wall fuel tank, 1667 L (440 g) Radiator-mounted fuel cooler
Generator	Brushless, permanent magnet Coastal corrosion protection Shock mounted VR6 voltage regulator Space heater UL approved Reconnectable 240-480 volt
Mounting System	Generator soft mounted to base Base contains integral fuel tank Skiddable structural steel design 110% oil and coolant spill containment
Starting System	Electric starting motor Battery set with disconnect switch Jacket water heater with thermostat, shut-off valves

OPTIONAL FEATURES	
Trailer	Full frame support Independent tandem axle trailer frame with tongue Electric actuated hydraulic brakes with rechargeable battery backup breakaway system Overcenter mechanical parking brake Full length fenders Non-skid surface on steps Heavy duty safety chains and grab hooks Reinforced 4540 kg (10,000 lb) top wind drop jack

SPECIFICATIONS



CAT SR4B GENERATOR

Frame size 449
 Type Permanent magnet brushless
 Construction Single bearing, close coupled
 Three phase 12 lead reconnectable
 Insulation Class H with coastal insulation protection
 IP rating 22
 Alignment Pilot shaft
 Voltage regulator 3-phase sensing with Volts-per-Hertz
 Voltage regulation $\pm 1/2\%$ steady state/ $\pm 1/2\%$
 no load to full load
 TIF Less than 50
 THD Less than 5%



CAT ENGINE

C9 ATAAC, 4-stroke-cycle watercooled diesel
 Bore – mm (in) 112 (4.41)
 Stroke – mm (in) 149 (5.87)
 Displacement – L (cu in) 8.8 (537)
 Compression ratio 16.1:1
 Aspiration Turbocharged-ATAAC
 Engine control ADEM™ A4



CAT CONTROL PANEL – EMCP 3.2

24 Volt DC Control
 NEMA 1, IP22 enclosure
 Lockable hinged door
 Enclosure mounted
 Single location customer connector point
 16 light alarm module with alarm horn
 Electric fuel level gauge

Consult your Caterpillar dealer for available voltages.



TECHNICAL DATA

		XQ300			
Power Rating		Standby	TMI Ref.	Prime	TMI Ref
60 Hz	ekW	300	DM8168	275	DM8500
50 Hz	kVA	310	DM8503		
Engine and Container Information		C9			
Engine model		see chart on page 6			
Container dimensions					
Shipping Weight (Dry)					
Unit with trailer	kg (lb)	6210 (13,690)			
Unit without trailer	kg (lb)	4980 (10,980)			
Maximum Fuel Capacity Weight					
Unit with trailer	kg (lb)	7506 (16,550)			
Unit without trailer	kg (lb)	6278 (13,840)			
Engine Lubricating Oil Capacity	L (qts)	40 (10.55)			
Engine Coolant Capacity with Radiator	L (gal)	36 (9.5)			
Fuel Tank Capacity	L (gal)	1516 (400)			
Fuel Consumption	L/hr (gal/hr)	89.1 (23.5)		81.3 (21.5)	
Fuel Consumption (75% Prime)	L/hr (gal/hr)		63.5 (16.8)		
Running Time @ 75% Prime	hours		24		
Sound Level					
Standby	dB(A)	74.72			
No load @ 7 m (23 ft)	dB(A)	70.20			
Prime	dB(A)	73.49			
Ambient Capability	Deg C (Deg F)	43 (109.4)			

RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications:

- NEMA MG1-32, IEC 60034, CSA, 98/37/EEC, 72/23/EEC, UL 508, UL142, ISO3046/1, ISO8528, 89/336/EEC

Standby – Output available with varying load for the duration of the interruption of the normal source power. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046/1, AS2789, DIN6271, and BS5514.

Prime – Output available with varying load for an unlimited time. Prime power in accordance with ISO8528. 10% overload power in accordance with ISO3046/1, AS2789, DIN6271, and BS5514 available on request.


Ratings are based on SAE J1349 standard conditions.

These ratings also apply at ISO3046/1, DIN6271, and BS5514 standard conditions.

Fuel rates are based on fuel oil of 35° API [@ 16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lb/U.S. gal).

Additional ratings may be available for specific customer requirements. Consult your Caterpillar representative for details.


DISTRIBUTION PANEL




Wiring Descriptions

1. 1200A main breaker 240V/480V with adjustable trip and 24V DC shunt trip
2. Voltage change over board
3. 50 amp 240V branch breaker
4. 20 amp 240V branch breaker
5. 20 amp 120V branch breaker
6. 15 amp 120V branch breaker
7. 50 amp 240V twistlock receptacle
8. 20 amp 240V twistlock receptacle
9. 20 amp 120V twistlock receptacle (2x)
10. 20 amp 120V ground fault interrupter, (2x)
11. 15 amp 120V ground fault interrupter, duplex receptacle (2x)
12. 30 amp 120V battery charger/generator space heater receptacle
13. 30 amp 120V JWH receptacle
14. Remote start/stop contacts
15. 12.7 mm (1/2") ground stud
16. Load connection bus board
[6.35 mm × 101.6 mm × 101.6 mm
(1/4" × 4" × 4") bus bars]

CONTAINER DIMENSIONS — TOP VIEW



CONTAINER DIMENSIONS — RIGHT SIDE VIEW



Overall Dimensions				
	Package		With Trailer	
Length	4597.4 mm	181 in	6248.3 mm	246 in
Width	1498.6 mm	59 in	2540.0 mm	100 in
Height	2387.6 mm	94 in	2882.8 mm	113.5 in

This page intentionally left blank.

This page intentionally left blank.