

C18 ACERT™

MARINE GENERATOR SET PACKAGE

425 ekW 465 bkW 1800 rpm
550 ekW 599 bkW 1800 rpm



Image shown
may not reflect
actual engine

SPECIFICATIONS

I-6, 4-Stroke-Cycle-Diesel


- EPA Tier 3/IMO II compliant
- 18.0 L (1098 cu in) displacement
- 60 hz 1800 rpm rated engine speed
- 145 mm (5.7 in) bore x 183 mm (7.2 in) stroke
- Turbocharged and aftercooled aspiration
- Electronically governed
- Heat exchanger or keel cooled
- Refill capacity
 - Cooling system: 45 L (12 gal)
 - Lube oil system: 68 L (18 gal) deep pan
- 500-hour oil change interval deep pan
- Caterpillar Diesel Engine Oil 10W30 or 15W40
- SAE No. 0 flywheel and flywheel housing
136 flywheel teeth (18 inch)
- Counterclockwise rotation from flywheel end



STANDARD ENGINE EQUIPMENT

- Separate circuit aftercooler (SCAC)
- Heavy-duty inlet air filter
- Heat exchanger or keel cooling
- SCAC and JW shunt tanks with sight glass
- Auxiliary pump for heat exchanger cooling
- SCAC and jacket water pumps
- Watercooled exhaust manifold and turbocharger
- Round flanged exhaust outlet
- Center sump oil pan, deep
- Oil filler, filter, and dipstick, front service
- MEUI fuel system
- Fuel filter, front service
- Fuel transfer and priming pumps
- Hybrid fuel lines
- Electronic fuel/air ratio control
- Formed C-channel rails
- Vibration isolators
- SR4B permanent magnet 12-lead generator
- Digital voltage regulator
- Class H insulation, Class F temperature rise, IP23 protection

DIMENSIONS





ENGINE DIMENSIONS & WEIGHT

(1) Length	3040 mm	119.7 in
(2) Width	1547 mm	60.9 in
(3) Height	1684 mm	66.3 in
Weight, Net Dry (approx)	4406 kg	9713 lb

Note: Do not use these dimensions for installation design. See general dimension drawings for detail.

MARINE ENGINE PERFORMANCE

Prime Rating – EM0129-00						Prime Rating – EM0128-00					
% Load	ekW	bhp	g/hr	bkW	g/bkW-hr	ekW	bhp	g/hr	bkW	g/bkW-hr	
100	425	624	32.2	465	220	550	803	40.2	599	212	
75	319	468	24.5	349	223	413	603	30.3	449	214	
50	213	312	17.5	233	239	275	402	22.0	300	234	
25	106	156	10.3	116	282	138	201	12.3	150	261	
10	43	62	5.3	47	360	55	80	6.4	60	339	



OPTIONAL ATTACHMENTS

- Air inlet adapter
- Cat® alarm and protection system
- EMCP 3.3 control panel
- Battery charger 10 amp
- Charging alternator 24V 105 amp
- Exhaust elbows, dry or watercooled
- Exhaust flange and flexible fitting
- Mufflers (option for spark arresting)
- Duplex fuel filter – front service
- Fuel cooler
- Primary fuel/water separator
- Duplex oil filter – front service
- Manual sump pump
- Starting motors – electric and/or air
- Jacket water heaters
- Battery sets – 24V 950-1300 CCA
- Load sharing module (option for type approved module)
- Low voltage connections
- Extension terminal box
- Power take-offs
- Fumes disposal (closed system)

CAT, CATERPILLAR, their respective logos, ACERT, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.