

# DELTA LEVER

A clean, streamlined design on the Delta fits a wide range of decorating styles: from traditional and ranch to contemporary.

- Featuring SmartKey Security<sup>™</sup>
- ANSI/BHMA Grade 3 Certification
- Easy to install



Delta Entry Lever in Venetian Bronze



# Specifications

Door Prep	Cross Bore 21/8". Edge Bore 1" Latch Face 1 x 2 1/4"		
Backset	Adjustable 2 3⁄8″ or 2 3⁄4″		
Door Thickness	1 ¾" - 1 ¾" Doors standard. Thick Door Kit Available for 200 & 405 functions for up to 2 ¼"		
Cylinder	SmartKey Security <sup>™</sup> or traditional 5-pin Pin & Tumbler		
Faceplates	$1^{\prime\prime}$ x $2{}^{1}\!\!4^{\prime\prime}$ includes round corner, square corner and drive-in		
Strikes	2 ¼″ full lip. Includes round corner. Other options available.		
Bolt	1⁄2" throw		
Door Handing	Reversible for right or left-handed doors		
ANSI/BHMA	A156.2 Grade 3 (all functions except 488).		
UL	90 Min UL Rating available on 409 series in 15 & 26D finish		
ADA	N/A		
Warranty	Lifetime Mechanical and Lifetime Finish		

## Functions



Passage/Hall/Closet: Both levers always free. - 200 DL



Privacy/Bed/Bath: Both levers locked or unlocked by turn-button inside. Outside lever unlocked by emergency key. - 300 DL



Keyed Entry: Both sides locked or unlocked by key outside or turnbutton inside. - 405 DI



**Storeroom:** Outside unlocked only while key is turned. Inside always free. -412 DL -Available with SmartKey cylinder in 26D finish




Half Dummy Trim, Surface Mounted: For doors where only a pull is required. No operation. - 488 DL



Interior Pack: Inside lever & thumb turn of handleset. 687/800 Handlesets: - 966 DL: Single Cylinder

### Dimensions




Design	Α	В	С	C (Keyed)
Delta	2 5/8″	3 19/32″	1 29/32″	2 15/32"



#### One Key For All Your Locks

Protects against advanced break-in techniques and allows you to re-key your lock yourself in seconds.



# Finishes



Polished Brass Lo3/3 Available only for 405DL entry lever with SmartKey cylinder



Kwikset







#### LIFETIME WARRANTY

