

HomeConnect 620

Z-WAVE[®] SMART LOCK



Complete Access Control for a Seamless Smart Home Experience

- EASY CODE MANAGEMENT: Customize up to 250 user codes.
- **Z-WAVE 700 LONG RANGE:** Increased wireless range throughout the home.
- **S2 AND SMARTSTART COMPATIBLE:** S2 for advanced Z-Wave security and SmartStart for easy setup and provisioning.
- **SMART HOME COMPATIBLE:** Works with popular Z-Wave smart home controllers, gateways and hubs.
- **KEYLESS ENTRY:** Makes coming and going secure and convenient.

1 SELLING U.S. LOCK BRAND


Specifications

Wireless Communication:

Protocol	Z-Wave 700 Series Long Range (LR)		
RF Operation	908.42 MHz (mesh), 912 and 920 MHz (LR)		
Electrical:			
Input Power	Input Power 6V (4 x AA alkaline batteries)		
Mechanical:			
Door Prep	$1{}^{1\!\prime}_{\!\!2}{}^{\prime\prime}$ and $2{}^{\prime}_{\!\prime}{}_{\!\!8}{}^{\prime\prime}$ diameter cross bore hole and 1" edge bore latch hole		
Backset	Adjustable 2 $\frac{3}{8}$ " or 2 $\frac{3}{4}$ "		
Door Thickness	1 ³ / ₈ " - 2"		
Faceplates	1" x 2 ¼" round corner standard		
Strikes	Round corner, 4 hole strike, $1\frac{1}{8}$ " x 2 $\frac{3}{4}$ "		
Latch	h Round corner adjustable 2 ³ / ₈ " x 2 ³ / ₄ "		
Bolt	t 1" throw, steel deadbolt		
Door Handing	ding Reversible		
Cylinder	SmartKey Security™ KW1 cylinder		
Environmental:			
Temperature Range	Exterior: -40°F to 150°F Interior: 32°F to 140°F		


Dimensions

Traditional



TRL Design	Α	в	С	D
Interior	2 ²³ / ₃₂ " (69.1 mm)	5 ²⁵ / ₃₂ " (146.6 mm)	1 ¹⁵ / ₁₆ " (49.5 mm)	4 ¹⁹ / ₃₂ " (116.5 mm)
Exterior	2 ¹³ / ₁₆ " (71.43 mm)	4 ⁹ /16″ (115.88 mm)	1 1/4″ (31.75 mm)	-





CNT Design	Α	В	С	D
Interior	2 ²³ / ₃₂ " (69.1 mm)	5 ²⁵ / ₃₂ " (146.6 mm)	2 1/8" (53.97 mm)	4 ¹ / ₂ " (114.3 mm)
Exterior	2 ²⁵ / ₃₂ " (70.64 mm)	4 ⁵ / ₁₆ " (109.53 mm)	1 ¹ / ₄ " (31.75 mm)	-

Temperature Range	Exterior: -40°F to 150°F Interior: 32°F to 140°F
Humidity	Exterior: 100% condensing Interior: 30% - 95% non-condensing

Features

- AUTO LOCK: Convenience and peace of mind with customizable 30 second, 1, 3, 5 or 10 minute auto lock time delay.
- 12-MONTH BATTERY LIFE: 4x AA alkaline batteries (included).
- EASY INSTALL: Easily install with screwdriver. No hard wiring required.
- CERTIFIED SECURITY: Grade 2 BHMA Certified, up to 2.5x stronger than Grade 3.
- FEATURING SMARTKEY SECURITY: Protects against advanced break-in techniques and allows you to re-key your lock yourself in seconds.
- PROGRAMMING CODE: Provides improved access code management where a programming code is required to add or delete user codes (optional).

Finishes











Kwikzet









Satin Nickel 15 98935-001

98935-002

Venetian Bronze 11P Polished Brass LO3

Satin Nickel 15 Venetian Bronze 11P 98935-004 98935-005

Polished Chrome 26 98935-006

Matte Black 514 98935-007



19701 DaVinci, Lake Forest, CA 92610 • Kwikset.com • 1-800-327-LOCK



ONE YEAR ELECTRONIC WARRANTY*

*See kwikset.com/support/warranty for the lifetime limited mechanical and finish warranties and one year limited electronics warranty.

*Consulte kwikset.com/support/warranty para ver las garantías mecánicas y de acabado limitadas de por vida y la garantía limitada de un año de los electrónicos



