

SAFE LOCK

by **Kwikset**



REMINY™ Lever

- ANSI/BHMA Grade 3 certified security
- 3-hour UL fire-rated product available
- ADA Compliant
- Lifetime Warranty
- Available in round contemporary rose
- Push-Button locking feature



Privacy function
interior push-button
in Polished Chrome



Privacy function
interior push-button
in Satin Nickel





SAFE LOCK

by **Kwikset**

Specifications

Door Prep	Cross Bore 2-1/8", Edge Bore 1"
Backset	Adjustable 2-3/8" or 2-3/4".
Door Thickness	1-3/8" - 1-3/4" standard doors
Cylinder	Traditional 5-Pin, Pin & Tumbler
Faceplates	1" x 2-1/4" Round corner or drive-in
Strikes	Lever: 2-1/4" full lip, specify round corner
Bolt	Lever: 1/2" Throw
Door Handing	Non-handed
ANSI/BHMA	Grade 3 certified
UL	Meets 3 hour UL fire rating for SL1002. Optional 1/3 hour UL fire rating for SL1000 and SL6000.

Function Availability

	Model No.	Description (ANSI/BHMA functions are listed in italics)
	1000/1002UL	Passage/Hall/Closet: Both levers always free. <i>-F75</i>
	4000	Privacy/Bed/Bath: Both levers locked or unlocked by push button inside. Outside knob unlocked by emergency key. <i>-F76</i>
	6000	Entry: Both levers locked or unlocked by key outside or push button inside. <i>-F82</i>
	7000	Half Dummy Trim, Surface Mounted: For doors where only a pull is required. No operation. <i>-Int.</i>

Available Finishes



15 Satin Nickel



26 Polished Chrome



514 Matte Black

