

SMARTCODE™ 888 DEADBOLT FEATURING Z-WAVE® 500



Model #: 888

Function: Single Cylinder Electronic Deadbolt

Convenience

- 5-Button keypad with one-touch locking
- Motorized deadbolt enables true remote locking & unlocking
- Tapered deadbolt design permits misaligned doors to lock & unlock with ease
- Features SmartKey® Re-Key Technology with BumpGuard™ Protection

Customizable Features

- Auto re-lock 30 seconds after unlocking - ON/OFF
- Interior LED locked/unlocked status - ON/OFF
- Audible feedback - ON/OFF

Security

- 30 user access code capacity, 4-8 digit code length
- MasterCode feature for improved user code management
- 128-bit Advanced Encryption Standard (AES) communication
- Meets BHMA Grade 3 deadbolt operational and security standards
- Drill and pick resistant backup keyway with BumpGuard™ protection
- Incorrect code protection with audible alarm
- Audit trail logging stores access history in the lock memory
- Date/time scheduled user access control

Specifications

Electrical:

Input Power 6V (4 x AA alkaline batteries)

Mechanical:

Door Prep 2 1/8" diameter face hole & 1" diameter latch hole

Backset Adjustable 2 3/8" or 2 3/4"

Door Thickness 1 3/8" - 1 3/4" automatic adjustment

Faceplates 1" x 2 1/4" round corner standard

Strikes Round corner strike 2 3/4" x 2 1/8"

Latch Round corner adjustable 2 3/8" x 2 3/4"

Bolt 1" throw, steel deadbolt

Door Handing Reversible

Cylinder SmartKey Security™

Environmental:

Temperature Range Exterior: -40°F to 150°F
Interior: 32°F to 140°F

Humidity Exterior: 100% condensing
Interior: 30% - 95% non-condensing


Wireless Communication

- Z-Wave® 500 wireless technology
- RF Operation: 908.42 MHz (US)
- Range: Typical 160ft or more line of sight



Electronic Compliance

- Z-Wave® Plus
- FCC Part 15
- Industry Canada
- Australia-New Zealand



Design	A	B	C	D
Interior	2 23/32" (69.1 mm)	5 25/32" (146.6 mm)	1 15/16" (49.5 mm)	4 19/32" (116.5 mm)
Exterior	2 21/32" (67.4 mm)	4 19/32" (116.3 mm)	1 3/16" (29.8 mm)	---

Supported Command Classes:

- BASIC
- VERSION
- SECURITY
- Z-WAVE PLUS
- MANUFACTURER SPECIFIC
- DEVICE RESET LOCALLY
- BATTERY
- SCHEDULE ENTRY LOCK
- FIRMWARE UPDATE MD
- DOOR LOCK
- USER CODE
- POWER LEVEL
- ASSOCIATION
- ASSOCIATION GROUP INFO
- NOTIFICATION/ALARM
- CONFIGURATION
- TIME PARAMETERS
- DOOR LOCK LOGGING
- ANTITHEFT

Event Notifications:

- Manual Lock Operation
- Manual Unlock Operation
- RF Lock Operation
- RF Unlock Operation
- Keypad Lock Operation (with user ID info)
- Keypad Unlock Operation (with user ID info)
- RF Not Fully Locked Operation
- Autolock Locked Operation
- Autolock Not Fully Locked Operation
- Lock Jammed
- All User Codes Deleted
- Single User Code Deleted (with user ID)
- New User Code Added (with user ID)
- New User Code Not Added, Duplicate
- New User Code Id Entered (with user ID)
- Entered Access Code Exceeds Code Limit
- Unlock By RF, Invalid User Code
- Locked By RF, Invalid User Code
- Battery Alarm
- Tamper Alarm

SMARTCODE 888
TOUCHPAD ELECTRONIC DEADBOLT
With Z-Wave® 500 Chipset

