

Kwikset

SMARTCODE 888

TOUCHPAD ELECTRONIC DEADBOLT

With Z-Wave® 500 Chipset



Features

- 5-Button keypad with one-touch locking
- Sleek, all metal design
- Z-Wave® 500 for extended wireless range, over-the-air firmware updates and superior wireless encryption

User Codes

- Up to 30 user codes
- Send access codes to family and guests
- MasterCode feature for improved user code management

Connected Benefits

- Lock/Unlock your doors from anywhere
- View lock status and receive notifications of your lock's activity
- Connect to other devices in the home and create scenes driven by the door lock

■ Finishes



Lifetime Polished Brass - L03



Satin Nickel - 15



Venetian Bronze - 11P

■ Specifications

Function	Single cylinder deadbolt
Door Prep	2 1/8" diameter face hole & 1" diameter latch hole
Backset	Adjustable 2 3/8" or 2 3/4"
Door Thickness	1 3/8" - 1 3/4" automatic adjustment
Faceplates	1" x 2 1/4" round corner standard
Strikes	Round corner strike 2 3/4" x 2 1/8"
Latch	Round corner adjustable 2 3/8" x 2 3/4"
Bolt	1" throw, steel deadbolt
Door Handing	Reversible
Cylinder	SmartKey™

Wireless Protocol Z-Wave 500; lock complies with Z-Wave standard of open air, line of sight transmission of 160 feet or more. Compliant with FCC Part 15. Industry Canada.

**Range may vary depending on radio frequency environment. Work with your home control platform to optimize range.*

■ Easy Installation

- Replaces existing deadbolt with just a screwdriver
- No hard wiring needed
- Operates on 4 AA batteries that will last for approximately 1 year


■ Warranty

- Lifetime mechanical and finish warranty
- 1 year electronics warranty

■ Innovative Security

- BHMA Grade 3 certified
- Full 128-bit encryption security
- Featuring SmartKey Security™
- Revolutionary tapered deadbolt design—enables misaligned doors to lock without pulling and pushing your door shut

■ Dimensions



Design	A	B	C	D
SmartCode™ 888 Interior	2 23/32" (69.1 mm)	5 25/32" (146.6 mm)	1 15/16" (49.5 mm)	4 19/32" (116.5 mm)
SmartCode™ 888 Exterior	2 21/32" (67.4 mm)	4 19/32" (116.3 mm)	1 3/16" (29.8 mm)	---