



CON-COIL™

Condenser Coil Cleaner

[Description](#) | [Characteristics](#) | [Applications](#) | [Packaging](#) | [Instructions](#) | [Precautions](#) | [Specifications](#) | [Limited Warranty](#)

DESCRIPTION:

Con-Coil™ is an acid based foaming brightener and cleaner for finned, air-cooled condenser coils. It's penetrating, surfactant aided, foaming action lifts obstructing contaminants such as bugs, cotton-wood, grass, lint, dirt and oxides from coils. Con-Coil™ can also be used for cleaning electronic air filters.

[Top of Page](#)

CHARACTERISTICS:

- Foaming action lifts dirt, lint and oxides from coils and disperses it so coils can be rinsed clean with water
- Concentrated - dilute with water for economical use
- Leaves aluminum surfaces not only bright and shiny, but completely clean and insulation free in less than five minutes
- Will not harm copper or aluminum

[Top of Page](#)

APPLICATIONS:

Con-Coil™ may be safely used on aluminum and copper and will not cause damage if used as directed.

For industrial use only by trained professional personnel.

[Top of Page](#)

PACKAGING:

Code	Size	Qty. Per Case	Lbs. per Case	Cu. Ft Per Case
82622	Gallon (3.8 L)	4 bottles	40	1.21
82624	5 Gallons (18.9 L)	1 pail	53	1.10
82628	55 Gallons (208 L)	1 drum	612	9.01

[Top of Page](#)

INSTRUCTIONS:

READ ALL DIRECTION AND WARNINGS ON LABEL BEFORE USING

CONCENTRATE

1. Dilute Con-Coil™ with 3 parts of water.
2. Shut off system.
3. AVOID BACKSPRAY FROM WIND OR HIGH PRESSURE WASHERS.
4. **CAUTION: This product may cause severe burns to eyes, skin and mucous membranes. Wear protective eye wear and rubber gloves. KEEP OUT OF REACH OF CHILDREN.**
5. Spray the diluted Con-Coil™ on accessible areas. Use a low pressure all plastic sprayer.
6. Wait 30 seconds and spray again.
7. To penetrate a multi-bank coil spray again in 2 minutes.
8. Allow 5 minutes for full cleaning action.
9. Rinse coils and surrounding area off with water.

For additional technical information, call Toll Free 1-800-231-3345.

[Top of Page](#)

PRECAUTIONS:

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,

CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300



DANGER POISON!

MAY BE HARMFUL OR FATAL IF SWALLOWED

HARMFUL TO THE EYES

CONTAINS: Hydrofluoric and Phosphoric Acid. PRECAUTIONS:

Corrosive - may cause burns to any body surface contacted. Burns may not be immediate and may take up to 48 hours to appear. Swallowing is harmful and may be fatal. Avoid breathing fumes, direct contact and do not ingest. Wear adequate protective clothing and safety equipment. Use only with good ventilation and where clean water is quickly available for flushing. Wash thoroughly after use. **FIRST AID:** For any overexposure, get immediate medical attention after first aid is given. **Eyes and Skin** - Flush with large amounts of clean water for at least 15 minutes. **Inhalation** - Remove to fresh air. Give oxygen or artificial respiration if needed. **Ingestion** - Only if conscious, give large amounts of water, then milk of magnesia. **DO NOT INDUCE VOMITING.** **FIRE AND SPILLS:** For fire, use water fog, CO₂, foam or dry chemicals to extinguish. For spills, shut off ignition sources, ventilate confined areas and wipe up with absorbent materials to prevent footing hazard. **STORAGE AND HANDLING:** Store in cool place away from all food. Keep container upright and tightly closed when not in use. Do not reuse empty container. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Material Safety Data Sheet.

[Top of Page](#)

SPECIFICATIONS:

Wt/Gal @ 77 degree F	10.0+-0.5 lbs/gal.
Flash Point SETA CC	None

Color	Pink
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

[Top of Page](#)

LIMITED WARRANTY:

RectorSeal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.

[Top of Page](#)

MANUFACTURED BY

RectorSeal®

2601 Spenwick Drive • Houston, TX 77055 USA
713-263-8001 • Fax 713-263-7577
Toll-free 800-231-3345 • Fax 800-441-0051

[Back](#)