



## Quick-N-EZ Impact Bullet Puller



Collet #1 (1 Groove)





**O-Ring** 

Head

Cap

Collet #3 (No Grooves)


Collet #2

(2 Grooves)



See below for applications.

**Typical Cartridge Case / Collet Assembly** 



Impact Surface Only strike impact surface against hardwood



Collet #1 (1 Groove)
.17 Remington
.218 Bee
.22 Hornet
.222 Remington
.223 Remington

.30 Carbine	
.32 Auto	_
.32-20 Winchester	
380 Auto/9mm Luger/	

.38 Super/.40 S&W/10mm

.25 Auto

See Reverse Side for Additional Instructions



Collet#2(2Grooves)
22 Jet/38 Special/
357 Magnum/357 Maximum
25-35 Winchester
250 Savage
257 Roberts
25-06 Rem/270 Win/
280 Rem/30-06/243 Win/
7mm-08 Rem/308 Win/
.358 Win/.45 ACP & 240 Win.
30 Remington
30-30 Winchester
7.62x39

257 Roberts
25-06 Rem/270 Win/
280 Rem/30-06/243 Win/
7mm-08 Rem/308 Win/
358 Win/.45 ACP & 240 Win.
30 Remington
30-30 Winchester
7.62x39
32 Winchester
35 Remington
38-40Win/.44-40Win/
.41 Mag/.44 Spl/.44 Mag.
.45 Auto Rim
.45 Long Colt

Collet #3 (No Grooves)
.264 Win/.7mm Rem. Mag/.300
Win. Mag J.338 Win. Mag J.375
H&H/.458 Win. Mag./ All
Weatherby Mag Calibers Except
.378, .416 & .460
.33 Winchester
.348 Winchester
.444 Marlin
.45-70 Govt.
50-70 Govt.

See Reverse Side for Additional Instructions





## **A** WARNING:

Using this Bullet Puller to pull certain types of ammunition can result in a cartridge explosion with the potential for serious personal injury and/or property damage.

- Do not attempt to disassemble bullets from rimfire ammunition
- Do not attempt to disassemble any ammunition identified as "Explosive", "Observation" or "Incendiary".
- Do not attempt to disassemble any cartridge with a high primer
- Do not attempt to disassemble ammunition loaded with black powder
- Do not attempt to disassemble any cartridge whose projectile or powder cannot be positively identified.
- Do not attempt to disassemble factory ammunition where bullet sealant has been used.

## **Instructions For Use:**

## **A** WARNING:

Read these instructions in their entirety. Failure to heed these instructions could result in a cartridge explosion and/or flying debris with the potential for serious personal injury and/or property damage.

The Frankford Arsenal Quick-N-EZ Bullet Puller is designed to pull bullets from reloaded ammunition. Three separate collet assemblies are provided to accommodate most centerfire calibers; see chart on the reverse side for collet application.



Always wear safety glasses while using the Bullet Puller or any other tool while reloading ammunition.

Remove the screw on cap and select the appropriate collet set from the chart listings on the other side.

Secure collet set with an O-ring (as shown in Figure 1 on other side) with rounded edge up. Place assembled collet set over hole in top of Bullet Puller and screw cap on loosely.



Ensure rounded edge of collet is up as shown.

Insert cartridge with a rotary motion until case rim seats against the collet, or the extractor groove engages the collet.



For belted ammunition, it may be necessary to manually slide collet over cartridge to ensure case rim seats against the collet or extractor groove engages the collet.

Tighten cap firmly.



Do not use heavy blows to remove a bullet. A series of short, sharp impacts will remove most bullets effectively.

Strike the Bullet Puller against a hard wood surface, while holding the Bullet Puller handle parallel to the surface and the Bullet Puller head perpendicular to the surface at the time of impact. Let the bullet puller bounce back after impact. This technique will give the maximum inertia to the bullet being pulled. Two or three impacts should pull most bullets.

Never strike the Bullet Puller against steel or concrete. Only use a hard, wood surface. The best hard surface to use is the "end grain" of a block of wood.

Check the tightness of the cap after each blow.